



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** BEDDING PLASTER VF
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Levelling
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Fescon Oy
Hämeenkatu 9
FI-05820 Hyvinkää - Suomi - Finland
Phone.: +358 (0)20 789 5900 - Fax: +358 (0)20 789 5909
fescon@fescon.fi
www.fescon.fi
- 1.4 Emergency telephone number:** 112

SECTION 2: HAZARDS IDENTIFICATION **

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Eye Dam. 1: Serious eye damage, Category 1, H318
Skin Irrit. 2: Skin irritation, Category 2, H315
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Danger
-
- Hazard statements:**
Eye Dam. 1: H318 - Causes serious eye damage
Skin Irrit. 2: H315 - Causes skin irritation
STOT SE 3: H335 - May cause respiratory irritation
- Precautionary statements:**
P102: Keep out of reach of children
P261: Avoid breathing dust/fume/gas/mist/vapours/spray
P280: Wear protective gloves/protective clothing/eye protection/face protection
P284: Wear respiratory protection
P302+P352: IF ON SKIN: Wash with plenty of water
P304+P341: IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P312: Call a POISON CENTER/doctor if you feel unwell
P333+P313: If skin irritation or rash occurs: Get medical advice/attention
P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment
- Substances that contribute to the classification**
Cement, portland, chemicals
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria

** Changes with regards to the previous version

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**

- CONTINUED ON NEXT PAGE -



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Non-applicable

3.2 Mixture:

Chemical description: Inorganic compounds

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification | Chemical name/Classification | Concentration |
|---|--|----------------------|
| CAS: 65997-15-1 EC: 266-043-4 Index: Non-applicable REACH: Non-applicable | Cement, portland, chemicals <input type="checkbox"/> ¹ <input type="checkbox"/> | Self-classified |
| | Regulation 1272/2008 Eye Dam. 1: H318; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger | 10 - <25 % |
| CAS: 68475-76-3 EC: 270-659-9 Index: Non-applicable REACH: 01-2119486767-17-XXXX | Flue dust, portland cement <input type="checkbox"/> ¹ <input type="checkbox"/> | Self-classified |
| | Regulation 1272/2008 Eye Dam. 1: H318; Skin Irrit. 2: H315; Skin Sens. 1: H317 - Danger | <1 % |
| CAS: 108-05-4 EC: 203-545-4 Index: 607-023-00-0 REACH: 01-2119471301-50-XXXX | Vinyl Acetate <input type="checkbox"/> ² <input type="checkbox"/> | ATP ATP05 |
| | Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H351; Flam. Liq. 2: H225; STOT SE 3: H335 - Danger | <1 % |

¹ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

² Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 8, 11, 12, 15 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems. IT IS NOT RECOMMENDED to use tap water as an extinguishing agent.

- CONTINUED ON NEXT PAGE -



SECTION 5: FIREFIGHTING MEASURES (continued)

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Sweep up and shovel product or collect by other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Use in ventilated areas. Avoid the build up of dust

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, handling and use.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

Keep the container tightly sealed and protected from open air and humidity.

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

- CONTINUED ON NEXT PAGE -



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Substances whose occupational exposure limits have to be monitored in the workplace

| Identification | Environmental limits | | |
|--|----------------------|--------|------------------------|
| | IOELV (8h) | 5 ppm | 17.6 mg/m ³ |
| Vinyl Acetate CAS: 108-05-4 EC: 203-545-4 | IOELV (STEL) | 10 ppm | 35.2 mg/m ³ |

Nuisance dust: Inhalable dust 10 mg/m³ // Respirable dust 4 mg/m³

DNEL (Workers):

| Identification | | Short exposure | | Long exposure | |
|--|------------|------------------------|------------------------|------------------------|------------------------|
| | | Systemic | Local | Systemic | Local |
| Flue dust, portland cement CAS: 68475-76-3 EC: 270-659-9 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | 4 mg/m ³ | Non-applicable | 1 mg/m ³ |
| Vinyl Acetate CAS: 108-05-4 EC: 203-545-4 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | 0,42 mg/kg | Non-applicable |
| | Inhalation | 35,2 mg/m ³ | 35,2 mg/m ³ | 17,6 mg/m ³ | 17,6 mg/m ³ |

DNEL (General population):

| Identification | | Short exposure | | Long exposure | |
|--|------------|----------------|---------------------|----------------|---------------------|
| | | Systemic | Local | Systemic | Local |
| Flue dust, portland cement CAS: 68475-76-3 EC: 270-659-9 | Oral | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Dermal | Non-applicable | Non-applicable | Non-applicable | Non-applicable |
| | Inhalation | Non-applicable | 4 mg/m ³ | Non-applicable | 1 mg/m ³ |

PNEC:

| Identification | | Short exposure | | Long exposure | |
|--|--------------|----------------|-------------------------|---------------|-------|
| | | Systemic | Local | Systemic | Local |
| Flue dust, portland cement CAS: 68475-76-3 EC: 270-659-9 | STP | 6 mg/L | Fresh water | 0,028 mg/L | |
| | Soil | 5 mg/kg | Marine water | 0,003 mg/L | |
| | Intermittent | 0,282 mg/L | Sediment (Fresh water) | 0,875 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 0,088 mg/kg | |
| Vinyl Acetate CAS: 108-05-4 EC: 203-545-4 | STP | 6 mg/L | Fresh water | 0,016 mg/L | |
| | Soil | 0,0035 mg/kg | Marine water | 0,0016 mg/L | |
| | Intermittent | 0,126 mg/L | Sediment (Fresh water) | 0,067 mg/kg | |
| | Oral | Non-applicable | Sediment (Marine water) | 0,0067 mg/kg | |

8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|--|-----------|--|---|
| | Filter mask for gases, vapours and particles | | EN 149:2001+A1:2009 EN 405:2001+A1:2009 | Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. |

C.- Specific protection for the hands

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|---------------------------------------|-----------|--------------|---|
| | Protective gloves against minor risks | | | Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420 and EN 374. |



- CONTINUED ON NEXT PAGE -





SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"



D.- Ocular and facial protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|--|---|---|---------------------------------|---|
|  Mandatory face protection | Panoramic glasses against splash/projections. |  | EN 166:2001 EN ISO 4007:2012 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Body protection

| Pictogram | PPE | Labelling | CEN Standard | Remarks |
|-----------|----------------------|---|-------------------|---|
| | Work clothing |  | | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2001, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994. |
| | Anti-slip work shoes |  | EN ISO 20347:2012 | Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345 y EN 13832-1 |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|--------------------------------|--|-------------------------------|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2002 |  Eyewash stations | DIN 12 899 ISO 3864-1:2002 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

Appearance:

| | |
|--------------------------|------------------|
| Physical state at 20 °C: | Solid |
| Appearance: | Powdery |
| Colour: | Characteristic |
| Odour: | Characteristic |
| Odour threshold: | Non-applicable * |

Volatility:

| | |
|--|------------------|
| Boiling point at atmospheric pressure: | Non-applicable * |
| Vapour pressure at 20 °C: | Non-applicable * |
| Vapour pressure at 50 °C: | Non-applicable * |
| Evaporation rate at 20 °C: | Non-applicable * |

Product description:

| | |
|-------------------------------|------------------|
| Density at 20 °C: | Non-applicable * |
| Relative density at 20 °C: | Non-applicable * |
| Dynamic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 20 °C: | Non-applicable * |
| Kinematic viscosity at 40 °C: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

| | |
|--|------------------|
| Concentration: | Non-applicable * |
| pH: | 11 - 13 |
| Vapour density at 20 °C: | Non-applicable * |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable * |
| Solubility in water at 20 °C: | Non-applicable * |
| Solubility properties: | Non-applicable * |
| Decomposition temperature: | Non-applicable * |
| Melting point/freezing point: | Non-applicable * |
| Explosive properties: | Non-applicable * |
| Oxidising properties: | Non-applicable * |
| Flammability: | |
| Flash Point: | Non-applicable |
| Flammability (solid, gas): | Non-applicable * |
| Autoignition temperature: | Non-applicable * |
| Lower flammability limit: | Non-applicable * |
| Upper flammability limit: | Non-applicable * |
| Explosive: | |
| Lower explosive limit: | Non-applicable * |
| Upper explosive limit: | Non-applicable * |
| 9.2 Other information: | |
| Surface tension at 20 °C: | Non-applicable * |
| Refraction index: | Non-applicable * |

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|------------|---------------------|
| Not applicable | Not applicable | Precaution | Precaution | Avoid direct impact |

10.5 Incompatible materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------|--|---------------------|-----------------------|---|
| Incompatible | Silicate formation and calcium hydroxide | Avoid direct impact | Not applicable | Base metal salts (Al, NH ₄ ,...) |

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with carcinogenic effects. For more information see section 3.
IARC: Vinyl Acetate (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Contact with human skin, without adequate protection, can result in skin thickening, cracking, or fissuring

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|----------------|-----------------|----------------|--------|
| | LD50 oral | LD50 dermal | |
| Vinyl Acetate | 2920 mg/kg | 2340 mg/kg | Rat |
| CAS: 108-05-4 | | | Rabbit |
| EC: 203-545-4 | LC50 inhalation | Non-applicable | |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

- CONTINUED ON NEXT PAGE -



SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification | Acute toxicity | | Species | Genus |
|---|----------------|------------------|---------------------------------|------------|
| Vinyl Acetate CAS: 108-05-4 EC: 203-545-4 | LC50 | 31.1 mg/L (96 h) | Lebistes reticulatus | Fish |
| | EC50 | 12.6 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 12.7 mg/L (72 h) | Pseudokirchneriella subcapitata | Algae |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradability | |
|---|---------------|----------------|------------------|----------|
| Vinyl Acetate CAS: 108-05-4 EC: 203-545-4 | BOD5 | Non-applicable | Concentration | 100 mg/L |
| | COD | Non-applicable | Period | 14 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 98 % |

12.3 Bioaccumulative potential:

| Identification | Bioaccumulation potential | |
|---|---------------------------|------|
| Vinyl Acetate CAS: 108-05-4 EC: 203-545-4 | BCF | 3 |
| | Pow Log | 0.73 |
| | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|---|-----------------------|----------------------|------------|-----------------------------|
| Vinyl Acetate CAS: 108-05-4 EC: 203-545-4 | Koc | 24 | Henry | 56,1 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | Yes |
| | Surface tension | 2,399E-2 N/m (25 °C) | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

| Code | Description | Waste class (Regulation (EU) No 1357/2014) |
|-----------|--|--|
| 16 03 03* | inorganic wastes containing hazardous substances | Dangerous |

Type of waste (Regulation (EU) No 1357/2014):

HP4 Irritant — skin irritation and eye damage, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

- CONTINUED ON NEXT PAGE -



SECTION 15: REGULATORY INFORMATION (continued)

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable
Article 95, REGULATION (EU) No 528/2012: Non-applicable
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

1. Cement and cement-containing mixtures shall not be placed on the market, or used, if they contain, when hydrated, more than 2 mg/kg (0,0002 %) soluble chromium VI of the total dry weight of the cement.
2. If reducing agents are used, then without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances and mixtures, suppliers shall ensure before the placing on the market that the packaging of cement or cement-containing mixtures is visibly, legibly and indelibly marked with information on the packing date, as well as on the storage conditions and the storage period appropriate to maintaining the activity of the reducing agent and to keeping the content of soluble chromium VI below the limit indicated in paragraph 1.
3. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for, and use in, controlled closed and totally automated processes in which cement and cement-containing mixtures are handled solely by machines and in which there is no possibility of contact with the skin.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):
· Supplementary information

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation
H318: Causes serious eye damage
H335: May cause respiratory irritation

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H332 - Harmful if inhaled
Carc. 2: H351 - Suspected of causing cancer
Eye Dam. 1: H318 - Causes serious eye damage
Flam. Liq. 2: H225 - Highly flammable liquid and vapour
Skin Irrit. 2: H315 - Causes skin irritation
Skin Sens. 1: H317 - May cause an allergic skin reaction
STOT SE 3: H335 - May cause respiratory irritation

Classification procedure:

Skin Irrit. 2: Calculation method
Eye Dam. 1: Calculation method
STOT SE 3: Calculation method

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

- CONTINUED ON NEXT PAGE -



SECTION 16: OTHER INFORMATION (continued)

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5-day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
Log-POW: Octanol-water partition coefficient
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -