

Product catalog 2024





Fescon Oy head office

Fescon Oy

Hämeenkatu 9, 05800 HYVINKÄÄ

Tel. +358 20 789 5900

fescon@fescon.se

Business ID: 0560006-4

Emails: förnamn.efternamn@fescon.fi

Regions 1-3

Hausjärvi factory

Hikiäntie 1336, 05820 HYVINKÄÄ

Tel. +358 20 789 5911

tilaukset@fescon.fi

Region 4

Haukipudas factory

Topinperäntie 102, 90820 KELLO

Tel. +358 8 563 4440

haukipudas.tilaukset@fescon.fi

Bulk sand orders

Raahe factory

Kalkankatu 6, 92150 RAAHE

Tel. +358 20 789 5930

hiekkatilaukset@fescon.fi

Harjavalta factory

Hiisikuja, 29200 HARJAVALTA

Tel. +358 20 789 5930

hiekkatilaukset@fescon.fi

Hausjärvi factory

Hikiäntie 1336, 05820 HYVINKÄÄ

Tel. +358 20 789 5930

hiekkatilaukset@fescon

Nanten floor coatings

Tuusula factory

Teollisuuskatu 6, 04300 TUUSULA

Tel. +358 9 274 7970

nanten@fescon.fi

Sales - region 1

Plaster business

Hardware sales

Jori Leskinen Tel. +358 40 301 6053

Project sales of façade products and concrete repair products

Uusimaa | Lahti | Tampere | Turku

Eetu Jäntti Tel. +358 40 301 6031

Project sales of façade products and concrete repair products

Keijo Neffling Tel. +358 50 404 9371

Project sales of façade products and concrete repair products

Timo Lehtimaa Tel. +358 50 301 6024

Levelling and tiling products, contractor sales

Mikko Rahkala Tel. +358 40 301 6042

Masonry mortars, dry concrete, construction company sales

Jani Jokinen Tel. +358 40 301 6027

Masonry mortars, dry concrete, construction company sales

Uusimaa | Lahti | Tampere

Janette Niskala Tel. +358 40 301 6054

Nanten floor coatings

Project sales

Architects and designers

Jarno Helisma Tel. +358 40 902 2323

Project sales

Tomi Pennanen Tel. +358 0 374 4388

Throughout Finland

Pumpable floor levelling products, dry hardeners and hard concrete

Juha Pirhonen Tel. +358 50 301 6057

Façade solutions, industrial clients and designers

Mikko Syrjänen Tel. +358 400 178 897

Sales - region 2

All Fescon products

Sakari Kaukonen Tel. +358 40 301 6030

Nanten floor coatings

Project sales

Architects and designers

Pasi Heinonen Tel. +358 50 431 8267

Sales - region 3

All Fescon products

Elina Vuori Tel. +358 40 831 1358

Nanten floor coatings

Project sales

Architects and designers

Pasi Heinonen Tel. +358 50 431 8267

Sales - region 4

All Fescon products

Kai Saastamoinen Tel. +358 40 301 6019

Nanten floor coatings

Projektförsäljning Project sales

Architects and designers

Kimmo Väänänen Tel. +358 44 744 0884

Sales - Throughout Finland

Sand business

Sands, blasting and power plant materials

Eero Majanen Tel. +358 40 506 9021

Power plant materials and technology services

Tapio Klasila Tel. +358 40 150 8035

Sands, blasting and sports field materials

Tomi Koota Tel. +358 40 128 1883



Plaster products

Tel. +358 20 789 5901



Power plant materials and technology services

Tapio Klasila Tel. +358 40 150 8035



Sand products

Tomi Koota Tel. +358 40 128 1883



Nanten floor coatings

Tel. +358 9 274 7970

The background of the lower half of the page is split vertically. The left side shows a close-up of a light-colored, textured surface, possibly concrete or stone. The right side is a solid, deep red color.

fescon

Master of Materials

Fescon Oy general delivery terms and conditions 2024

SCOPE These terms and conditions apply to the domestic trade of products in the Fescon price list and those made to order. To the extent that the trade-related issues have not been otherwise agreed in these terms of delivery or separately, the general procurement and delivery terms for construction products (RYHT) shall be respected.

PRICE Invoicing is done on the date of delivery at the valid price excluding tax. Value added tax is added to the sum total of the invoice. Fescon Oy reserves the right to introduce a possible energy surcharge if energy costs increase significantly after the publication of the price list.

TERM OF DELIVERY Free carrier at the factory indicated in the price list (FCA, Finnterms 2001). Transports arranged by Fescon Oy will be charged in accordance with a separate transport price list. Sand deliveries under a separate agreement either FCA or DAP (Finnterms 2001). Pick-up of Nanten products according to a separate agreement.

PRODUCTS MADE TO ORDER Orders for special products and products made to order are binding on the buyer. The buyer is obliged to receive and pay for the products made to order that the buyer has ordered. Fescon is entitled to charge the price and disposal costs of the product from the buyer if the buyer does not receive the products within the schedule indicated in the order confirmation.

TIME OF DELIVERY Products in stock in Hausjärvi and Haukiputaa, delivered either on full pallets or in large bags, can be picked up at the warehouse three (3) hours after placing the order at the customer service centre.

Pick up of products in stock in partially full pallets: Can be picked up from the factory 1 working day after ordering.

Products made to order can be picked up from the factory:

- grey and fireproof products and sand products 10 business days after the order
- coloured products 10 business after the order
- liquid facade products delivered within 15 business days of placing the order
- rendering materials and other accessories according to agreement

In site deliveries organized by Fescon Oy, the transport time from the factory to the site is 1–5 business days.

Work-site silos are delivered according to separate agreement and terms of delivery. The availability of work-site silos must be ensured on a site-specific basis. The binding delivery and return date of a silo must be communicated and confirmed six weeks before the delivery.

PALLET SIZES AND PRICING The products are packaged on pallets, which are EUR-pallets in size 800 x 1,200 mm. The number of bags per pallet depends on the product and is indicated in the price list. The price is € 12.00 per pallet, excl. VAT. The price is valid until further notice. If the delivery method requires a pallet under each large bag, we charge the customer for the pallets in accordance with the currently valid pallet price list. Fescon does not accept pallets or make a refund for any.

ADDITIONAL FEE FOR COLLECTION / INCOMPLETE PALLET A fee of € 15.00/delivery (VAT 0%) is charged for incomplete pallets and pallets that contain several products. This does not apply to product groups 7, 9–13. Only full pallets are delivered from Harjavalta and Raahel.

COMPLAINTS AND DAMAGES The buyer must inspect the goods delivered to the buyer immediately and report any faults and deficiencies without delay, and at the latest within eight (8) days of receiving them by indicating this in the waybill or using another method in writing. Errors that are noticeable only when using the product must be reported immediately before starting any casting, rendering, masonry or other use of the product. Fescon shall not be liable for any damage caused if the buyer has not made the said claims within the time limit and/or the buyer has taken the product into use contrary to the foregoing.

The buyer must approve the tinted colour model delivered to the work site for the coloured façade products before ordering the actual product. Otherwise, Fescon will not be liable for any errors related to or resulting from the colour.

INSTRUCTIONS Before using the product, consult the product packaging and product specifications for more detailed instructions for use. Detailed product information is available at www.fescon.fi

LIABILITIES OF THE SUPPLIER AND BUYER In addition to what is stated in the RYHT terms, Fescon Oy's liability for the product is limited to the information provided on the product datasheet, and matters excluded from liability comprise the structures, the events during storage and processing, interaction with other products and any conditions with local effect. The buyer must note that the information reported on the product datasheet has been measured under standardised laboratory conditions. The selection of the product and the choices related to the use of the product shall be made project-specifically, taking into account the entire structure. If the product is to be used as part of a Fescon solution or system, the project structure must be formed in accordance with the instructions of the relevant system.

LIMITATION OF LIABILITY Fescon shall not be liable for any consequential or indirect damages caused by a defect of the product or for any damages that are not foreseeable, unless Fescon has acted in a grossly negligent manner. In addition, Fescon's maximum liability to payment of compensation for any direct damages in all situations shall not exceed 500,000 euros, unless Fescon has acted in a grossly negligent manner.

WARRANTY PERIOD Fescon's liability shall be limited to the errors for which the buyer has filed a complaint in writing within two years the delivery of the product. Tools have a warranty period of 12 months, but this does not extend to normal wear and tear.

RETURNS We cannot accept returns.

CHANGES Fescon reserves the right to changes in the price list and the terms of delivery.

DISPUTES Any disputes arising out of the trade, which cannot be settled in mutual negotiations between Fescon and the buyer are to be resolved permanently by a sole-arbitrator arbitration tribunal in accordance with the arbitration rules of the Central Chamber of Commerce. The arbitration procedure is to be held in Finnish and in the jurisdiction of Helsinki. However, without prejudice to the foregoing, Fescon shall have the right to bring an action for claims before a court of general jurisdiction.

Table of contents

1	Dry concretes and cement plasters	7
2	Fireplace mortars	15
3-4	Masonry mortars	17
5	Wall leveling compounds	27
6	Floor leveling products	32
7	Tiling plaster and waterproofing products	39
8	Plasters	47
9	Products for the repair of concrete surfaces and infrastructure construction	51
10	Mineral coatings and thin plaster	57
11	Mineral based facade paints	61
12	Liquid facade paints and coatings	62
13	Fescoterm plastering accessories	67
14	Sands	79
15	Fescotop floor hardeners	89
16	Tools	92

1 DRY CONCRETES AND CEMENT PLASTERS

Thin plaster S 06

For the repair and patching of casting defects, and the repair and surface patching of concrete walls and roofs. Maximum grain size 0.6 mm. Ready-to-apply compound 13-14 l/25 kg.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530189	Thin plaster S 06	53018	25 kg	48 sk	x	-

x = stock product

Cement plaster S 30

Suitable for casting thin surface flooring and corridor tiles, and the repair of casting defects and concrete structures. Maximum grain size 3 mm. Strength class C 30/37. Ready-to-apply compound 12-13 l/25 kg. Frost-resistant



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530202	CEMENT PLASTER S 30	53020	25 kg	48 sk	x	x
6416841330208	CEMENT PLASTER S 30	33020	1000 kg		x	x

x = stock product



Winter concrete TB S 30 ❄️

Special concrete for grouting and concrete work. Frost-resistant Largest grain size 3 mm. Strength class C 30/37. Ready-to-apply compound ca. 500 l/1000 kg. Working temperature -15°C...+5°C.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530042	Winter concrete TB S 30	53004	25 kg	48 sk	x	x
6416841330048	WINTER CONCRETE TB S 30	33004	1000 kg		x	x

x = stock product



Corro concrete K 45

Special concrete C 35/45 strength class casting. Frost-resistant Good wear resistance and tightness. Maximum grain size 3 mm. Ready-to-apply compound 11-12 l/25 kg. Grain size 10 mm also available to order (only in 1000 kg packages).

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530264	Corro concrete K 45	53026	25 kg	48 sk	x	-
6416841330260	CORRO CONCRETE K 45	33026	1000 kg		x	-

x = stock product

Corro concrete SR C35/45 **NEW!**

Fescon Corro Concrete SR C35/45 is a high-strength, salt and frost resistant specialty concrete with sulphate resistant cement as binding agent. Suitable for applications requiring wear-resistant and corrosion-resistant tightly sealed concrete surfaces. Applications include e.g. casting, repairing and reinforcing concrete structures, such as balcony slabs, maritime port facilities, parking garages or industrial construction. The strength class C 35/45 according to concrete standard SFS EN 206-1. The maximum grain size of the product is 4.0 mm. Minimum delivery batch is 3 big bags.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841332042	Corro concrete SR C35/45 1000 kg	33204	1000 kg		-	-

x = stock product

Cement concrete S 100

Basic concrete for general casting work. Maximum grain size 10 mm. Compressive strength around 25 MPa. Ready-to-apply compound 12-13-25 l/25 kg. Frost-resistant



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530219	CEMENT CONCRETE S 100	53021	25 kg	48 sk	x	x
6416841330963	CEMENT CONCRETE S 100	33096	500 kg		x	x
6416841330215	CEMENT CONCRETE S 100	33021	1000 kg		x	x

x = stock product



Grouting concrete JB 600/3

High-strength concrete that expands before setting, intended for grouting and supplementary casting in narrow and difficult spaces. The main applications are installation and jointing casting of pre-cast concrete elements and various anchor grouts. Maximum grain size 3 mm. Strength class C 50/60. SILKO-approved. Ready-to-apply compound 11-12-25 l/25 kg. Meets the requirements of the R4 class.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530226	GROUTING CONCRETE JB 600/3	53022	25 kg	48 sk	x	x
6416841330222	GROUTING CONCRETE JB 600/3	33022	1000 kg		x	x

x = stock product



Grouting concrete JB 1000/3

A very high-quality concrete for demanding precision casting, such as the fastening and installation castings of machinery. Due to slight expansion that takes place before setting, the concrete fills the casting space well. Largest grain size 3 mm. Strength class C 60/75. Ready-to-apply compound 11-12 l/25 kg. SILKO-approved. Meets the requirements of the R4 class.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530233	GROUTING CONCRETE JB 1000/3	53023	25 kg	48 sk	x	-
6416841330239	GROUTING CONCRETE JB 1000/3	33023	1000 kg		x	-

x = stock product

Grouting concrete SR JB 1000/3 **NEW!**

High-strength, salt and frost resistant special concrete with sulphate resistant cement as binding agent. Due to its slight swelling before binding, it fills the casting space effectively. Applications include demanding precision castings, narrow-space and difficult post-work and filling castings, installation and sealing castings of concrete elements and anchoring solders. The strength class C 60/75 according to concrete standard SFS EN 206-1. The maximum grain size of the product is 4.0 mm. Minimum delivery batch is 3 big bags.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841332080	Grouting concrete SR JB 1000/3 1000 kg	33208	1000 kg		-	-

x = stock product

Grouting concrete TJB Winter ❄️

Special concrete that expands before setting for grouting and small-scale concrete work and anchor grouting. Maximum grain size 3 mm. Strength class C40/50. Ready-to-apply compound 11-12 l/25 kg. Working temperature -15°C...+5°C.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530141	GROUTING CONCRETE TJB WINTER	53014	25 kg	48 sk	x	x
6416841330147	GROUTING CONCRETE TJB WINTER	33014	1000 kg		x	x

x = stock product

Vertical-joint concrete PSB K30

Non-draining, pumpable special concrete for vertical and horizontal jointing of concrete elements. Largest grain size 4 mm. Ready-to-apply compound approx 500 l/1000 kg. Strength class C 25/30.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330352	VERTICAL-JOINT CONCRETE PSB K 30	33035	1000 kg		x	x

x = stock product



Vertical-joint concrete winter TPSB K30

Non-draining, pumpable special concrete for vertical and horizontal jointing of concrete elements in winter conditions. Largest grain size 4 mm. Ready-to-apply compound ca. 500 l/1000 kg. Working temperature -15°C...+5°C. Strength class C 25/30.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330369	VERTICAL-JOINT CONCRETE WINTER TPSB K30	33036	1000 kg		x	x

x = stock product



Vertical-joint concrete PSB K40

Non-draining, pumpable special concrete for vertical and horizontal jointing of concrete elements. Largest grain size 4 mm. Ready-to-apply compound ca. 500 l/1000 kg. Strength class C 30/37.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330031	VERTICAL-JOINT CONCRETE PSB K 40	33003	1000 kg		x	-

x = stock product



Vertical-joint concrete winter TPSB K40

Non-draining, pumpable special concrete for vertical and horizontal jointing of concrete elements in winter conditions. Largest grain size 4 mm. Ready-to-apply compound ca. 500 l/1000 kg. Working temperature -15°C...+5°C. Strength class C 30/37.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330949	VERTICAL-JOINT CONCRETE WINTER TPSB K40	33094	1000 kg		x	-

x = stock product

Vertical-joint concrete PSB K50

Non-draining, pumpable special concrete for vertical and horizontal jointing of concrete elements. Largest grain size 4 mm. Ready-to-apply compound ca. 500 l/1000 kg. Strength class C 40/50.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841333476	VERTICAL-JOINT CONCRETE PSB K 50	33347	1000 kg		-	-

x = stock product

Vertical-joint concrete winter TPSB K45 ❄️

Non-draining, pumpable special concrete for vertical and horizontal jointing of concrete elements in winter conditions. Largest grain size 4 mm. Ready-to-apply compound ca. 500 l/1000 kg. Working temperature -15°C...+5°C. Strength class C 35/45.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841333568	Vertical-joint concrete winter TPSB K45	33356	1000 kg		-	-

x = stock product

Rapid concrete PB

A special concrete with a rapid strength gain that is suited to, for example, repairs of concrete structures, supplementary casting and floor casting. Strength class C 30/37. Largest grain size 3 mm. Ready-to-apply compound 12-13 l/25 kg. Grain size 10 mm also available to order (only 1000 kg package).



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530240	RAPID CONCRETE PB	53024	25 kg	48 sk	x	x
6416841331281	RAPID CONCRETE PB	33128	1000 kg		-	-

x = stock product



Special concrete PIKIS

Cement-based, super fast setting and hardening special concrete. Applications: Repairs of concrete surfaces, quick-casting of poles and structures as well as repairs of concrete wells. Not suitable for load-bearing structures.

					HAUSJÄRVI	HAUKIPUDAS
GTIN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841531070	Special concrete PIKIS 25 kg	53107	25 kg	48 sk	-	-

x = stock product

2 FIREPLACE MORTARS

Clay stove mortar SUL

For the burnt brick masonry of the frame and flues of wood-heated fireplaces indoors. Fireproof mortar must be used in fireplace masonry. Regular masonry mortar is used for the separate shell.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530653	CLAY STOVE MORTAR SUL	53065	25 kg	48 sk	x	x

x = stock product

Fireproof masonry mortar TKM

For laying firebricks used in indoor wood-fired household fireplaces. Heat resistance over +1200°C. A 20 kg bag yields 9,6 - 10,4 litres of finished mortar, which is enough for laying around 80 firebricks.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841630667	FIREPROOF MASONRY MORTAR TKM	63066	5 kg		x	x
6416841531162	Fireproof masonry mortar TKM 20 kg	53116	20 kg	48 sk	x	x

x = stock product

Fireproof casting concrete TKV

For the parts of ovens, fireplaces, grills and sauna stoves that need to be fireproof. Maximum operating temperature +1200°C. Minimum casting thickness 50 mm. Ready-to-apply compound 11-12 l/25 kg. Remains usable for one hour. Do not use reinforcement.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530677	FIREPROOF CASTING CONCRETE TKV	53067	25 kg	48 sk	x	x

x = stock product



Fireproof repairing compound TTK

For patching chips, cracks and cavities in the fire boxes of household fireplaces. Heat resistance +1300°C.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631510	FIREPROOF REPAIRING COMPOUND TTK	63151	2 kg	150 prk	x	x

x = stock product



FPTL-165 Industrial mortar

Chemical-ceramic binding mortar for applications with a temperature of max. +1650°C.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841531094	FPTL-165 Industrial mortar	53109	25 kg	48 sk	-	-

x = stock product

3-4 MASONRY MORTARS

Masonry mortar M100/600

Cement-based mortar for burnt and sand-lime brick masonry outdoors and indoors. For brick work jointing, jointing of natural and slate stones on vertical surfaces and for repairing existing mortar joints. For cold flue parts in chimney masonry, such as in cold attics and above the roof, as well as for the masonry of the outer brick shell of the fireplace. Maximum grain size 2.0 mm. Material usage 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT. Amount of finished mortar: 13 - 14 l / 25 kg.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530387	MASONRY MORTAR 100/600	53038	25 kg	48 sk	x	x
6416841330376	MASONRY MORTAR 100/600	33037	500 kg		x	x
6416841330383	MASONRY MORTAR 100/600	33038	1000 kg		x	x
6416841530394	MASONRY MORTAR 39 QUARTZ WHITE	53039	25 kg	48 sk	x	-
6416841330390	MASONRY MORTAR 39 QUARTZ WHITE	33039	1000 kg		-	-
6416841530592	Masonry mortar 59 Birch bark white	53059	25 kg	48 sk	x	-
6416841330598	Masonry mortar 59 Birch bark white	33059	1000 kg		-	-
6416841530400	Masonry mortar 40 Lime gray	53040	25 kg	48 sk	-	-
6416841330406	Masonry mortar 40 Lime gray	33040	1000 kg		-	-
6416841330413	Masonry mortar 41 Grain yellow	33041	1000 kg		-	-
6416841330420	Masonry mortar 42 Brick red	33042	1000 kg		-	-
6416841330451	Masonry mortar 45 Earth brown	33045	1000 kg		-	-
6416841530462	Masonry mortar 46 Peat brown	53046	25 kg	48 sk	x	-
6416841330468	Masonry mortar 46 Peat brown	33046	1000 kg		-	-
6416841530486	Masonry mortar 48 Black gray	53048	25 kg	48 sk	x	-
6416841330482	Masonry mortar 48 Black gray	33048	1000 kg		-	-
6416841530523	MASONRY MORTAR 52 LINEN LIGHT	53052	25 kg	48 sk	-	-
6416841330529	MASONRY MORTAR 52 LINEN LIGHT	33052	1000 kg		-	-
6416841330444	MASONRY MORTAR 44 SAND BROWN	33044	1000 kg		-	-
6416841339225	MASONRY MORTAR 71 SWAN	33922	1000 kg		-	-
6416841339263	Masonry mortar 72 Below	33926	1000 kg		-	-
6416841339270	MASONRY MORTAR 73 CUCKOO	33927	1000 kg		-	-
6416841339218	Masonry mortar 74 Hawk	33933	1000 kg		-	-
6416841339249	MASONRY MORTAR 75 LARK	33924	1000 kg		-	-

6416841339201	MASONRY MORTAR 77 JACKDAW	33920	1000 kg		-	-
6416841339256	MASONRY MORTAR 79 PTARMIGAN	33925	1000 kg		-	-
6416841339287	MASONRY MORTAR 80 SIBERIAN JAY	33928	1000 kg		-	-
6416841339324	MASONRY MORTAR 81 TEAL	33932	1000 kg		-	-
6416841339218	Masonry mortar 82 Capercaillie	33921	1000 kg		-	-
6416841339362	MASONRY MORTAR 83 WILLOW GROUSE	33936	1000 kg		-	-
6416841339348	MASONRY MORTAR 85 RAVEN	33934	1000 kg		-	-
6416841339355	Masonry mortar 86 Hazel hen	33935	1000 kg		-	-

x = stock product



Masonry mortar M100/600 Winter ❄️

Cement-based mortar for burnt and sand-lime brick facade masonry in winter conditions in the temperature range -15°C...+5°C. Suitable for brickwork repointing and for repairing mortar joints. The maximum grain size is 2.0 mm. Material usage 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330703	MASONRY MORTAR M100/600 WINTER	33070	1000 kg		x	-
6416841340009	MASONRY MORTAR 39 QUARTZ WHITE WINTER	34000	1000 kg		-	-
6416841340016	MASONRY MORTAR 59 BIRCH BARK WHITE WINTER	34001	1000 kg		-	-
6416841340023	MASONRY MORTAR 40 LIME GRAY WINTER	34002	1000 kg		-	-
6416841340030	MASONRY MORTAR 41 GRAIN YELLOW WINTER	34003	1000 kg		-	-
6416841340047	MASONRY MORTAR 42 BRICK RED WINTER	34004	1000 kg		-	-
6416841340054	MASONRY MORTAR 45 EARTH BROWN WINTER	34005	1000 kg		-	-
6416841340061	MASONRY MORTAR 46 PEAT BROWN WINTER	34006	1000 kg		-	-
6416841340078	MASONRY MORTAR 48 BLACK GRAY WINTER	34007	1000 kg		-	-
6416841340085	MASONRY MORTAR 52 LINEN LIGHT WINTER	34008	1000 kg		-	-
6416841340306	MASONRY MORTAR 44 SAND BROWN WINTER	34030	1000 kg		-	-
6416841340221	MASONRY MORTAR 71 SWAN WINTER	34022	1000 kg		-	-
6416841340252	Masonry mortar 72 Ali Winter	34025	1000 kg		-	-
6416841340276	MASONRY MORTAR 73 CUCKOO WINTER	34027	1000 kg		-	-
6416841340153	Masonry mortar 74 Hawk Winter	34015	1000 kg		-	-
6416841340269	MASONRY MORTAR 75 LARK WINTER	34026	1000 kg		-	-

6416841340207	MASONRY MORTAR 77 JACKDAW WINTER	34020	1000 kg		-	-
6416841340245	MASONRY MORTAR 79 PTARMIGAN WINTER	34024	1000 kg		-	-
6416841340290	MASONRY MORTAR 80 SIBERIAN JAY WINTER	34029	1000 kg		-	-
6416841340115	MASONRY MORTAR 81 TEAL WINTER	34011	1000 kg		-	-
6416841340214	Masonry mortar 82 Capercaillie Winter	34021	1000 kg		-	-
6416841340320	MASONRY MORTAR 83 WILLOW GROUSE WINTER	34032	1000 kg		-	-
6416841340122	MASONRY MORTAR 85 RAVEN WINTER	34012	1000 kg		-	-
6416841340139	Masonry mortar 86 Hazel hen Winter	34013	1000 kg		-	-

x = stock product

Compact mortar M100/600

Cement-based mortar for burnt and sand-lime brick masonry for facades exposed to harsh weather conditions. Suitable for locations subject to heavy slanted rain. Suitable for repointing brickwork and natural and slate stones on vertical surfaces, and for repairing mortar joints. Contains additives to improve density, weather resistance and workability. Maximum grain size 2.0 mm. Usage: 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331007	COMPACT MORTAR M 100/600	33100	1000 kg		x	-
6416841331335	Compact mortar 39 Quartz white	33133	1000 kg		-	-
6416841331014	Compact mortar 59 Birch bark white	33101	1000 kg		-	-
6416841331045	Compact mortar 40 Lime gray	33104	1000 kg		-	-
6416841331038	Compact mortar 41 Grain yellow	33103	1000 kg		-	-
6416841344250	Compact mortar 42 Brick red	34425	1000 kg		-	-
6416841331052	Compact mortar 45 Earth brown	33105	1000 kg		-	-
6416841331069	Compact mortar 46 Peat brown	33106	1000 kg		-	-
6416841331076	Compact mortar 48 Black gray	33107	1000 kg		-	-
6416841344274	COMPACT MORTAR 52 LINEN LIGHT	34427	1000 kg		-	-
6416841344182	COMPACT MORTAR 44 SAND BROWN	34418	1000 kg		-	-
6416841344137	COMPACT MORTAR 71 SWAN	34413	1000 kg		-	-
6416841344168	Compact mortar 72 Alli	34416	1000 kg		-	-
6416841344083	COMPACT MORTAR 73 CUCKOO	34408	1000 kg		-	-
6416841344144	Compact mortar 74 Hawk	34414	1000 kg		-	-
6416841344113	COMPACT MORTAR 75 LARK	34411	1000 kg		-	-

6416841344120	COMPACT MORTAR 77 JACKDAW	34412	1000 kg		-	-
6416841344106	COMPACT MORTAR 79 PTARMIGAN	34410	1000 kg		-	-
6416841344243	COMPACT MORTAR 80 SIBERIAN JAY	34424	1000 kg		-	-
6416841344298	COMPACT MORTAR 81 TEAL	34429	1000 kg		-	-
6416841344151	Compact mortar 82 Capercaillie	34415	1000 kg		-	-
6416841344229	COMPACT MORTAR 83 WILLOW GROUSE	34422	1000 kg		-	-
6416841344199	COMPACT MORTAR 85 RAVEN	34419	1000 kg		-	-
6416841344236	Compact mortar 86 Hazel hen	34423	1000 kg		-	-

x = stock product



Compact mortar M100/600 Winter ❄️

Cement-based mortar for burnt and sand-lime brick masonry for facades exposed to harsh winter weather in the temperature range -15°C...+5°C. Suitable for locations subject to heavy slanted rain. Suitable for repointing brickwork and natural and slate stones on vertical surfaces, and for repairing mortar joints. Contains additives to improve density, weather resistance and workability. Maximum grain size 2.0 mm. Usage: 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331106	Compact mortar M100/600 Winter 1000 kg	33110	1000 kg		x	-
6416841335418	COMPACT MORTAR 39 QUARTZ WHITE WINTER	33541	1000 kg		-	-
6416841331199	COMPACT MORTAR 59 BIRCH BARK WHITE WINTER	33119	1000 kg		-	-
6416841345424	COMPACT MORTAR 40 LIME GRAY WINTER	34542	1000 kg		-	-
6416841345417	COMPACT MORTAR 41 GRAIN YELLOW WINTER	34541	1000 kg		-	-
6416841345158	COMPACT MORTAR 42 BRICK RED WINTER	34515	1000 kg		-	-
6416841345455	COMPACT MORTAR 45 EARTH BROWN WINTER	34545	1000 kg		-	-
6416841345622	COMPACT MORTAR 46 PEAT BROWN WINTER	34562	1000 kg		-	-
6416841345479	COMPACT MORTAR 48 BLACK GRAY WINTER	34547	1000 kg		-	-
6416841345172	COMPACT MORTAR 52 LINEN LIGHT WINTER	34517	1000 kg		-	-
6416841345486	COMPACT MORTAR 44 SAND BROWN WINTER	34548	1000 kg		-	-
6416841335579	COMPACT MORTAR 71 SWAN WINTER	34557	1000 kg		-	-
6416841345615	Compact mortar 72 Below Winter	34561	1000 kg		-	-
6416841345684	COMPACT MORTAR 73 CUCKOO WINTER	34568	1000 kg		-	-
6416841345547	Compact mortar 74 Hawk Winter	34554	1000 kg		-	-
6416841345561	COMPACT MORTAR 75 LARK WINTER	34556	1000 kg		-	-

6416841345509	COMPACT MORTAR 77 JACKDAW WINTER	34550	1000 kg		-	-
6416841345608	COMPACT MORTAR 79 PTARMIGAN WINTER	34560	1000 kg		-	-
6416841345660	COMPACT MORTAR 80 SIBERIAN JAY WINTER	34566	1000 kg		-	-
6416841345585	COMPACT MORTAR 81 TEAL WINTER	34558	1000 kg		-	-
6416841345516	Compact mortar 82 Capercaillie Winter	34551	1000 kg		-	-
6416841345677	COMPACT MORTAR 83 WILLOW GROUSE WINTER	34567	1000 kg		-	-
6416841345639	COMPACT MORTAR 85 RAVEN WINTER	34563	1000 kg		-	-
6416841345653	Compact mortar 86 Hazel hen Winter	34565	1000 kg		-	-

x = stock product

Compact mortar Heavy M100/600

Cement-based mortar for burnt and sand-lime brick masonry for facades exposed to extremely harsh weather. Especially suitable for coastal sites where structures will have to withstand wind and weathering. Suitable for brickwork repointing and for repairing mortar joints. Contains additives to improve density, weather resistance and workability. Maximum grain size 2.0 mm. Usage: 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841344601	COMPACT MORTAR HEAVY M100/600	34460	1000 kg		-	-
6416841345011	COMPACT MORTAR HEAVY 39 KVARTSINVALKOINEN	34501	1000 kg		-	-
6416841345028	Compact mortar Heavy 59 Birch bark white	34502	1000 kg		-	-
6416841345035	Compact mortar Heavy 40 Lime gray	34503	1000 kg		-	-
6416841345042	Compact mortar Heavy 41 Grain yellow	34504	1000 kg		-	-
6416841345059	Compact mortar Heavy 42 Brick red	34505	1000 kg		-	-
6416841345066	Compact mortar Heavy 45 Earth brown	34506	1000 kg		-	-
6416841345073	Compact mortar Heavy 46 Peat brown	34507	1000 kg		-	-
6416841345080	Compact mortar Heavy 48 Black gray	34508	1000 kg		-	-
6416841345097	COMPACT MORTAR HEAVY 52 LINEN LIGHT	34509	1000 kg		-	-
6416841345189	COMPACT MORTAR HEAVY 44 SAND BROWN	34518	1000 kg		-	-
6416841345202	COMPACT MORTAR HEAVY 71 SWAN	34520	1000 kg		-	-
6416841345165	Compact mortar Heavy 72 Below	34516	1000 kg		-	-
6416841345141	COMPACT MORTAR HEAVY 73 CUCKOO	34514	1000 kg		-	-
6416841344649	Compact mortar Heavy 74 Hawk	34464	1000 kg		-	-
6416841345110	COMPACT MORTAR HEAVY 75 LARK	34511	1000 kg		-	-

6416841345127	COMPACT MORTAR HEAVY 77 JACKDAW	34512	1000 kg		-	-
6416841345103	COMPACT MORTAR HEAVY 79 PTARMIGAN	34510	1000 kg		-	-
6416841345240	COMPACT MORTAR HEAVY 80 SIBERIAN JAY	34524	1000 kg		-	-
6416841345219	COMPACT MORTAR HEAVY 81 TEAL	34521	1000 kg		-	-
6416841344410	Compact mortar Heavy 82 Capercaillie	34441	1000 kg		-	-
6416841345226	COMPACT MORTAR HEAVY 83 WILLOW GROUSE	34522	1000 kg		-	-
6416841345196	COMPACT MORTAR HEAVY 85 RAVEN	34519	1000 kg		-	-
6416841345233	Compact mortar Heavy 86 Hazel hen	34523	1000 kg		-	-

x = stock product



Compact mortar Heavy M100/600 Winter ❄️

Cement-based mortar for burnt and sand-lime brick masonry for facades exposed to extremely harsh winter weather in the temperature range -15°C...+5°C. Especially suitable for coastal sites where structures will have to withstand wind and weathering. Suitable for brickwork repointing and for repairing mortar joints. Contains additives to improve density, weather resistance and workability. Maximum grain size 2.0 mm. Usage: 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841346001	COMPACT MORTAR HEAVY M100/600 WINTER	34600	1000 kg		-	-
6416841345318	COMPACT MORTAR HEAVY 39 WINTER	34531	1000 kg		-	-
6416841345325	COMPACT MORTAR HEAVY 59 BIRCH BARK WHITE WINTER	34532	1000 kg		-	-
6416841345332	COMPACT MORTAR HEAVY 40 LIME GRAY WINTER	34533	1000 kg		-	-
6416841345349	COMPACT MORTAR HEAVY 41 GRAIN YELLOW WINTER	34534	1000 kg		-	-
6416841345356	COMPACT MORTAR HEAVY 42 BRICK RED WINTER	34535	1000 kg		-	-
6416841345363	COMPACT MORTAR HEAVY 45 EARTH BROWN WINTER	34536	1000 kg		-	-
6416841345370	COMPACT MORTAR HEAVY 46 PEAT BROWN WINTER	34537	1000 kg		-	-
6416841345387	COMPACT MORTAR HEAVY 48 BLACK GRAY WINTER	34538	1000 kg		-	-
6416841345295	COMPACT MORTAR HEAVY 52 LINEN LIGHT WINTER	34539	1000 kg		-	-
6416841345783	COMPACT MORTAR HEAVY 44 SAND BROWN WINTER	34578	1000 kg		-	-
6416841345905	COMPACT MORTAR HEAVY 71 SWAN WINTER	34590	1000 kg		-	-
6416841345462	Compact mortar Heavy 72 Below Winter	34546	1000 kg		-	-
6416841345691	COMPACT MORTAR HEAVY 73 CUCKOO WINTER	34569	1000 kg		-	-
6416841345844	Compact mortar Heavy 74 Hawk Winter	34584	1000 kg		-	-
6416841345004	COMPACT MORTAR HEAVY 75 LARK WINTER	34500	1000 kg		-	-

6416841345134	COMPACT MORTAR HEAVY 77 JACKDAW WINTER	34513	1000 kg		-	-
6416841345806	COMPACT MORTAR HEAVY 79 PTARMIGAN WINTER	34580	1000 kg		-	-
6416841345943	COMPACT MORTAR HEAVY 80 SIBERIAN JAY WINTER	34594	1000 kg		-	-
6416841345912	COMPACT MORTAR HEAVY 81 TEAL WINTER	34591	1000 kg		-	-
6416841345714	Compact mortar Heavy 82 Capercaillie Winter	34571	1000 kg		-	-
6416841345929	COMPACT MORTAR HEAVY 83 WILLOW GROUSE WINTER	34592	1000 kg		-	-
6416841345790	COMPACT MORTAR HEAVY 85 RAVEN WINTER	34579	1000 kg		-	-
6416841345950	Compact mortar Heavy 86 Hazel hen Winter	34595	1000 kg		-	-

x = stock product

Winter-time masonry mortar TML

For block and brick masonry in winter conditions in the temperature range -15°C...+5°C. Material usage: For bricks, the same as with masonry mortar, and for bricks, the same as with block mortar. Remains usable for around 0.5 h. Amount of finished mortar: 13-14 l/25 kg



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530509	WINTER-TIME MASORY MORTAR TML	53050	25 kg	48 sk	x	-

x = stock product

Block mortar M100/500

For lightweight aggregate block masonry. Usage: around 4 kg / H75-UH150, around 7 kg / UH200-RUH380. Remains usable for around 3 h.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530493	BLOCK MORTAR M100/500	53049	25 kg	48 sk	x	x
6416841330499	BLOCK MORTAR M100/500	33049	1000 kg		x	x

x = stock product



Block mortar M100/500 Winter ❄️

For lightweight aggregate block masonry in winter conditions in the temperature range -15°C...+5°C. Material usage: ca. 4 kg / H75-UH150, ca. 7 kg / UH200-RUH380.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330505	BLOCK MORTAR M100/500 WINTER	33050	1000 kg		-	-

x = stock product



Stone adhesive KVL

For thin-jointing of sand-lime bricks and blocks. Also suitable for rough coating. Usage: 2-4 kg/m², in rough coating 3-6 kg/m².

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530325	STONE ADHESIVE KVL 25 KG	53032	25 kg	48 sk	x	x

x = stock product



Mortar for tongue-and-groove blocks PHL

For the thin-joint masonry of lightweight aggregate blocks. Usage: around 1.5 kg/ UH 100-150, around 2.5 kg/ RUH 200-420, around 2.5 - 3.5 kg/ EH 420.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530196	MORTAR FOR TONGUE-AND-GROOVE BLOCKS PHL	53019	25 kg	48 sk	x	x
6416841330161	MORTAR FOR TONGUE-AND-GROOVE BLOCKS PHL	33016	500 kg		x	x
6416841330192	MORTAR FOR TONGUE-AND-GROOVE BLOCKS PHL	33019	1000 kg		x	x

x = stock product

Mortar for tongue and groove blocks PHL Winter ❄️

Fescon Mortar for tongue and groove blocks Winter is a dry mortar for the winter-time thin-jointing of lightweight aggregate blocks. The maximum grain size is 1.2 mm. Working temperature -15°C...+5°C.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530097	MORTAR FOR TONGUE-AND-GROOVE BLOCKS PHL WINTER	53009	25 kg	48 sk	-	-
6416841330246	MORTAR FOR TONGUE AND GROOVE BLOCKS PHL WINTER	33024	1000 kg		-	-

x = stock product

ELT Brick element grout

A coloured concrete-type grout for the grouting of industrial prefabricated brick elements. Maximum grain size 1.2 mm. Minimum delivery 3 big bags.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330901	ELT Brick element grout	33090	1000 kg		-	-
6416841330987	ELT Brick element grout quartz white	33098	900 kg		-	-
6416841332103	ELT Brick element grout that white	33210	900 kg		-	-
6416841332110	ELT Brick element grout lime gray	33211	900 kg		-	-
6416841332127	ELT Brick element grout grain yellow	33212	900 kg		-	-
6416841332134	ELT Brick element grout brick red	33213	900 kg		-	-
6416841332141	ELT Brick element grout earthy brown	33214	900 kg		-	-
6416841332158	ELT Brick element grout peat brown	33215	900 kg		-	-
6416841332165	ELT Brick element grout black-gray	33216	900 kg		-	-
6416841332172	ELT Brick element grout linen pale	33217	900 kg		-	-
6416841332349	ELT Brick element grout sand brown	33234	900 kg		-	-
6416841332356	ELT Brick element grout swan	33235	900 kg		-	-
6416841332318	ELT Brick element grout below	33231	900 kg		-	-
6416841332387	ELT Brick element grout persimmon	33238	900 kg		-	-
6416841332332	ELT Brick element grout Hawk	33233	900 kg		-	-
6416841332363	ELT Brick element grout lark	33236	900 kg		-	-

6416841332400	ELT Brick element grout jackdaw	33240	900 kg		-	-
6416841332455	ELT Brick element grout ptarmigan	33245	900 kg		-	-
6416841332462	ELT Brick element grout heard	33246	900 kg		-	-
6416841332301	ELT Brick element grout teal	33230	900 kg		-	-
6416841332394	ELT Brick element grout Capercaillie	33239	900 kg		-	-
6416841332417	ELT Brick element grout willow grouse	33241	900 kg		-	-
6416841332370	ELT Brick element grout raven	33237	900 kg		-	-
6416841332554	ELT Brick element grout Hazel hen	33255	900 kg		-	-

x = stock product



ELK Clinker element grout

Concrete-type grout for the grouting of industrial prefabricated clinker elements.
Maximum grain size 0.6 mm. Minimum delivery 3 big bags.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330918	ELK Clinker element grout	33091	1000 kg		-	-

x = stock product

5 WALL LEVELING COMPOUNDS

Joint filler SF

A polymer-based putty and jointing product for interior walls. Suitable for block, concrete, lightweight concrete, Bedding plaster LF, brick plaster and gypsum board surfaces, and in the levelling of painted surfaces and the jointing of gypsum boards. Usage: 1.2 kg/m²/1 mm layer. Whitish colour.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201003	JOINT FILLER SF	20100	20 kg	48 sk	-	-

x = stock product

Bedding plaster LF

A polymer-based bedding plaster for wall and ceiling surfaces in dry spaces. Suitable for block, concrete, lightweight concrete, brick, brick plaster, Bedding plaster VF and Finishing plaster VHF surfaces. Usage: 1.2 kg/m²/1 mm layer. Layer thickness 1 - 5 mm. Whitish colour.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201010	BEDDING PLASTER LF	20101	20 kg	48 sk	x	x

x = stock product

Bedding plaster LF RD

A polymer-based low-dust bedding plaster for wall and ceiling surfaces in dry spaces. Suitable for block, concrete, lightweight concrete, brick, brick plaster, Bedding plaster VF and Finishing plaster VHF surfaces. Usage: 1.2 kg/m²/1 mm layer. Layer thickness 1 - 5 mm. Whitish colour.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201010	BEDDING PLASTER LF	20101	20 kg	48 sk	x	x

x = stock product



Low dust.



Finishing plaster LRF



A polymer-based finishing plaster for wall and ceiling surfaces in dry spaces. Suitable for block, concrete, lightweight concrete, Bedding plaster LF, brick plaster and gypsum board surfaces. Usage: 1.2 kg/m²/1 mm layer. Layer thickness 0 - 3 mm. Whitish colour.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201027	FINISHING PLASTER LRF	20102	20 kg	48 sk	x	x

x = stock product



Finishing plaster LRF RD



A polymer-based, low-dust finishing plaster for wall and ceiling surfaces in dry spaces. Suitable for block, concrete, lightweight concrete, Bedding plaster LF and LF RD, brick plaster and gypsum board surfaces. Usage: 1.2 kg/m²/1 mm layer. Layer thickness 0 - 3 mm. Whitish colour.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202406	FINISHING PLASTER LRF RD	20240	20 kg	48 sk	-	-

x = stock product



Brick bedding plaster TTF



A cement-based bedding plaster for wall and ceiling surfaces in dry and wet spaces. Suitable for block, brick, lightweight concrete, brick plaster and plastered surfaces. Usage: 1.2 kg/m²/1 mm layer. Layer thickness 2 - 10 mm. Colour grey.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201034	BRICK BEDDING PLASTER TTF	20103	20 kg	48 sk	x	x

x = stock product



Low dust.

Bedding plaster VF

A cement-based bedding plaster for wall and ceiling surfaces in dry and wet spaces. Suitable for block, lightweight concrete, brick and concrete surfaces. Usage: 1.2 kg/m²/1 mm layer. Layer thickness 1 - 5 mm. Grey colour.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201041	BEDDING PLASTER VF	20104	20 kg	48 sk	x	-

x = stock product

Finishing plaster VHF

A cement-based finishing plaster for wall and ceiling surfaces in dry and wet spaces. Suitable for block, lightweight concrete and Bedding plaster VF surfaces. Usage: 1.2 kg/m²/1 mm layer. Layer thickness 0 - 3 mm. Grey colour.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201058	Finishing plaster VHF	20105	20 kg	48 sk	x	-

x = stock product

Levelling compound for wet areas WTT

A cement-based wall finishing plaster for wet areas, particularly under moisture insulation. Also suitable for pump application. Usage: 1.2 kg/m²/1 mm layer. Layer thickness 2-10 mm.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201072	LEVELLING COMPOUND FOR WET AREAS WTT 20 KG	20107	20 kg	48 sk	x	x

x = stock product



Low dust.



Filling plaster TLR

A quickly hardening and drying filling plaster with a special cement binder for interior wall surfaces in dry, humid and wet areas. Recommended layer thickness: over-levelling 5-30 mm, partial levelling 5-50 mm. Usage: 1 mm layer 1.5 kg/m².

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201089	FILLING PLASTER TLR 20 KG	20108	20 kg	48 sk	x	-

x = stock product



Indoor lime-cement plaster SR 7

Quickly hardening and drying indoor lime-cement plaster that can be sprayed or applied manually, containing special cement binders, fibre-reinforced. Use: Straightening walls and ceilings, filling and repairs in dry, damp and wet areas.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201102	INDOOR LIME-CEMENT PLASTER SR 7	20110	20 kg	48 sk	x	-

x = stock product



Gypsum plaster mix GL

Pumpable, lightweight, non-shrinking gypsum levelling compound, which is also suitable for shaping manually. Fescon Gypsum Plaster Mix GL is meant for straightening and levelling wall and ceiling surfaces in dry indoor spaces for layer thicknesses as large as 40 mm.


GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202383	Gypsum plaster mix GL	20238	15 kg	48 sk	x	-

x = stock product

Wall surface strengthening membrane



Surface reinforcement fabric for reinforcing screed surfaces of walls. Roll size 1.0 m x 50 m.



					HAUSJÄRVI	HAUKIPUDAS
GTIN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841257116	Wall surface strengthening membrane 1 m x 50 m	25711	1 roll		-	-

x = stock product

6 FLOOR LEVELING PRODUCTS



Underfloor heating filler LL 5500



A fibre-reinforced, casein-free floor underfloor heating filler with a special cement binder that hardens and dries rapidly, and can be manually applied. Use: underfloor heating filler for indoor concrete and primed plasterboard floors. Largest grain size 1.2 mm. Layer thickness 10-80 mm. Dry usage: around 1.8 kg/m²/mm.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202017	Underfloor heating filler LL 5500 20 KG	20201	20 kg	48 sk	x	x

x = stock product



Coarse floor levelling compound LM 5000



A cement-based, casein-free floor levelling compound that hardens and dries rapidly, and can be manually applied. Uses: casting, straightening, filling and grading of concrete floors. Largest grain size 1.2 mm. Layer thickness 5-80 mm. Dry usage: around 1.8 kg/m²/mm.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202024	Coarse floor levelling compound LM 5000 20 KG	20202	20 kg	48 sk	x	x

x = stock product



Floor levelling plaster LT 4000



A cement-based, casein-free floor levelling compound that is easily levelled, rapidly hardening and drying, and can be manually applied. Used to level the surface of concrete floors. Also suitable for graded floors. Largest grain size 0.6 mm. Layer thickness 3-30 mm. Dry usage: approx. 1.5 kg/m²/mm.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202031	Floor levelling plaster LT 4000 20 KG	20203	20 kg	48 sk	x	x

x = stock product



Low dust.

Floor concrete LB 7

Special cement based, pumpable and rapidly drying floor concrete. Suitable for casting graded floors, conduit filling and applications where the structure must be taken into use rapidly, such as pipe renovations. Compressive strength around 40 MPa Fibre-reinforced. Layer thickness 30 - 150 mm. Dry usage: around 1.8 kg/m²/mm.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202154	FLOOR CONCRETE LB 7	20215	20 kg	48 sk	x	-
6416841333407	FLOOR CONCRETE LB 7	33340	1000 kg		x	-

x = stock product

Fescorapid

A quickly hardening and drying repair plaster with a special cement binder for repairing holes in a concrete floor, correcting the floor grade, and repairing and levelling stairs. Strength approx. 30 MPa, maximum grain size 0.6 mm, and layer thickness 2-20 mm. Usage: 1.5 kg/m²/1 mm.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631015	Fescorapid	63101	5 kg		x	x
6416841202352	Fescorapid 20 KG	20235	20 kg	48 sk	x	-

x = stock product

Fescofine

A quickly hardening and drying repair plaster with a special cement binder for repairing holes in a concrete floor, correcting the floor grade, and repairing and levelling stairs. Maximum grain size 0.1 mm.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202390	Fescofine	20239	20 kg	48 sk	x	-

x = stock product



Low dust.

FlowPlan



Easy to use and highly spreadable cement-based floor screed for layers of less than 20 mm. Suitable for use as a base for mats in public areas and for all finishing and overlay applications. Can be used for overlaying all Fescon flooring products and as a subfloor structure for polyurethane and epoxy coatings with a layer thickness of more than 3 mm. FlowPlan can be used for overlaying underfloor heating cables and for thin finishing layers in wet rooms before waterproofing. Suitable for painting, tiling or as a base for adhesive surface materials. Maximum grain size 0.3 mm. For layer thickness 1 - 15 mm (partial levelling max. 20 mm). A low-alkali (pH < 11). For indoor use.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202307	FlowPlan	20230	20 kg	48 sk	x	x

x = stock product

Flow CS



Flow CS is a high-strength cement-based floor screed. Especially suitable for polyurethane and epoxy-coated subfloor structures in homes, commercial premises, hospitals, offices and schools. The product does not contain fiber that would hinder coating work. When using acrylic coatings, check product compatibility with the coating manufacturer. Flow CS can be applied by trowel or by pumping. With a minimum layer thickness of 5 mm, the product can be used for alkali protection. Layer thickness 2 - 30 mm (partial levelling max. 50 mm). Maximum grain size 0.6 mm. A low-alkali (pH < 11). For indoor use.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202475	Flow CS 20 kg	20247	20 kg	48 sk	-	-
6416841338174	Flow CS 1000 kg	33817	1000 kg		-	-

x = stock product

Flow FS



A cost-effective and versatile fiber-reinforced, cement-based floor screed. Suitable for a wide range of adhesive carpeting in public areas and for floor levelling in residential construction, either hand-applied or pumped. Can be used for the surface casting of thermal floors and floating floor systems in public spaces and residential buildings, and for levelling cavity slabs and concrete floors. Flow FS is low alkaline. Compressive strength C 20. Layer thickness 4 - 50 mm (partial levelling max. 80 mm). Maximum grain size 1.2 mm. For indoor use. Bulk delivery pricing according to a separate offer.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202451	Flow FS 20 kg	20245	20 kg	48 sk	x	-
6416841331458	Flow FS 1000 kg	33145	1000 kg		-	-
	Flow FS bulk delivery	33845	1 kg		-	-

x = stock product

FlowBase



High strength, fiber-reinforced cement-based pumpable floor leveling compound. Suitable for leveling cavity slabs and concrete floors in homes, commercial premises, hospitals, offices and schools. Suitable as a base for mats, for painting, tiling or as a base for adhesive surface materials. FlowBase can be used for alkali protection with a minimum layer thickness of 5 mm. Maximum grain size 0.6 mm. For layer thicknesses 8-30 mm (partial levelling max. 50 mm). A low-alkali (pH < 11). For indoor use.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331489	FlowBase 1000 kg	33148	1000 kg		-	-

x = stock product



Flow GS 3.0 mm Gypsum floor mass



Flow GS 3.0 mm Gypsum floor mass is a pump-applied, easily levelling floor compound with a gypsum binder and having excellent workability and spreading characteristics. Suitable for heated floor structures, in particular. Maximum grain size: 3.0 mm. Layer thickness 20-80 mm (partial levelling max. 100 mm)

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331496	Flow GS 3.0 mm Gypsum floor mass	33149	1000 kg		-	-

x = stock product

Flow Primer



Brush-on primer for surface pretreatment before floor levelling. Flow Primer improves the adhesion of floor levelling compounds, reduces or eliminates the formation of air bubbles, and prevents water contained in the floor levelling compound from being absorbed into the surface too quickly. Usage: Hollow-core slab surfaces: about 10 m²/l. Cast-in-place concrete surfaces: about 5 m²/l. Plaster and wood surfaces: about 7 m²/l. Mixing ratio: Concrete surfaces and surfaces with cement-based levelling: 1 part Flow Primer, 3 parts water. Surfaces that cannot withstand moisture, e.g. plaster and wood surfaces: Use undiluted. For indoor use.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841769053	Flow Primer	76905	10 l	50 prk	x	-

x = stock product



Primer PLUS



Brush-on special primer for the pretreatment of the base on non-absorbent surfaces (ceramic, glass or steel) before levelling. Usage: around app. 150 g/ m²l. Product is ready for use and does not need to be thinned. Pallet size (5 kg) 90 cans / pallet. For indoor use.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841769060	Primer PLUS	76906	5 kg	80 prk	x	-

x = stock product

Elevation mark

Elevation mark with adhesive tape for floor levelling compounds. Scale 10-65 mm or 10-100 mm. Sold in bags of 100.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259332	ELEVATION MARK	25933	1 pcs		x	-
6416841259363	ELEVATION MARK	25936	1 pcs		x	-

x = stock product

Bordering strip 30x30x2000 mm

Fescon Bordering strip is a self-adhesive polyester strip for bordering floor levelling compounds. With the Bordering strip, the pumped areas can be restricted to the required size, also suitable for making door stops. Installation on a cleaned and primed base. Package size 25 pcs. / bag (50 m).



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259394	Bordering strip 30x30x2000 mm	25939	50 m		x	-

x = stock product

Bordering strip 8x150 mm

A bordering strip for separating floating floor structures from vertical structures. The Bordering strip has a ready-fitted overlapping plastic sheet with adhesive tape, to be installed over separation fabric or insulation. The back of the Bordering strip has a fastening tape for wall mounting. Roll length 25 m. Sales lot 4 rolls/package (100 m).



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259387	Bordering strip 8x150 mm	25938	100 m		x	-

x = stock product



Separation fabric 1.5x50 m

Breathable Separation fabric for separating floating floor structures, if the base is of weak concrete, a floor base, or insulation. Diffusion open, separation fabric, made of polypropylene, through which the water in the floor levelling compound cannot penetrate. Both long sides of the separation fabric have an overlapping tape ready-fitted, overlapping according to alignment lines.

					HAUSJÄRVI	HAUKIPUDAS
GTIN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841259370	Separation fabric 1.5x50 m	25937	75 m ²		x	-

x = stock product

7 TILING PLASTER AND WATERPROOFING PRODUCTS

Waterproofing compound

1-component, rollable and fibre-reinforced waterproofing compound for indoor applications. Suitable for waterproofing floors and walls. Consumption about 0.7 l/m² on walls and about 1.0 l/m² on floors. Accessories used with the waterproofing compound: Fescon primer, drain flange 300 x 300 mm fibre or drain flange KL-B, waterproofing strip 0.15 x 25 m and/or waterproofing accessories FS. Eurofins Expert Services Oy product certificate no. C-870-06, EEA and M1 approved, with CE marking.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259097	Waterproofing compound 3L	25909	3 l		x	x
6416841259035	Waterproofing compound 12L	25935	12 l	52 prk	x	x

x = stock product

Waterproofing compound WS



Fast-drying, single-component indoor waterproofing compound that can be rolled or sprayed. Suitable for the waterproofing of floors and walls. Consumption about 0.7 l/m² on walls and floors. Accessories used with Waterproofing compound WS: Fescon Primer KP, Drain flange KL-B, Waterproofing accessories (FS and VE series) and Waterproofing strip 0.15 x 25 m fibre. ETA- and M1-approved, with CE marking.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841769091	Waterproofing compound WS	76909	3 l	100 prk	x	-
6416841769121	Waterproofing compound WS	76912	15 l	24 prk	x	-

x = stock product



Fescoseal A+B

The Fescoseal A+B two-component waterproofing compound is used in the waterproofing of floors and walls before ceramic tiles are installed. Fescoseal A+B is easy to apply, it dries rapidly, it is extremely flexible after drying, and it has excellent adhesive properties. The product is non-shrink and can withstand chlorides and frost stress. The waterproofing system has the cleanest M1 building material emission class. Eurofins Expert Services Oy product certificate C-11838-16.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841769008	Fescoseal A	76900	10 kg	40 prk	x	-
6416841769084	Fescoseal B	76908	10 kg	40 prk	x	-

x = stock product

Adhesion promoter



Water-soluble primer for pretreatment of the base. The primer is used as part of the Fescon waterproofing system. Also suitable for all Fescon floor leveling compounds and wall filler, to improve the stress category of wall fillers. Improves adhesion to the substrate, absorbs dust, prevents the formation of air bubbles, and prevents the water in the leveling compound from being absorbed too quickly into the substrate. For indoor use. Pack size 5 x 3 ltr / box and 10 x 1 ltr / box.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259110	ADHESION PROMOTER	25911	1 l		x	x
6416841259103	ADHESION PROMOTER	25910	3 l		x	x
6416841259042	ADHESION PROMOTER	25904	10 l	50 prk	x	x

x = stock product

Primer KP



Water-soluble primer for pretreatment of substrate in the Fescon WS and Fescoseal A+B waterproofing systems. Consumption: dense surfaces approx. 10 m²/l, porous surfaces approx. 6 m²/l. Mixing ratio: concrete and cement-based leveling compounds: 1 part primer and 3 parts water, building boards suitable for wet spaces: not to be thinned. For indoor use.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841769039	Primer KP 1 l	76903	1 l	100 prk	x	-
6416841769046	Primer KP	76904	5 l	100 prk	x	-
6416841769015	PRIMER KP	76901	10 l	40 prk	x	-

x = stock product


Waterproofing strip

A strip made of fibre material used in the Fescon WS and waterproofing systems to strengthen inside and outside corners and joints. A waterproofing strip can be used for through-holes with a maximum diameter of 75 mm. The strip dimensions are 0.15 x 25 m, 10 rolls per box. Also available as waterproofing membrane 1.0 x 10 m. Not suitable for the Fescoseal A+B waterproofing system.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259073	Waterproofing strip 0,15 m x 25 m fiber	25907	1 roll		x	x
6416841259059	Waterproofing membrane 1mx10m 10m ² /roll	25905	1 roll		x	x

x = stock product



Drain flange 300x300 mm fibre

Fibre floor drain sealing material for Fescon waterproofing systems. Also suitable as a through-hole flange for a 110 mm sewer pipe. The drain flange size is 300 x 300 mm. Sold in packages of 2 or 10. Two required for one drain. Not suitable for Fescon WS or Fescoseal waterproofing systems.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259141	Drain flange 300X300 mm fibre (2 pcs)	25914	2 pcs		x	x
6416841259424	Drain flange 300X300 mm fibre (10 pcs)	25942	10 pcs		x	x

x = stock product



Drain flange KL-B

The self-adhesive butyl drain flange can be used with all Fescon waterproofing systems. The surface is reinforced with a polypropylene material. Drain flange size 37 x 37 cm. Package size: 10 pcs per box. Use: For drains that are fully covered with a butyl drain flange before the clamping ring is installed.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259530	BUTYLMANSCHETTE KL-B	25953	1 pcs		x	-

x = stock product

Waterproofing accessories FS

Waterproofing accessories FS can be used in all Fescon waterproofing systems. The product family includes: waterproofing strip, inner and outer corners, and through-hole flanges. The waterproofing compounds are made of butyl, with a surface made of polypropylene fabric for extra strength. The through-hole flange must be one size smaller than the hole to be waterproofed.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259431	SEALING TAPE FS-N	25943	1 roll		x	-
6416841259448	OUTSIDE CORNER FS-U	25944	1 pcs		x	-
6416841259479	INSIDE CORNER FS-S	25947	1 pcs		x	-
6416841259486	WALL PACKING FS-L 10	25948	1 pcs		x	-
6416841259790	WALL PACKING FS-L 23	25979	1 pcs		x	-
6416841259493	WALL PACKING FS-L 40	25949	1 pcs		x	-
6416841259783	WALL PACKING FS-L 55	25978	1 pcs		x	-
6416841259516	WALL PACKING FS-L 70	25951	1 pcs		x	-
6416841259530	BUTYLMANSCHETTE KL-B	25953	1 pcs		x	-

x = stock product

Waterproofing accessories VE

Waterproofing accessories VE can be used in all Fescon WS and Fescoseal waterproofing systems. The product family includes: waterproofing strip, inner and outer corners, and through-hole flanges. The waterproofing compounds are made of butyl, with a surface made of polypropylene fabric for extra strength. The through-hole flange must be one size smaller than the hole to be waterproofed.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259547	SEALING TAPE VE-N	25954	1 roll		x	-
6416841259554	OUTSIDE CORNER VE-U	25955	1 pcs		x	-
6416841259561	INSIDE CORNER VE-S	25956	1 pcs		x	-
6416841259578	WALL PACKING VE-L 10	25957	1 pcs		x	-
6416841259806	WALL PACKING VE-L 23	25980	1 pcs		x	-
6416841259585	WALL PACKING VE-L 40	25958	1 pcs		x	-
6416841259813	WALL PACKING VE-L 55	25981	1 pcs		x	-
6416841259592	WALL PACKING VE-L 70	25959	1 pcs		x	-
6416841259530	BUTYLMANSCHETTE KL-B	25953	1 pcs		x	-

x = stock product



Tile adhesive plaster VSL



A non-sag, flexible adhesive plaster for fastening ceramic and clinker tiles to concrete, tile, plastic and painted bases. For outdoor and indoor use. Usage: 2-3 kg/m². The properties of the plaster meet the C2, S1 and T requirements.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631060	TILE ADHESIVE PLASTER VSL	63106	5 kg		x	x
6416841203021	TILE ADHESIVE PLASTER VSL	20302	20 kg	48 sk	x	x

x = stock product



Tile adhesive plaster ILL



Adhesive plaster particularly designed for large floor tiles on concrete, plastic and painted bases. Enables full plaster adhesion of a large tile. Suitable for both indoor and outdoor use. Usage: 3-6 kg/m². The properties of the plaster meet the C2 and S1 requirements.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841203014	TILE ADHESIVE PLASTER ILL	20301	20 kg	48 sk	x	x

x = stock product



Tile adhesive plaster SS2



Fastening for flexible or otherwise moving bases, such as sheet-metal walls, and for fastening natural stones. Usage: 2-3 kg/m². The properties of the plaster meet the C2 and S2 requirements.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841203038	TILE ADHESIVE PLASTER SS2	20303	20 kg	48 sk	-	-

x = stock product



Low dust.

Tile adhesive plaster SSL Lite



Fescon Tile adhesive plaster SSL Lite is a light-coloured, non-sag, lightweight, M1-rated adhesive plaster with cement binder. Enables tiling without strips or other spacers; see research report VTT-S-05228-16. A frost-resistant adhesive plaster; see test report VTT-S-05228-16. Suitable for indoor and outdoor use.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841203052	Tile adhesive plaster SSL LITE	20305	15 kg	48 sk	x	-

x = stock product

Tile seaming plaster SML



Fescon Tile Seaming Plaster SML is a dry mortar with a cement binder, max. grain size 0.3 mm. Certificate No. VTT-C-870-06.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841671004	Tile seaming plaster SML white 3 kg	67100	3 kg		x	-
6416841204004	Tile seaming plaster SML white 15 kg	20400	15 kg	48 sk	x	-
6416841671011	Tile seaming plaster SML marble white 3 kg	67101	3 kg		x	-
6416841204011	Tile seaming plaster SML marble white 15 kg	20401	15 kg	48 sk	x	-
6416841671028	Tile seaming plaster SML gray 3 kg	67102	3 kg		x	-
6416841204028	Tile seaming plaster SML gray 15 kg	20402	15 kg	48 sk	x	-
6416841671035	Tile seaming plaster SML light gray 3 kg	67103	3 kg		x	-
6416841204035	Tile seaming plaster SML light gray 15 kg	20403	15 kg	48 sk	x	-
6416841671042	Tile seaming plaster SML dark gray 3 kg	67104	3 kg		x	-
6416841204042	Tile seaming plaster SML dark gray 15 kg	20404	15 kg	48 sk	x	-
6416841671073	Tile seaming plaster SML light beige 3 kg	67107	3 kg		x	-
6416841204073	Tile seaming plaster SML light beige 15 kg	20407	15 kg	48 sk	x	-
6416841671127	Tile seaming plaster SML beige 3 kg	67112	3 kg		x	-
6416841204127	Tile seaming plaster SML beige 15 kg	20412	15 kg	48 sk	x	-
6416841671110	Tile seaming plaster SML black 3 kg	67111	3 kg		x	-
6416841204110	Tile seaming plaster SML black 15 kg	20411	15 kg	48 sk	x	-
6416841671134	Tile seaming plaster SML blackgray 3 kg	67113	3 kg		x	-
6416841204134	Tile seaming plaster SML blackgray 15 kg	20413	15 kg	48 sk	x	-

x = stock product



Sanitary silicone

One-component silicone mass for expansion joints and sealing.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259134	Sanitary silicone colorless	25913	1 pcs		x	-
6416841259165	Sanitary silicone white	25916	1 pcs		x	-
6416841260109	Sanitary silicone marble white	26010	1 pcs		x	-
6416841259202	Sanitary silicone gray	25920	1 pcs		x	-
6416841260055	Sanitary silicone light grey	26005	1 pcs		x	-
6416841259219	Sanitary silicone dark gray	25921	1 pcs		x	-
6416841260017	Sanitary silicone light beige	26001	1 pcs		x	-
6416841260123	Sanitary silicone beige	26012	1 pcs		x	-
6416841260130	Sanitary silicone black	26013	1 pcs		x	-
6416841260116	Sanitary silicone black gray	26011	1 pcs		x	-

x = stock product

8 PLASTERS

Lime-cement plaster KS 10/90

Adhesive plaster. A spray-applied lime-cement plaster for adhesion plastering. Also suitable for manual application. Usage: adhesion 6 - 10 kg/m²/mm. The minimum delivery batch is 1 large bag or 3 pallets of small bags.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530554	Lime-cement plaster KS 10/90 3 mm	53055	25 kg	48 sk	-	-
6416841330550	Lime-cement plaster KS 10/90 3 mm	33055	1000 kg		-	-

x = stock product

Lime-cement plaster KS 35/65

Adhesive plaster and filling plaster. A spray-applied lime-cement plaster for adhesion plastering and filling. Also suitable for manual application. Usage: adhesion plaster 6 - 10 kg/m²/mm, filling plaster 15 - 30 kg/m²/mm. Also available to order with a maximum grain size of 1.2 mm.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530561	Lime-cement plaster KS 35/65 3 mm	53056	25 kg	48 sk	x	-
6416841330567	Lime-cement plaster KS 35/65 3 mm	33056	1000 kg		-	-

x = stock product



Lime-cement plaster KS 50/50



A filling plaster. A lime-cement plaster for filling and finishing. Also suitable for manual application. Usage: filling approx 30 kg/m²/mm. Maximum grain size 1.2 mm or 3.0 mm.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841560575	Lime-cement plaster KS 50/50 1,2 mm	56057	25 kg	48 sk	x	x
6416841360571	Lime-cement plaster KS 50/50 1,2 mm	36057	1000 kg		-	-
6416841530578	Lime-cement plaster KS 50/50 3 mm	53057	25 kg	48 sk	x	x
6416841330574	Lime-cement plaster ks 50/50 3 mm	33057	1000 kg		x	-

x = stock product



Lime-cement plaster KS 65/35



Finishing plaster. A spray-applied lime-cement finishing plaster. Also suitable for manual application. Grain size 3 mm also available to order. Usage: 6-10 kg/m².

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841570611	Lime-cement plaster KS 65/35 0,6 mm	57061	25 kg	48 sk	x	-
6416841560612	Lime-cement plaster KS 65/35 1,2 mm	56061	25 kg	48 sk	x	-
6416841360618	Lime-cement plaster KS 65/35 1,2 mm	36061	1000 kg		-	-

x = stock product

Lightweight lime-cement plaster KEV KS 35/65



Adhesive and filling plaster with lime-cement binder containing mineral lightweight filler materials. Also suitable for manual application. Usage: 1 mm layer 1.2 kg/m². Grain size 3 mm also available to order (only in 800 kg packages). Minimum delivery 3 big bags.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841253217	Lightweight lime-cement plaster KEV KS 35/65 1,2 mm 20 kg	25321	20 kg	48 sk	x	-

x = stock product

Lime-cement plaster HD KS 35/65 fibre

A fibre-reinforced adhesion and filling plaster with a low water absorption for 5-30 mm layer thicknesses. Also suitable for manual application. Usage 1.4 kg for a 1 mm layer. Maximum grain size 3 mm (available to order in 1.2 mm grain size).



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841571014	Lime-cement plaster KS 35/65 3 mm fibre 25 kg	57101	25 kg	48 sk	x	-
6416841371010	Lime-cement plaster KS 35/65 3 mm fibre	37101	1000 kg		-	-

x = stock product

Lime-cement plaster HD KS 20/80 fibre

A fibre-reinforced adhesion and filling plaster with a low water absorption for 5-30 mm layer thicknesses. Also suitable for manual application. Usage 1.4 kg for a 1 mm layer. Maximum grain size 3 mm (available to order in 1.2 mm grain size).



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841572011	Lime-cement plaster HD KS 20/80 3 mm fibre	57201	25 kg	48 sk	x	-
6416841372017	Lime-cement plaster KS 20/80 3 mm fibre	37201	1000 kg		-	-

x = stock product



Lime plaster K100/1200

Basic plaster for the on-site preparation of lime-cement plaster by adding water and cement either as volume fractions or by weighing. The finished wet plaster is suitable for use in adhesion plastering or filling according to the amount of cement. The finished lime-cement plaster is suitable for both machine and manual application. Usage in adhesion plastering 5-10 kg/m² and in filling 15-30 kg/m².

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841339010	Lime plaster K100/1200 0,6 mm	33901	800 kg		-	-
6416841339102	Lime plaster K100/1200 1,5 mm	33910	1000 kg		-	-
6416841339119	Lime plaster K100/1200 4 mm	33911	1000 kg		-	-

x = stock product



Wet plaster

Fescon Wet plaster is a lime-based dry plaster from which ready-to-use wet plaster is prepared at a work site. With the Fescon special manufacturing method, the plaster has the good properties of traditional wet plaster. The maximum grain size is 0.6-4.0 mm. The finished wet plaster is suitable for use in adhesion plastering, filling and surface plastering according to the amount of cement. Suitable for mechanical and manual plastering.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841339010	Lime plaster K100/1200 0,6 mm	33901	800 kg		-	-
6416841339102	Lime plaster K100/1200 1,5 mm	33910	1000 kg		-	-
6416841339119	Lime plaster K100/1200 4 mm	33911	1000 kg		-	-

x = stock product

9 PRODUCTS FOR THE REPAIR OF CONCRETE SURFACES AND INFRASTRUCTURE CONSTRUCTION

Bolting plaster SR

Pumpable special plaster with cement binder for bolting during quarrying. Also available in a sulphate-resistant grade. Used in tunnel excavation, and rock and infrastructure construction. CE-marked, ready-to-use dry mix that meets quality and strength requirements.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533357	BOLTING PLASTER SR	53335	25 kg	48 sk	x	-

x = stock product

Winterbolting plaster SR

Pumpable special plaster for reinforcement work in rock construction. Can be used in winter conditions down to -10°C. The binder is made of sulphate-resistant cement. Used in tunnel excavation, and rock and infrastructure construction. CE-marked, ready-to-use dry mix that meets quality and strength requirements.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533319	Winterbolting plaster SR	53331	25 kg	48 sk	-	-

x = stock product



SILKO Corro SKC C35/45

Special concrete for demanding casting applications with salt and frost stress. Largest grain size 10 mm. Strength class C 35/45. SILKO-approved. Minimum delivery 3 big bags.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841333049	SILKO Korro SKC C 35/45 10 mm	33304	1000 kg		-	-

x = stock product



SILKO Rapid Corro SPC C35/45

Rapidly hardening special plaster for demanding applications. Largest grain size 3 mm. Strength class C 35/45. SILKO-approved. Minimum delivery 3 big bags or 3 pallets of small sacks.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533050	SILKO Rapid corro SPC 35/45 3 mm	53305	25 kg	48 sk	-	-
6416841333056	SILKO Rapid corro SPC C 35/45 3 mm	33305	1000 kg		-	-

x = stock product



Adhesive plaster TL

The Fescon Adhesive Plaster is a cement-based, polymer-modified, cement-based dry mortar with additives. The maximum grain size is 0.6 mm. The smallest delivery batch of a 5 kg container is 4 containers.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631268	Adhesive plaster TL	63126	5 kg		x	-
6416841450265	Adhesive plaster TL	45026	25 kg	48 sk	x	-

x = stock product

Repairing plaster KL 1.2

A cement-based, polymer-modified repairing plaster for the repair of damage, pits and casting defects in concrete structures, and the coating of walls, floors, stairs, plinths, and other such concrete surfaces. Largest grain size 1.2 mm. Estimated usage: 1 mm layer 1.8 kg/m².



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841430342	Repairing plaster KL 1.2 mm	43034	25 kg	48 sk	x	-

x = stock product

Repairing plaster KL 40

A polymer-modified repair plaster with cement binder for grading corrections of balconies and the repairs and patching of concrete structures. Maximum grain size 1.2 mm. Compressive strength around 40 MPa. Estimated usage: 1 mm layer 1.6 kg/m².



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450197	Repairing plaster KL 40 1,2 mm 25 kg	45019	25 kg	48 sk	x	-

x = stock product

Overlevelling plaster YTL

A polymer-modified plaster with cement binder for the levelling and thin-layer plastering of lightweight aggregate and concrete block structures and concrete surfaces. Maximum grain size 0.6 mm. Levelling work 5-10 kg/m² (depending on how even the wall is). Thin-layer plastering 6-8 kg/m² / 2 layer applications.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450814	Overlevelling plaster YTL	45081	25 kg	48 sk	x	-

x = stock product

Repair concrete RKB



Fescon Repair concrete RKB is a multi-purpose, strength-rated, non-sag and fiber-reinforced special concrete that meets the requirements of EN 1504-3 structural repair material class R3. Repair concrete can be used for filling and patching concrete structures, repairing and coating floor, wall and roof surfaces and increasing the structural strength of concrete. Suitable for indoor and outdoor use. It is also suitable for use as cast concrete and sprayed concrete in applications where high strength and good weather-resistance are required. SILKO approved. Maximum grain size 3.0 mm. Strength class C30/37. Material usage approx. 2.0 kg/m²/mm. M approved.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530073	Repair concrete RKB	53007	25 kg	48 sk	x	-
6416841330055	Corro shotcrete RKB	33005	1000 kg		x	-

x = stock product



Dry concrete K-10 POZZ

Fescon Dry concrete K-10 POZZ is dry concrete with a special binder. The portion of pozzolanic substances in it is 50 %, making it well suitable for fixing tiles of various kinds in places where it is desirable to avoid the building up of harmful lime. The maximum grain size is 10 mm. Product availability is limited, check availability before ordering. Minimum delivery batch 3000 kg.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841531353	Dry concrete K-10 POZZ 25 kg	53135	25 kg	48 sk	-	-

x = stock product

Korrogard R 0.6 mm

A polymer-modified, fibre-reinforced levelling and protective plaster for concrete structures. SILKO-approved.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533067	Korrogard R 0.6 mm 25 kg	53306	25 kg	48 sk	x	-

x = stock product

Korrogard R 1.2 mm

A polymer-modified, fibre-reinforced repair plaster for concrete structures. SILKO-approved.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533029	Korrogard R 1.2 mm 25 kg	53302	25 kg	48 sk	x	-

x = stock product

Korrogard R 3.0 mm

A polymer-modified, fibre-reinforced repair plaster for concrete structures. SILKO-approved. Minimum delivery 3 pallets.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533036	Korrogard R 3.0 mm 25KG	53303	25 kg	48 sk	-	-

x = stock product



Korroshot D KSD 5.0 mm

A polymer-modified, fibre-reinforced special concrete for shotcreting using the dry spray method. SILKO-approved. Minimum delivery 3 big bags or 3 pallets of small sacks.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533074	Korroshot D KSD 5 mm	53307	25 kg	48 sk	-	-
6416841333100	Korroshot D KSD 5 mm	33310	1000 kg		-	-

x = stock product



Quick Drill 45

The Fescon Quick Drill concept is a new system for accelerating borehole concreting (grouting) in ore prospecting. The system consists of fast-setting concrete, Ciment Fondu Lafarge, and a Quick Drill additive package, by means of which the characteristics of the cement paste can be adjusted. Prices according to separate offer.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631800	Quick Drill 45 2,5 l	63180	2,5 l		-	-
6416841533807	Quick Drill 45 20 l	53380	20 l		-	-

x = stock product

10 MINERAL COATINGS AND THIN PLASTER

Facade coating JSP 0.5



A polymer-modified coating with cement binder for brick and concrete surfaces. Maximum grain size 0.5 mm. Estimated usage: 4-6 kg/m² / two applications. Smallest manufacturing batch 100 kg/tint.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450852	Facade coating JSP 0.5 mm color 235	45085	25 kg	48 sk	-	-
6416841015617	Facade coating JSP 0.5 mm Fescon colors	45100	25 kg	48 sk	-	-

x = stock product

Facade coating JSP 1.5



A polymer-modified coating with cement binder for brick and concrete surfaces. Maximum grain size 1.5 mm. Estimated usage: 4-6 kg/m² / two applications. Smallest manufacturing batch 100 kg/tint.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450869	Facade coating JSP 1.5 mm Fescon 235	45086	25 kg	48 sk	x	-
6416841016065	Facade coating JSP 1.5 mm Fescon colors	45150	25 kg	48 sk	-	-

x = stock product



Lime-cement coating KSP

A coloured, polymer-modified lime-cement coating that can be spray-applied. Suitable for coating lime-cement plaster and brick surfaces. Largest grain size 1.5 mm. Estimated usage: 4-6 kg/m² /two applications. Smallest manufacturing batch 200 kg/tint.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841451514	Lime-cement coating KSP 1,5 mm Fescon colors	45151	25 kg	48 sk	-	-

x = stock product



Lime-cement coating JL

A spray-applied coloured lime cement finishing plaster. Other tints offered separately. Largest grain size 1.5 mm or 3.0 mm. Usage: 4-8 kg/m². Minimum manufacturing batch 1.5 mm 200 kg/tint and 3 mm 500 kg/tint.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450166	Lime-cement coating JL 1,5 mm color 235	45016	25 kg	48 sk	-	-
6416841015075	Lime-cement coating JL 1,5 mm Fescon colors	45200	25 kg	48 sk	-	-
6416841028495	Lime-cement coating JL 3,0 mm Fescon colors	45017	25 kg	48 sk	-	-

x = stock product



Thin-layer compo plaster KRL

Coloured lime-cement plaster for the thin-layer plastering of brick surfaces. Suitable for both spray and manual application. Other colours offered separately. Largest grain size 1.5 mm. Estimated usage: 5-8 kg/m². Smallest manufacturing batch 500 kg/tint.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841017031	Thin-layer compo plaster KRL 1,5 mm Fescon colors	45014	25 kg	48 sk	-	-

x = stock product

Antique plaster AL



Suitable for the coating, decorative coating and thin-layer plastering of concrete, sand-lime brick, burnt brick, lightweight aggregate block, sturdy concrete, levelling plaster, fibre plaster and cement levelling compound surfaces both indoors and outdoors. Maximum grain size 0.5 mm or 1.5 mm. Usage 3.5-5.5 kg/m²/ 2 applications. Colour white.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530318	Antique plaster AL 0,5 mm	53031	25 kg	48 sk	x	-
6416841530257	Antique plaster AL 1,5 mm	53025	25 kg	48 sk	x	-

x = stock product

Socle and adjusting plaster SOL



For the levelling and two-layer plastering of lightweight aggregate block foundation walls and walls, and concrete surfaces. Maximum grain size 0.6 mm. Levelling work 5-10 kg/m² (depending on how even the wall is). Estimated usage: 1 mm layer 1.5 kg/m².



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530066	Socle and adjusting plaster SOL	53006	25 kg	48 sk	x	x

x = stock product

Fibre plaster FL



Polymer-modified plaster with cement binder and added plastic fibres. For the plastering of lightweight aggregate and concrete block surfaces, and lightweight concrete and brick surfaces. Maximum grain size 0.6 mm. Estimated usage: 1 mm layer 1.5 kg/m².



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450210	Fibre plaster FL	45021	25 kg	48 sk	x	x

x = stock product



Levelling plaster TSL

A polymer-modified, cement-based plaster for levelling a thickly plastered precast element on the worksite. Maximum grain size 0.6 mm. Usage around approx. 1,6 kg/m²/layer. Stock product between 1 April and 30 September at the Hausjärvi factory.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841203106	Levelling plaster TSL	20310	25 kg	48 sk	-	-

x = stock product



Adhesive mortar FLL

A polymer-modified plaster with cement binder. For the fastening of Fescoterm thin-layer plastering insulation. Maximum grain size 0.6 mm. Usage 4.5 kg/m². Also available in winter grade.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450234	Adhesive mortar FLL	45023	25 kg	48 sk	x	-

x = stock product



Adhesive mortar FLL Winter ❄️

A polymer-modified plaster with cement binder for the fastening of Fescoterm thin-layer plastering insulation in the temperature range -10°C...+5°C. Maximum grain size 0.6 mm. Usage 4-5 kg/m².

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841640116	Adhesive mortar FLL Winter	64011	25 kg	48 sk	-	-

x = stock product

11 MINERAL BASED FACADE PAINTS

Stone colour KS



Facade paint with lime cement binder for brick and rendered surfaces. Maximum grain size 0.1 mm. Usage 0.3-0.8 kg/m²/ 2 applications. Smallest manufacturing batch 100 kg/tint.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450500	Stone colour KS 235 white	45050	15 kg	48 sk	-	-
6416841001344	Stone colour KS Fescon colors	45055	15 kg	48 sk	-	-

x = stock product

Stone colour S



Facade paint with cement binder for concrete surfaces. Maximum grain size 0.1 mm. Usage 0.3-0.8 kg/m²/ 2 applications. Smallest manufacturing batch 100 kg/tint.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450401	Stone colour S 235 white	45040	20 kg	48 sk	-	-
6416841016577	Stone colour S Fescon colors	45045	20 kg	48 sk	-	-

x = stock product

Lime paint KM

The lime paint is produced in a traditional manner from hand-picked, charcoal-burnt limestone, as well as lime stored for more than a year and wet-quenched with clean water. Other colors are offered separately.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841762689	Lime paint KM	76268	10 l	44 prk	-	-

x = stock product

12 LIQUID FACADE PAINTS AND COATINGS



Protective paint

Liquid, water-soluble, alkali-resistant acrylate paint for protecting concrete surfaces against moisture and carbonisation. Usage 0.2-0.5 l/m²/application.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841761002	Protective paint	76100	18 l	22 prk	x	-
	Protective paint HR 1 Fescon colors	50300	18 l		-	-
	Protective paint HR 2 other colors	50301	18 l		-	-

x = stock product



Silicone-resin primer MC

Solvent-free primer guaranteeing adhesion and even absorption for concrete, board and plaster surfaces, and paint surfaces in good condition. Primer for application before the Silicone resin coating and Fescosan coating. Usage 0.2 kg/m² (when thinned by 50%). Can be tinted.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760500	Silicone-resin primer MC	86050	15 kg	40 prk	x	-
	Silicone-resin primer MC HR 1 Fescon colors	50305	15 kg		-	-
	Silicone-resin primer MC HR 2 other colors	50306	15 kg		-	-

x = stock product

Silicone resin coating MC

A liquid, water-soluble silicone resin coating that is extremely breathable and water-resistant. This durable coating is suitable for new and previously coated stone surfaces on façades. It is also a coating product in the Fescoterm thin-layer plastering system. Usage: 2.2 - 4.2 kg/m² (depending on grain size). Grain sizes 1.5 and 3.0 mm also available to order. The silicone resin primer MC is used as the primer.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760685	Silicone resin coating MC 2 mm	86068	25 kg	24 prk	x	-
	Silicone resin coating MC HR 1 Fescon colors	50310	25 kg		-	-
	Silicone resin coating MC HR 2 other colors	50311	25 kg		-	-

x = stock product

Piirto Silicone resin coating

A liquid, water-soluble silicone resin coating that is extremely breathable and water-resistant. This durable coating is suitable for new and previously coated stone surfaces on façades. It is also a coating product in the Fescoterm thin-layer plastering system. Usage: 3.5 kg/m² (depending on grain size). The silicone resin primer MC is used as the primer.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760678	Piirto Silicone resin coating 2 mm	86067	25 kg	24 prk	-	-
	Piirto silicone resin coating HR 1 Fescon colors	50312	25 kg		-	-
	Piirto silicone resin coating HR 2 other colors	50313	25 kg		-	-

x = stock product

Fescosan-Coating



The silicone resin based Fescosan coating minimises dirt accumulation on the façade. Its homogeneous composition, optimal open time and good workability help achieve an extremely good result. The product is very water-resistant and weather-resistant and permeates water vapour. Fescosan offers good protection against algae and mould. Can be applied by rubbing and spraying. It is also a coating product in the Fescoterm thin-layer plastering system. Usage 2.2-4.2 kg/m² (depending on grain size). Also available in 1.5 and 3.0 mm grain sizes to order. The silicone resin primer MC is used as a primer.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760814	Fescosan-Coating 2 mm	86081	25 kg	24 prk	x	-
	Fescosan-Coating HR 1 Fescon colors	50314	25 kg		-	-
	Fescosan-Coating HR 2 other colors	50315	25 kg		-	-

x = stock product



Deeply penetrating primer

Colourless primer for sand-releasing and weak bases. Usage around 0.2 l/m²/application.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760661	Deeply penetrating primer	76066	10 l	60 prk	x	-

x = stock product

Silicone resin paint

A high-quality, matte finish silicone resin paint for façades that is highly permeable to water vapour. Suitable bases include mineral plaster surfaces, durable façade surfaces, and textured plaster surfaces. Usage: 0.2 l/m²/application.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760562	Silicone resin paint WHITE 235 12,5L	76056	12,5 l	32 prk	x	-
	Silicone resin paint HR 1 Fescon colors	50318	12,5 l		-	-
	Silicone resin paint HR 2 other colors	50319	12,5 l		-	-

x = stock product

Fescosan-Facade paint

A highly water-repellent, extremely high-quality façade paint with excellent opacity. Dries quickly into a rainproof coating even in adverse weather conditions, good colour fastness. Microporous and CO₂ permeable, weather and alkali resistant. Dirt-repellent and self-cleaning like bionic mechanisms (repels liquid, beading effect). The protection provided by the Fescosan-Facade paint prevents the growth of algae and fungi on the treated surface. Usage: 0.2 l/m²/application. Tinting net prices.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760708	Fescosan-Facade paint	76070	12,5 l	32 prk	x	-
	Fescosan-Facade paint HR 1 Fescon colors	50320	12,5 l		-	-
	Fescosan-Facade paint HR 2 other colors	50321	12,5 l		-	-

x = stock product



Silicate Primer

Colourless primer for the Silicate facade paint. Suitable for strengthening mineral bases. For evening the absorption of highly absorptive and sand-releasing surfaces. Does not contain solvents. Usage around 0.2-0.4 l/m² (thinned 2:1 with water)

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760616	Silicate Primer	76061	10 l	60 prk	x	-

x = stock product



Silicate facade paint

A high-quality potassium silicate based façade paint. Effective coverage. A silicate façade paint forms an extremely weather-resistant façade coating with good water vapour permeability. Suitable bases are masonry walls, previously plastered surfaces, and durable, previously silicate-coated surfaces. Usage: around 0.18-0.25 l/m²/application.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760623	Silicate facade paint 12,5L	76062	12,5 l	32 prk	x	-
	Silicate façade paint HR 1 Fescon colors	50322	12,5 l		-	-
	Silicate façade paint HR 2 other colors	50323	12,5 l		-	-

x = stock product

13 FESCOTERM PLASTERING ACCESSORIES

Permabase plastering board

Used in Fescopanel board plastering as a baseboard for plastering. For outdoor and indoor use. Grey colour.



					HAUSJÄRVI	HAUKIPUDAS
GTIN code	Product name	Product number	Package size	Platform size	In Stock	In Stock

x = stock product

Side moulding for board plastering with mesh

Used in Fescopanel board plastering at the side edges of the board. Length 2500 mm. 25 pcs./box. Colour white.




					HAUSJÄRVI	HAUKIPUDAS
GTIN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841501394	Side moulding for board plastering with mesh	50139	1 pcs		-	x

x = stock product

Side moulding for board plastering without mesh 2,5 m

Used in Fescopanel board plastering at the side edges of the board. Length 2500 mm. 20 pcs./box



					HAUSJÄRVI	HAUKIPUDAS
GTIN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841502070	Side moulding for board plastering with mesh 2,5 m	50207	1 pcs		x	-

x = stock product




Side moulding for board plastering without mesh

Used in Fescopanel board plastering at the side edges of the board. Length 2500 mm. 10 pcs./box

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501431	Side moulding for board plastering without mesh	50143	1 pcs		x	-

x = stock product



Bottom moulding for board plastering with mesh

Used in Fescopanel board plastering at the bottom edge of the board. Length 2500 mm. 20 pcs./box

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501554	Bottom moulding for board plastering with mesh	50155	1 pcs		x	-

x = stock product



Top moulding for board plastering


Used in Fescopanel board plastering at the top edge of the board. Length 2500 mm. 20 pcs./bundle. Colour white.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501288	Top moulding for board plastering 2,5 M	50128	1 pcs		x	-

x = stock product

Expansion joint with fibreglass mesh

The moulding is used as an expansion joint profile in plastering. Profile depth 6 mm. Length 2500 mm. A package contains 10 pcs.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501547	Expansion joint with mesh 2,5M	50154	1 pcs		x	-

x = stock product

Expansion joint with fibreglass mesh

The moulding is used as an expansion joint profile in plastering for 5-25 mm wide movement joints. Length 2500 mm. A package contains 25 pcs.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501943	Expansion joint with mesh 2,5M	50194	1 pcs		x	-
6416841501974	Expansion joint angle	50197	1 pcs		x	-

x = stock product


Ventilation profile for board plastering

Used in Fescopanel board plastering as a ventilation profile at the bottom of the wall.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501752	Ventilation profile for board plastering 25 mm	50175	1 pcs		x	-
6416841501769	Ventilation profile for board plastering 90 mm	50176	1 pcs		x	-

x = stock product




Angle guide profile 5 mm

Used for reinforcing outer corners in thin-layer plastering. Length 2500 mm 15 pcs./box.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501837	Angle guide profile 5 mm	50183	1 pcs		x	-

x = stock product




Socle moulding with mesh 6 mm

The PVC socle moulding with mesh is used as the starting strip in thin-layer plastering. Length 2500 mm. A package contains 25 pcs. Smallest delivery batch one package.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841040718	Socle moulding with mesh 6 mm	50177	1 pcs		x	-

x = stock product



Socle moulding 10 mm for thin-layer plastering

Used in thin-layer plastering as a starting and edge molding. Length 2.5 m. 25 pcs./box.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501530	Socle moulding 10 mm	50153	1 pcs		x	x

x = stock product

Socle moulding 8 mm for thin-layer plastering with mesh

A PVC starting strip, length 2000 mm.




GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501998	Socle moulding 8 mm for thin-layer plastering with mesh	50199	1 pcs		x	-

x = stock product

Water bar for thin plaster applications

Used as a water bar on the upper parts of thin plaster walls and under the water dampers of windows. Length 2500 mm. 10 pcs. / box.




GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501981	Water bar for thin plaster applications 2,5 m	50198	1 pcs		x	-

x = stock product


Bordering moulding with mesh 6 mm

Used in Fescopanel board plastering, for example for separation or mirroring. Length 2500 mm. 50 pcs./box



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501639	Bordering moulding with mesh 6 mm	50163	1 pcs		-	-

x = stock product




Fibreglass mesh

7 mm x 7 mm, width 1000 mm. The fibreglass mesh is used in board and thin-layer plastering on wall surfaces to strengthen the plastering surface. Can also be used with floor levelling compounds. Alkali-protected. One roll contains 50 m².

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841500380	Fibreglass mesh 1000 mm 50 m ² /roll	50038	1 roll	24 roll	x	x

x = stock product




Corner bead 100 x 150 mm

Used for corner reinforcement in thin-layer plastering. Length 2500 mm. 50 pcs/bundle. Smallest delivery batch one bundle.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841500502	Corner bead 100 x 150 mm	50050	1 pcs		x	x

x = stock product



Corner bead roll 90 x 110 mm

Used for corner reinforcement in thin-layer plastering. Angle can be freely adjusted between 0 and 180 degrees. Length 50 lineal metres. Smallest delivery batch one box.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501561	Corner bead roll 90 x 110 mm	50156	1 roll		x	-

x = stock product

Stick-on corner moulding 6 mm

Used for finishing window frames in thin-layer plastering. Length 2600 mm 30 pcs./box



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501844	Stick-on corner moulding 6 mm	50184	1 pcs		-	-

x = stock product

Stick-on corner moulding 10 mm

Used for finishing window frames in thin-layer plastering. The moulding is fastened to the window or door frame using the included adhesive tape. A protective plastic sheet can be easily fastened to the frame moulding with adhesive tape. Length 2600 mm. A package contains 60 pcs.




GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841500601	Stick-on corner moulding 10 mm white	50060	1 pcs		x	x

x = stock product

Stick-on corner moulding with mesh

Used for finishing window frames in thin-layer plastering. The moulding is fastened to the window or door frame using the included adhesive tape. A protective plastic sheet can be easily fastened to the frame moulding with adhesive tape. Length 2600 mm. A package contains 50 pcs.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501509	Stick-on corner moulding with mesh	50150	1 pcs		x	-

x = stock product




Stick-on corner moulding 9 mm grey

Used for finishing window frames in thin-layer plastering. Length 2600 mm. 60 pcs./box

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501578	Stick-on corner moulding 9 mm grey	50157	1 pcs		-	-

x = stock product



Stick-on corner moulding with mesh 9 mm grey

Length 2600 mm. 50 pcs./box

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501615	Stick-on corner moulding with mesh 9 mm grey	50161	1 pcs		-	-

x = stock product



Fescoterm aluminium profile


Aluminium profile for protecting the bottom edge of the insulation in the Fescoterm thin-layer plastering system. Package size 10 pcs/bundle. Smallest delivery batch one bundle. Length 2.5 m.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841500519	Fescoterm aluminium profile 50 mm 2,5 m	50051	1 pcs		-	-
6416841500526	Fescoterm aluminium profile 70 mm 2,5 m	50052	1 pcs		-	-
6416841500533	Fescoterm aluminium profile 100 mm 2,5 m	50053	1 pcs		-	-
6416841500540	Fescoterm aluminium profile 140 mm 2,5 m	50054	1 pcs		-	-
6416841500557	Fescoterm aluminium profile 160 mm 2,5 m	50055	1 pcs		-	-
6416841500571	Fescoterm aluminium profile 80 mm 2,5 m	50057	1 pcs		-	-
6416841501356	Fescoterm aluminium profile 180 mm 2,5 m	50135	1 pcs		-	-
6416841501363	Fescoterm aluminium profile 200 mm 2,5 m	50136	1 pcs		-	-
6416841501370	Fescoterm aluminium profile 200-300 mm	50137	1 pcs		-	-

x = stock product

Drip moulding with mesh

A mesh reinforcement attached to the front edge of the aluminium profile. Drip moulding.
Application thickness 10 mm. Length 2.5 m, 15 pcs/package.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501523	Drip moulding with mesh 2,5M	50152	1 pcs		-	-

x = stock product

Connector

Used to connect Fescoterm aluminium profiles to each other. Reduces the risk of cracking in insulation plastering. A bag contains 100 pcs. Supplied in batches of one bag.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501585	Connector 100 PCS	50158	100 pcs		-	-

x = stock product



Fescoterm plug fastener

The nylon fastener is used to fasten the Fescoterm thin-layer plastering system insulation.
Package size 100 pcs/box.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Fescoterm plug fastener 115 mm 100 pcs	50420	100 pcs		-	-
	Fescoterm plug fastener 135 mm 100 pcs	50421	100 pcs		-	-
	Fescoterm plug fastener 155 mm 100 pcs	50422	100 pcs		-	-
	Fescoterm plug fastener 175 mm 100 pcs	50423	100 pcs		-	-
	Fescoterm plug fastener 195 mm 100 pcs	50424	100 pcs		-	-
	Fescoterm plug fastener 215 mm 100 pcs	50425	100 pcs		-	-
	Fescoterm plug fastener 235 mm 100 pcs	50426	100 pcs		-	-
	Fescoterm plug fastener 275 mm 100 pcs	50427	100 pcs		-	-

x = stock product



Covering flange mineral wool

Used as a covering flange for the Fescoterm thin-layer plastering system's inset fasteners.
Diameter 65 mm, thickness 15 mm. 100 pcs/box.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501714	Covering flange mineral wool 100PCS	50171	100 pcs		-	-

x = stock product



Covering flange EPS

Used as a covering flange for the inset fasteners of the Fescoterm thin-layer plastering system. Diameter 65 mm, thickness 15 mm. 100 pcs/box.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501721	Covering flange EPS 100PCS	50172	100 pcs		-	-

x = stock product

Installation piece

For straightening the socle profile and adjusting its distance from the mounting surface on uneven surfaces. 100 pcs/box.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501738	Installation piece 100PCS	50173	100 pcs		-	-

x = stock product

Fastener for the Fescoterm thick-layer plastering system

A fastener for fastening the insulation and mesh to the bedding in the Fescoterm thick-layer plastering insulation system. Usage: 4-10 pcs/m². 100 pcs/box.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Fastener for the Fescoterm thick-layer plastering system	50097	100 pcs		-	-
	MERK mounting hook 50 mm 100 pcs	50400	100 pcs		-	-
	MERK mounting hook 70 mm 100 pcs	50401	100 pcs		-	-
	MERK mounting hook 100 mm 100 pcs	50402	100 pcs		-	-
	MERK mounting hook 150 mm 100 pcs	50403	100 pcs		-	-
	MERK mounting hook 160 mm 100 pcs	50404	100 pcs		-	-
	MERK mounting hook 170 mm 100 pcs	50405	100 pcs		-	-
	MERK mounting hook 180 mm 100 pcs	50406	100 pcs		-	-
	MERK mounting hook 200 mm 100 pcs	50407	100 pcs		-	-

x = stock product



Plaster mesh fastener RVK

Used in thick-layer plastering to fasten the mesh to the base so that it stays clear of the base. Material RST A2. 500 pcs/package.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501783	Plaster mesh fastener RVK 5/6	50178	500 pcs		-	-
6416841501790	Plaster mesh fastener RVK 10/6	50179	500 pcs		x	-

x = stock product



Plaster mesh Tammet

Hot-dip galvanised plaster mesh for thick-layer plastering. Opening size 19 x 19 mm/1.0 mm.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501486	Plaster mesh Tammet 250 mm	50148	1 roll	48 rll	-	-
6416841500120	Plaster mesh Tammet 1000 mm	50012	1 roll	12 rll	x	-
6416841500243	Plaster mesh Tammet 1500 mm	50024	1 roll	12 rll	x	-

x = stock product

14 SANDS

Seaming and blasting sand SPH

Seaming sand for the seaming of yard stones and slabs and sand blasting. Grain size 0.1-0.6 mm. Loose seaming sand delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610041	Seaming and blasting sand SPH 0,1-0,6 mm	61004	25 kg	48 sk	x	x
6416841620019	Seaming and blasting sand SPH 0,1-0,6 mm	62001	1000 kg		-	x
	Seaming and blasting sand SPH		1 kg		-	-

x = stock product

Seaming sand, black SHM

Hard, impermeable and almost dust-free black seaming sand for the seaming of yard stones and slabs. Grain size 0.1-0.6 mm. Also suitable for sandblasting. Loose seaming sand delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610133	Seaming sand, black SHM	61013	25 kg	48 sk	-	-
	Seaming sand, black SHM		1 kg		-	-

x = stock product



Blasting sand PH

Screened, clean natural sand for sand blasting. Grain size 0.5-1.6 mm. Loose blasting sand delivered in full carloads.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610058	Blasting sand PH 0,5-1,6 mm	61005	25 kg	48 sk	x	x
6416841620026	Blasting sand PH 0,5-1,6 mm	62002	1000 kg		-	x
	Blasting sand PH		1 kg		-	-

x = stock product



FescoStone Seaming sand

FescoStone is jointing sand for paving. FescoStone is made of natural sand and binders. FescoStone prevents weeds from growing, does not wash away with rain, and reduces the needs for maintaining the gaps between paving stones. Once the product has hardened, it still allows water to permeate through it, and it is suitable for seams of less than 5 mm. Recommended for grey concrete stones. Material usage: stone 60x140x280 mm, app. 3-4 kg/m²/2 mm seam width.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610195	FescoStone Seaming sand	61019	25 kg	48 sk	x	-

x = stock product

Sanding aggregate HSS

Dried gritting crushed stone macadam for gritting passages in yards and for preventing slipperiness. Grain size 3-6 mm. Pack size 20 kg plastic sack and a 1000 kg large sack.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610096	Sanding aggregate HSS 3-6 mm	61009	20 kg	48 sk	x	x
6416841610355	Sanding aggregate HSS 3-6 mm	61035	1000 kg		-	-

x = stock product

Playground sand LH

Screened, clean natural sand for yard construction, e.g. for sandboxes or installation use. Grain size 0-2 mm.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610072	Playground sand LH 0-2 mm	61007	25 kg	48 sk	x	-
6416841610119	Playground sand LH 0-2 mm	61011	1000 kg		-	-

x = stock product

Playground sand TRH

Playground sand is sieved, round, non-compacting, pure natural sand under playground equipment to minimise impact when tripping or falling. Playground sand grain size is 1-8 mm.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841620163	Playground sand TRH 1-8 mm	62016	1000 kg		-	-

x = stock product



Levelling sand TH

Screened, clean natural sand for the installation of yard stones and slabs, and the levelling of the base. Grain size 0-8 mm.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610065	Levelling sand TH 0-8 mm	61006	25 kg	48 sk	x	-
6416841610102	Levelling sand TH 0-8 mm	61010	1000 kg		-	-

x = stock product



Stone dust KVT

Crushed stone for driveways and garden paths and as foundation for levelling the ground for garden tiles. Grain size 0-6 mm, gray in color.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610126	Stone dust KVT 0-6 mm 25 kg	61012	25 kg	48 sk	x	-
6416841610300	Stone dust KVT 0-6 mm	61030	1000 kg		-	-

x = stock product



Aggregate SEP

Crushed stone for foundations and filling the sides of walls.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610409	Aggregate SEP 8 - 16 mm	61040	1000 kg		-	-

x = stock product

Black blasting abrasive PRM OKTO

Blasting abrasive is made of crushed, hard rock material. It is a coarse media suitable for sandblasting for both professional and home use. Hard abrasive is also suitable for seaming yard stones. Deep-cutting blasting abrasive is almost dust-free, making it an excellent media for sandblasting.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610164	Black blasting abrasive PRM OKTO	61016	25 kg	48 sk	-	-
6416841620156	Black blasting abrasive PRM OKTO	62015	1000 kg		-	-
	Black blasting abrasive PRM OKTO		1 kg		-	-

x = stock product

Filter sand

Filter sand produced by Fescon is widely used in a number of different water filtering processes. Our products are based on carefully selected raw materials and industrial sand processing methods. We provide precision sieved sand fractions for water filtering for all our customers' needs. Grain size: Standard sizes: 0.8–1.2 mm and 1.2–2.0 mm. Other fractions available where required. Delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841615831	Filter sand SUH 0,8-1,2 mm	61583	25 kg	48 sk	-	-
	Filter sand 0,8-1,2 mm		1000 kg		-	-
	Filter sand 0,8-1,2 mm		1 kg		-	-
	Filter sand 1,2-2,0 mm		25 kg		-	-
	Filter sand 1,2-2,0 mm		1000 kg		-	-
	Filter sand 1,2-2,0 mm		1 kg		-	-

x = stock product

Top-dressing sand for golf courses



Top-dressing sand is manufactured from natural sand. The sand is precision sieved to the desired fractions. The dust removal system at our plant considerably reduces the amount of fine particles in the sand, resulting in significantly less dust at the application stage compared to regular sand. The removal of excess dust also improves conditions at the putting green. Delivered in full carloads.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Top-dressing sand for golf courses		1 kg		-	-

x = stock product

Fairway sand for golf courses

Fairway sand is manufactured from natural sand. It can be made in two different ways, wet-sieved or precision-sieved. The benefit of precision-sieved product is its more precise fraction distribution. Delivered in full carloads.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Fairway sand for golf courses		1 kg		-	-

x = stock product



Bunker sand for golf courses

Bunker sand is manufactured from natural sand according to customer needs. Available in wet-sieved and precision-sieved varieties. Bunker sand meets USGA requirements. Delivered in full carloads.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Bunker sand for golf courses		1 kg		-	-

x = stock product

Top-dressing sand for natural grass

Top-dressing sand is manufactured from natural sand. The sand is precision sieved to the desired fractions. The dust removal system at our plant considerably reduces the amount of fine particles in the sand, resulting in significantly less dust at the application stage compared to regular sand. The removal of excess dust also improves conditions at the putting green. The sand meets FIFA's requirements for football pitches. Delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Top-dressing sand for natural grass		1 kg		-	-

x = stock product

Top-dressing sand for artificial turf

Top-dressing sand is manufactured from natural sand. The sand is precision sieved to the desired fractions. The dust removal system at our plant considerably reduces the amount of fine particles in the sand, resulting in significantly less dust at the application stage compared to regular sand. The removal of excess dust also improves conditions at the putting green. The sand meets FIFA's requirements for football pitches. Delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Top-dressing sand for artificial turf		1 kg		-	-

x = stock product

Long jump sand

Long jump sand is manufactured from natural sand, dried and precision sieved. During the manufacturing process, dust is removed from sand with a dust removal system; thanks to this procedure, the sand is almost dust-free. Complies with WA requirements. Delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Long jump sand		1 kg		-	-

x = stock product



Manège sand

Manège sand is manufactured from natural sand according to customer needs. Delivered in full carloads.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Manège sand		1 kg		-	-

x = stock product

Substrate for lawn

The substrate is manufactured from precision-sieved sand and sieved peat. Sand and peat are mixed to the desired ratio. The correct distribution of different fractions and the decomposition stage of peat have a major impact on the functioning of the substrate. Characteristics such as water permeability and moisture retention are important in the manufacturing of substrates. Delivered in full carloads.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Substrate for lawn		1 kg		-	-

x = stock product

Top-dressing sand for baseball fields (artificial turf)



Top-dressing sand is manufactured from natural sand. The sand is precision sieved to the desired fractions. The dust removal system at our plant considerably reduces the amount of fine particles in the sand, resulting in significantly less dust at the application stage compared to regular sand. The removal of excess dust also improves conditions at the putting green. Delivered in full carloads.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Top-dressing sand for baseball fields (artificial turf)		1 kg		-	-

x = stock product

Beach Volley sand

The sand is manufactured from natural sand, dried and precision sieved to the desired fractions. Meets the FIVB requirements of the International Volleyball Federation. Delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Beach Volley sand		1 kg		-	-

x = stock product

Playground sand for playgrounds

Playground sand is sieved, round, non-compacting, pure natural sand under playground equipment to minimise impact when tripping or falling. Playground sand grain size is 1-8 mm. Product tested and approved according to the SFS-EN 1177:2008 method. Delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Playground sand TRH		1 kg		-	-

x = stock product

Alkali-resistant bed material GR-GRANULI™

Thanks to its composition and high melting point, alkali-resistant GR-Granuli is suitable for power plants where difficult materials, such as glues, are incinerated, or where a very high bed temperature is required. The melting point of GR-Granuli is over 1400°C. Grain size: Standard grain size 0.5–1.5 mm. Other fractions available where required. Delivered in full carloads.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Alkali-resistant bed material GR-GRANULI™		1 kg		-	-

x = stock product



Bed sand HP 1000™ for standard boiler conditions

Bed sand manufactured from natural sand for standard boiler conditions. Grain size: Available in several different fractions. Delivered in full carloads.

					HAUSJÄRVI	HAUKIPUDAS
GTIN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
	Bed sand HP1000™ for standard boiler conditions		1 kg		-	-

x = stock product

15 FESCOTOP FLOOR HARDENERS

Fescotop F10

A quartz-based dry-shake hardener for hardening concrete surfaces. Grain size 3.0 mm. Available in 9 standard colours. Coloured dry-shake hardeners are offered separately. Minimum manufacturing batch of coloured dry-shake hardeners is 3 tonnes. Usage: 5-10 kg/m².



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770035	Fescotop F10 3 mm natural/betharm	77003	25 kg	48 sk	x	x
6416841771209	Fescotop F10 3 mm bright gray	77120	25 kg	48 sk	-	-
6416841770608	Fescotop F10 3 mm black	77060	25 kg	48 sk	-	-
6416841770615	Fescotop F10 3 mm bone white	77061	25 kg	48 sk	-	-
6416841770622	Fescotop F10 3 mm dark brown	77062	25 kg	48 sk	-	-
6416841770639	Fescotop F10 3 mm brown-gray	77063	25 kg	48 sk	-	-
6416841770646	Fescotop F10 3 mm terracotta	77064	25 kg	48 sk	-	-
6416841770653	Fescotop F10 3 mm green	77065	25 kg	48 sk	-	-
6416841770660	Fescotop F10 3 mm light blue	77066	25 kg	48 sk	-	-

x = stock product



Fescotop F45K

A corundum-based dry-shake hardener for hardening concrete surfaces. Grain size 3 mm. Available in 9 standard colours. Coloured dry-shake hardeners are offered separately. Minimum manufacturing batch of coloured dry-shake hardeners is 3 tonnes. Usage: 5-10 kg/m².

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770042	Fescotop F45K 3 mm natural/betharm	77004	25 kg	48 sk	x	x
6416841770011	Fescotop F45K 3 mm bright gray	77001	25 kg	48 sk	-	-
6416841770677	Fescotop F45K 3 mm black	77067	25 kg	48 sk	-	-
6416841770684	Fescotop F45K 3 mm bone white	77068	25 kg	48 sk	-	-
6416841770691	Fescotop F45K 3 mm dark brown	77069	25 kg	48 sk	-	-
6416841770707	Fescotop F45K 3 mm brown-gray	77070	25 kg	48 sk	-	-
6416841770714	Fescotop F45K 3 mm terracotta	77071	25 kg	48 sk	-	-
6416841770721	Fescotop F45K 3 mm green	77072	25 kg	48 sk	-	-
6416841770738	Fescotop F45K 3 mm light blue	77073	25 kg	48 sk	-	-

x = stock product



Fescotop F300

A corundum-based dry-shake hardener for hardening concrete surfaces. Grain size 3 mm. The minimum production batch is 3000 kg. Usage: 5-10 kg/m².

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770806	Fescotop F300 natural/betharm	77080	25 kg	48 sk	-	-

x = stock product

Fescotop F90K high-performance concrete

Fescotop F90K is a cement-based fibre-reinforced corundum hard concrete. Polymer modification in the product improves adhesion, allowing the product to be used without separate adhesion mortars. Hard concrete can be used on a hardened concrete floor or on fresh concrete casting. Fescotop F90K Hard concrete is intended for applications requiring heavy wear-resistant and corrosive-resistant compact concrete surfaces. Suitable for use in parking garages, driving ramps, industrial production and storage facilities, transport routes, and repair of deteriorated and worn concrete floors. Standard colour: concrete grey, other colours according to the Fescon colour map. Wear resistance class A6, maximum grain size 3 mm, compressive strength class C50, material usage approx 2,0 kg/m²/mm. Layer thickness 10 - 20 mm, partial levelling max. 50 mm. The minimum delivery lot for a big bags is 3000 kg.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770264	Fescotop F90K high-performance concrete natural/betharm 25 kg	77026	25 kg	48 sk	x	-
6416841770264	Fescotop F90K high-performance concrete natural/betharm 1000 kg	77036	1000 kg		-	-

x = stock product

Curing compound

One-component water-soluble polymer dispersion. Applied on fresh concrete to prevent the concrete from drying too rapidly. A clear liquid after drying. Coverage around 10 m² / l.



GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770226	Curing compound 5 L	77022	5 l	90 prk	-	-
6416841770219	Curing compound 20L	77021	20 l	32 prk	x	x

x = stock product

16 TOOLS



FescoBlaster FBL mortar pump

Hand-held mortar pump for applying plaster and concrete to seams and for fixing holes in concrete and stone structures, for example. A very high-quality, professionally designed mortar pump that allows you to easily apply different pastes into difficult places. Easy and simple to use: Pull the trigger to fill the pump's container, and then fill the hole by pushing the paste out of the pump.

GTIN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841100009	FescoBlaster FBL 1 Mortar pump, nozzle 18 mm rectangle	10000	1 pcs		x	-
6416841100016	FescoBlaster FBL 2 Mortar pump, nozzle 24 mm round, bent	10001	1 pcs		x	-
6416841100023	FescoBlaster FBL 3 Mortar pump, nozzle 18 mm rectangle, bent	10002	1 pcs		x	-
6416841100030	FescoBlaster FBL 4 Mortar pump, nozzle 10 mm rectangle	10003	1 pcs		x	-
6416841100054	FescoBlaster FBL 6 Mortar pumps, tubing 13 mm	10005	1 pcs		x	-
6416841100061	FescoBlaster FBL 7 Mortar pumps, tubing 25 mm	10006	1 pcs		x	-
6416841100108	FescoBlaster FBL piston, spare part	10010	1 pcs		x	-
6416841100115	FescoBlaster FBL pump cover, spare part	10011	1 pcs		x	-

x = stock product

Index

Adhesion promoter	40	Facade coating JSP 1.5	57
Adhesive mortar FLL	60	Fairway sand for golf courses	84
Adhesive mortar FLL Winter	60	Fastener for the Fescoterm thick-layer plastering system	77
Adhesive plaster TL	52	FescoBlaster FBL mortar pump	92
Aggregate SEP	82	Fescofine	33
Alkali-resistant bed material GR-GRANULI™	87	Fescorapid	33
Angle guide profile 5 mm	70	Fescosan-Coating	64
Antique plaster AL	59	Fescosan-Facade paint	65
Beach Volley sand	87	Fescoseal A+B	40
Bed sand HP1000™ for standard boiler conditions	88	FescoStone Seaming sand	80
Bedding plaster LF	27	Fescoterm aluminium profile	74
Bedding plaster LF RD	27	Fescoterm plug fastener	76
Bedding plaster VF	29	Fescotop F10	89
Black blasting abrasive PRM OKTO	83	Fescotop F300	90
Blasting sand PH	80	Fescotop F45K	90
Block mortar M100/500	23	Fescotop F90K high-performance concrete	91
Block mortar M100/500 Winter	24	Fibre plaster FL	59
Bolting plaster SR	51	Fibreglass mesh	72
Bordering moulding with mesh 6 mm	71	Filling plaster TLR	30
Bordering strip 30x30x2000 mm	37	Filter sand	83
Bordering strip 8x150 mm	37	Finishing plaster LRF	28
Bottom moulding for board plastering with mesh	68	Finishing plaster LRF RD	28
Brick bedding plaster TTF	28	Finishing plaster VHF	29
Bunker sand for golf courses	84	Fireproof casting concrete TKV	15
Cement concrete S 100	9	Fireproof masonry mortar TKM	15
Cement plaster S 30	7	Fireproof repairing compound TKK	16
Clay stove mortar SUL	15	Floor concrete LB 7	33
Coarse floor levelling compound LM 5000	32	Floor levelling plaster LT 4000	32
Compact mortar Heavy M100/600 Winter	22	Flow CS	34
Compact mortar Heavy M100/600	21	Flow FS	35
Compact mortar M100/600	19	Flow GS 3.0 mm Gypsum floor mass	36
Compact mortar M100/600 Winter	20	Flow Primer	36
Connector	75	FlowBase	35
Corner bead 100 x 150 mm	72	FlowPlan	34
Corner bead roll 90 x 110 mm	72	FPTL-165 Industrial mortar	16
Corro concrete K 45	8	Grouting concrete JB 1000/3	10
Corro concrete SR C35/45	9	Grouting concrete JB 600/3	10
Covering flange EPS	76	Grouting concrete SR JB 1000/3	11
Covering flange mineral wool	76	Grouting concrete TJB Winter	11
Curing compound	91	Gypsum plaster mix GL	30
Deeply penetrating primer	64	Indoor lime-cement plaster SR 7	30
Drain flange 300x300 mm fibre	42	Installation piece	77
Drain flange KL-B	42	Joint filler SF	27
Drip moulding with mesh	75	Korrogard R 0.6 mm	55
Dry concrete K-10 POZZ	54	Korrogard R 1.2 mm	55
Elevation mark	37	Korrogard R 3.0 mm	55
ELK Clinker element grout	26	Korroshot D KSD 5.0 mm	56
ELT Brick element grout	25	Levelling compound for wet areas WTT	29
Expansion joint with fibreglass mesh	69	Levelling plaster TSL	60
Expansion joint with fibreglass mesh	69	Levelling sand TH	82
Facade coating JSP 0.5	57	Lightweight lime-cement plaster KEV KS 35/65	49

Lime paint KM	61	Special concrete PIKIS	14
Lime plaster K100/1200	50	Stick-on corner moulding 10 mm	73
Lime-cement coating JL	58	Stick-on corner moulding 6 mm	73
Lime-cement coating KSP	58	Stick-on corner moulding 9 mm grey	74
Lime-cement plaster HD KS 20/80 fibre	49	Stick-on corner moulding with mesh	73
Lime-cement plaster HD KS 35/65 fibre	49	Stick-on corner moulding with mesh 9 mm grey	74
Lime-cement plaster KS 10/90	47	Stone adhesive KVL	24
Lime-cement plaster KS 35/65	47	Stone colour KS	61
Lime-cement plaster KS 50/50	48	Stone colour S	61
Lime-cement plaster KS 65/35	48	Stone dust KVT	82
Long jump sand	85	Substrate for lawn	86
Manège sand	86	Thin plaster S 06	7
Masonry mortar M100/600	17	Thin-layer compo plaster KRL	58
Masonry mortar M100/600 Winter	18	Tile adhesive plaster ILL	44
Mortar for tongue and groove blocks PHL Winter	25	Tile adhesive plaster SS2	44
Mortar for tongue-and-groove blocks PHL	24	Tile adhesive plaster SSL Lite	45
Overlevelling plaster YTL	53	Tile adhesive plaster VSL	44
Permabase plastering board	67	Tile seaming plaster SML	45
Piirto Silicone resin coating	63	Top moulding for board plastering	68
Plaster mesh fastener RVK	78	Top-dressing sand for artificial turf	85
Plaster mesh Tammet	78	Top-dressing sand for baseball fields (artificial turf)	86
Playground sand for playgrounds	87	Top-dressing sand for golf courses	84
Playground sand LH	81	Top-dressing sand for natural grass	85
Playground sand TRH	81	Underfloor heating filler LL 5500	32
Primer KP	41	Wall surface strengthening membrane	31
Primer PLUS	36	Water bar for thin plaster applications	71
Protective paint	62	Waterproofing accessories FS	43
Quick Drill 45	56	Waterproofing accessories VE	43
Rapid concrete PB	13	Waterproofing compound	39
Repair concrete RKB	54	Waterproofing compound WS	39
Repairing plaster KL 1.2	53	Waterproofing strip	41
Repairing plaster KL 40	53	Ventilation profile for board plastering	69
Sanding aggregate HSS	81	Vertical-joint concrete PSB K30	11
Sanitary silicone	46	Vertical-joint concrete PSB K40	12
Seaming and blasting sand SPH	79	Vertical-joint concrete PSB K50	13
Seaming sand, black SHM	79	Vertical-joint concrete winter TPSB K30	12
Separation fabric 1.5x50 m	38	Vertical-joint concrete winter TPSB K40	12
Side moulding for board plastering with mesh	67	Vertical-joint concrete winter TPSB K45	13
Side moulding for board plastering without mesh	68	Wet plaster	50
Side moulding for board plastering without mesh 2,5 m	67	Winter concrete TB S 30	8
Silicate facade paint	66	Winterbolting plaster SR	51
Silicate Primer	66	Winter-time masonry mortar TML	23
Silicone resin coating MC	63		
Silicone resin paint	65		
Silicone-resin primer MC	62		
SILKO Corro SKC C35/45	52		
SILKO Rapid Corro SPC C35/45	52		
Socle and adjusting plaster SOL	59		
Socle moulding 10 mm for thin-layer plastering	70		
Socle moulding 8 mm for thin-layer plastering with mesh	71		
Socle moulding with mesh 6 mm	70		



Master of Materials

A Finnish developer and manufacturer

Founded in 1984, Fescon Oy is the largest Finnish developer and manufacturer of mortar, sand and coating products and solutions for the construction sector and industry.

High-quality mortar, sand and coating products for construction

Fescon's main products are dry mortars and concretes, plaster and repair mortars, facade coatings and paints, wall and floor plasters, Nanten concrete floor coatings, insulation plastering systems, and tiling and water-proofing products. We also rent silo and mixing equipment for masonry and plastering sites. In addition, our sand business unit offers a variety of sand and mineral products. Our sand products business unit also offers various sands that are suitable for golf and sports courts,

Reliable and efficient logistics, and professional customer service

Fescon's strengths are quality products, reliable and fast deliveries, customer service, a fast colour card service and longterm product development in cooperation with customers.

We help professionals to achieve the best possible quality of work in all phases of the construction process and offer support for choosing the right products and solutions. Our technology services also

Fescon Oy

Hämeenkatu 9, FI-05800 Hyvinkää, Finland

tel. +358 20 789 5900 | fescon@fescon.fi

www.fescon.fi

Factories in Finland: Hausjärvi | Harjavalta | Haukipudas | Raahelä | Tuusula

