

SILICONE RESIN COATING MC 1,5 MM

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** SILICONE RESIN COATING MC 1,5 MM
- Other means of identification:**
Non-applicable
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Paints and varnishes
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Fescon Oy
Hämeenkatu 9
FI-05820 Hyvinkää - Suomi - Finland
Phone: +358 (0)20 789 5900
fescon@fescon.fi
www.fescon.fi
- 1.4 Emergency telephone number:** 112

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
CLP Regulation (EC) No 1272/2008:
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412
- 2.2 Label elements:**
CLP Regulation (EC) No 1272/2008:
Hazard statements:
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements:
P273: Avoid release to the environment.
P501: Dispose of contents/container according to the separated collection system used in your municipality.
Supplementary information:
EUH208: Contains 2-methyl-4-isothiazolin-3-one, octhlinone (ISO), reaction mass of (3:1): 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6]. May produce an allergic reaction.
EUH211: Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Additional labeling:
This paint contains a biocidal product with fungicidal and algaecidal properties. Active substance: isoproturon (ISO), Terbutryn, 3-iodo-2-propynol butylcarbamate. The water used for cleaning tools must not enter soil or surface water.
- 2.3 Other hazards:**
Product fails to meet PBT/vPvB criteria
Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

- 3.1 Substance:**
Non-applicable
- 3.2 Mixture:**
Chemical description: Mixture of substances
Components:
In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

SILICONE RESIN COATING MC 1,5 MM

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Chemical name/Classification		Concentration
CAS: 68855-54-9 EC: 272-489-0 Index: Non-applicable REACH: 01-2119488518-22-XXXX	Kieselguhr, soda ash flux-calcined (1 % < RCS < 10 %)⁽¹⁾	Self-classified	1 - <10 %
	Regulation 1272/2008	STOT RE 2: H373 - Warning	
CAS: 6846-50-0 EC: 229-934-9 Index: Non-applicable REACH: 01-2119451093-47-XXXX	1-isopropyl-2,2-dimethyltrimethylene diisobutyrat⁽¹⁾	Self-classified	0,1 - <1 %
	Regulation 1272/2008	Aquatic Chronic 3: H412; Repr. 2: H361 - Warning	
CAS: 26530-20-1 EC: 247-761-7 Index: 613-112-00-5 REACH: 01-2120768921-45-XXXX	octhilinone (ISO)⁽¹⁾	ATP ATP15	0,0025 - <0,025 %
	Regulation 1272/2008	Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1: H314; Skin Sens. 1A: H317; EUH071 - Danger	
CAS: 13463-41-7 EC: 236-671-3 Index: 613-333-00-7 REACH: 01-2119511196-46-XXXX	Pyrithione zinc⁽¹⁾	ATP ATP15	0,0001 - <0,01 %
	Regulation 1272/2008	Acute Tox. 2: H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Repr. 1B: H360D; STOT RE 1: H372 - Danger	
CAS: 2682-20-4 EC: 1272/2008 Index: Non-applicable REACH: Non-applicable	2-methyl-4-isothiazolin-3-one⁽¹⁾	ATP ATP13	<0,0015 %
	Regulation 1272/2008	Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1B: H314; Skin Sens. 1A: H317; EUH071 - Danger	
CAS: 55965-84-9 EC: Non-applicable Index: 613-167-00-5 REACH: Non-applicable	reaction mass of (3:1): 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6]⁽²⁾	Self-classified	<0,001 %
	Regulation 1272/2008	Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Corr. 1B: H314; Skin Sens. 1A: H317 - Danger	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

⁽²⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	M-factor	
octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	Acute	100
	Chronic	100
Pyrithione zinc CAS: 13463-41-7 EC: 236-671-3	Acute	1000
	Chronic	10
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	Acute	10
	Chronic	1
reaction mass of (3:1): 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] CAS: 55965-84-9 EC: Non-applicable	Acute	100
	Chronic	10

Identification	Specific concentration limit
octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	% (w/w) ≥ 0,0015: Skin Sens. 1A - H317
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	% (w/w) ≥ 0,0015: Skin Sens. 1A - H317
reaction mass of (3:1): 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] CAS: 55965-84-9 EC: Non-applicable	% (w/w) ≥ 0,6: Skin Corr. 1B - H314 0,06 ≤ % (w/w) < 0,6: Skin Irrit. 2 - H315 % (w/w) ≥ 0,06: Eye Irrit. 2 - H319 % (w/w) ≥ 0,0015: Skin Sens. 1A - H317

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 4: FIRST AID MEASURES (continued)

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occupational exposure limits		
Kieselguhr, soda ash flux-calcined (1 % < RCS < 10 %) CAS: 68855-54-9 EC: 272-489-0	IOELV (8h)		0,1 mg/m ³
	IOELV (STEL)		

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Kieselguhr, soda ash flux-calcined (1 % < RCS < 10 %) CAS: 68855-54-9 EC: 272-489-0	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,05 mg/m ³	Non-applicable
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate CAS: 6846-50-0 EC: 229-934-9	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	17,62 mg/m ³	Non-applicable
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	0,01 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	Non-applicable	Non-applicable

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0,043 mg/m ³	Non-applicable	0,021 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Kieselguhr, soda ash flux-calcined (1 % < RCS < 10 %) CAS: 68855-54-9 EC: 272-489-0	Oral	Non-applicable	Non-applicable	18,7 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	Non-applicable	0,05 mg/m ³	Non-applicable
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate CAS: 6846-50-0 EC: 229-934-9	Oral	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	5 mg/kg	Non-applicable
	Inhalation	Non-applicable	Non-applicable	4,35 mg/m ³	Non-applicable
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	Oral	0,053 mg/kg	Non-applicable	0,027 mg/kg	Non-applicable
	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
	Inhalation	Non-applicable	0,043 mg/m ³	Non-applicable	0,021 mg/m ³

PNEC:

Identification					
Kieselguhr, soda ash flux-calcined (1 % < RCS < 10 %) CAS: 68855-54-9 EC: 272-489-0	STP	100 mg/L	Fresh water	Non-applicable	
	Soil	Non-applicable	Marine water	Non-applicable	
	Intermittent	Non-applicable	Sediment (Fresh water)	Non-applicable	
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable	
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate CAS: 6846-50-0 EC: 229-934-9	STP	3 mg/L	Fresh water	0,014 mg/L	
	Soil	1,05 mg/kg	Marine water	0,001 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	5,29 mg/kg	
	Oral	0,0833 g/kg	Sediment (Marine water)	0,529 mg/kg	
octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	STP	Non-applicable	Fresh water	0,0022 mg/L	
	Soil	0,0082 mg/kg	Marine water	0,00022 mg/L	
	Intermittent	0,00122 mg/L	Sediment (Fresh water)	0,0475 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,00475 mg/kg	
Pyrrithione zinc CAS: 13463-41-7 EC: 236-671-3	STP	0,01 mg/L	Fresh water	0,00009 mg/L	
	Soil	1,02 mg/kg	Marine water	0,00009 mg/L	
	Intermittent	Non-applicable	Sediment (Fresh water)	0,009 mg/kg	
	Oral	Non-applicable	Sediment (Marine water)	0,009 mg/kg	
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	STP	0,23 mg/L	Fresh water	0,00339 mg/L	
	Soil	0,047 mg/kg	Marine water	0,00339 mg/L	
	Intermittent	0,00339 mg/L	Sediment (Fresh water)	Non-applicable	
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable	

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.



B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands



- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)



Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Protective gloves against minor risks			Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.



D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Panoramic glasses against splash/projections.		EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing			Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes		EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES
9.1 Information on basic physical and chemical properties:
Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	Not available
Odour:	Not available
Odour threshold:	Non-applicable *

Volatility:

Boiling point at atmospheric pressure:	280 °C
Vapour pressure at 20 °C:	6,24E-1 Pa
Vapour pressure at 50 °C:	7,33 Pa (0,01 kPa)
Evaporation rate at 20 °C:	Non-applicable *

Product description:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Density at 20 °C:	Non-applicable *
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	Non-applicable *
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	
Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	423 °C
Lower flammability limit:	Non-applicable *
Upper flammability limit:	Non-applicable *
Particle characteristics:	
Median equivalent diameter:	Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components:	Non-applicable *

Other safety characteristics:

Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 10: STABILITY AND REACTIVITY (continued)

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
- IARC: Non-applicable
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate CAS: 6846-50-0 EC: 229-934-9	LD50 oral	>5000 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	Non-applicable	
octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	LD50 oral	125 mg/kg	
	LD50 dermal	311 mg/kg	
	LC50 inhalation	Non-applicable	
Pyrethione zinc CAS: 13463-41-7 EC: 236-671-3	LD50 oral	221 mg/kg	Rat
	LD50 dermal	Non-applicable	
	LC50 inhalation	0,14 mg/L (4 h)	Rat
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	LD50 oral	120 mg/kg	Rat
	LD50 dermal	242 mg/kg	Rat
	LC50 inhalation	Non-applicable	
reaction mass of (3:1): 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] CAS: 55965-84-9 EC: Non-applicable	LD50 oral	64 mg/kg	Rat
	LD50 dermal	87,12 mg/kg	Rabbit
	LC50 inhalation	0,33 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

SILICONE RESIN COATING MC 1,5 MM

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration	Species	Genus
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate CAS: 6846-50-0 EC: 229-934-9	LC50 >10 - 100 (96 h)		Fish
	EC50 >10 - 100 (48 h)		Crustacean
	EC50 >10 - 100 (72 h)		Algae
octhilinone (ISO) CAS: 26530-20-1 EC: 247-761-7	LC50 >0.1 - 1 (96 h)		Fish
	EC50 >0.1 - 1 (48 h)		Crustacean
	EC50 >0.1 - 1 (72 h)		Algae
Pyrethione zinc CAS: 13463-41-7 EC: 236-671-3	LC50 0,003 mg/L (96 h)	Pimephales promelas	Fish
	EC50 0,008 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 Non-applicable		
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	LC50 4,77 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50 0,934 mg/L (48 h)	Daphnia magna	Crustacean
	EC50 Non-applicable		
reaction mass of (3:1): 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] CAS: 55965-84-9 EC: Non-applicable	LC50 >0.1 - 1 (96 h)		Fish
	EC50 >0.1 - 1 (48 h)		Crustacean
	EC50 >0.1 - 1 (72 h)		Algae

Chronic toxicity:

Identification	Concentration	Species	Genus
Pyrethione zinc CAS: 13463-41-7 EC: 236-671-3	NOEC Non-applicable		
	NOEC 0,022 mg/L	Daphnia magna	Crustacean
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	NOEC 4,93 mg/L	Oncorhynchus mykiss	Fish
	NOEC 0,044 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	Degradability	Biodegradability
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate CAS: 6846-50-0 EC: 229-934-9	BOD5 Non-applicable	Concentration 100 mg/L
	COD Non-applicable	Period 28 days
	BOD5/COD Non-applicable	% Biodegradable 39 %
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	BOD5 Non-applicable	Concentration 10 mg/L
	COD Non-applicable	Period 28 days
	BOD5/COD Non-applicable	% Biodegradable 55,8 %

12.3 Bioaccumulative potential:

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
1-isopropyl-2,2-dimethyltrimethylene diisobutyrate CAS: 6846-50-0 EC: 229-934-9	BCF	1
	Pow Log	4.1
	Potential	Low
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	BCF	
	Pow Log	-0.49
	Potential	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
2-methyl-4-isothiazolin-3-one CAS: 2682-20-4 EC: 1272/2008	Koc	Non-applicable	Henry	OE+0 Pa·m ³ /mol
	Conclusion	Non-applicable	Dry soil	Non-applicable
	Surface tension	Non-applicable	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:

SILICONE RESIN COATING MC 1,5 MM

SECTION 14: TRANSPORT INFORMATION (continued)

- 14.1 UN number or ID number:** Non-applicable
14.2 UN proper shipping name: Non-applicable
14.3 Transport hazard class(es): Non-applicable
 Labels: Non-applicable
14.4 Packing group: Non-applicable
14.5 Environmental hazards: No
14.6 Special precautions for user
 Special regulations: Non-applicable
 Tunnel restriction code: Non-applicable
 Physico-Chemical properties: see section 9
 Limited quantities: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 39-18:



- 14.1 UN number or ID number:** UN3082
14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (octhiline (ISO))
14.3 Transport hazard class(es): 9
 Labels: 9
14.4 Packing group: III
14.5 Marine pollutant: Yes
14.6 Special precautions for user
 Special regulations: 335, 969, 274
 EmS Codes: F-A, S-F
 Physico-Chemical properties: see section 9
 Limited quantities: 5 L
 Segregation group: Non-applicable
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



- 14.1 UN number or ID number:** UN3082
14.2 UN proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (octhiline (ISO))
14.3 Transport hazard class(es): 9
 Labels: 9
14.4 Packing group: III
14.5 Environmental hazards: Yes
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains reaction mass of (3:1): 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6], 2-methyl-4-isothiazolin-3-one, Pyridine zinc, octhiline (ISO).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 15: REGULATORY INFORMATION (continued)

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: octhilonone (ISO) (Product-type 6, 7, 8, 9, 10, 11, 13) ; Pyrithione zinc (Product-type 2, 6, 7, 9, 10, 21) ; 2-methyl-4-isothiazolin-3-one (Product-type 6, 11, 12, 13) ; reaction mass of (3:1): 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (Product-type 2, 4, 6, 11, 12, 13)
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Repr. 1B: H360D - May damage the unborn child.

Repr. 2: H361 - Suspected of damaging fertility or the unborn child.

Skin Corr. 1: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

- CONTINUED ON NEXT PAGE -

SILICONE RESIN COATING MC 1,5 MM

SECTION 16: OTHER INFORMATION (continued)

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
 IMDG: International maritime dangerous goods code
 IATA: International Air Transport Association
 ICAO: International Civil Aviation Organisation
 COD: Chemical Oxygen Demand
 BOD5: 5day biochemical oxygen demand
 BCF: Bioconcentration factor
 LD50: Lethal Dose 50
 LC50: Lethal Concentration 50
 EC50: Effective concentration 50
 LogPOW: Octanolwater partition coefficient
 Koc: Partition coefficient of organic carbon
 UFI: unique formula identifier
 IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -