


# FESCON



Product catalog 1.6.2022

EN

SCOPE	These terms and conditions apply to the domestic trade of products in the Fescon price list and those made to order. To the extent that the trade-related issues have not been otherwise agreed in these terms of delivery or separately, the general procurement and delivery terms for construction products (RYHT) shall be respected.
PRICE	Invoicing is done on the date of delivery at the valid price excluding tax. Value added tax is added to the sum total of the invoice.
TERM OF DELIVERY	Free carrier at the factory indicated in the price list (FCA, Finnterms 2001). Transports arranged by Fescon Oy will be charged in accordance with a separate transport price list. Sand deliveries under a separate agreement either FCA or DAP (Finnterms 2001).
PRODUCTS MADE TO ORDER	Orders for special products and products made to order are binding on the buyer. The buyer is obliged to receive and pay for the products made to order that the buyer has ordered. Fescon is entitled to charge the price and disposal costs of the product from the buyer if the buyer does not receive the products within the schedule indicated in the order confirmation.
TIME OF DELIVERY	<p>Products in stock in Hausjärvi and Haukiputaa, delivered either on full pallets or in large bags, can be picked up at the warehouse three (3) hours after placing the order at the customer service centre.</p> <p>Pick up of products in stock in partially full pallets: Can be picked up from the factory 1 working day after ordering. Products made to order can be picked up from the factory:</p> <ul style="list-style-type: none"> <li>- grey and fireproof products and sand products 10 business days after the order</li> <li>- coloured products 10 business after the order</li> <li>- rendering materials and other accessories according to agreement</li> </ul> <p>Work-site silos are delivered according to separate agreement and terms of delivery. The availability of work-site silos must be ensured on a site-specific basis. The binding delivery and return date of a silo must be communicated and confirmed six weeks before the delivery.</p>
PALLET SIZES AND PRICING	The products are packaged on pallets, which are either Fescon pallets in size 1,000 x 1,200 mm or EUR-pallets in size 800 x 1,200 mm. The number of bags per pallet depends on the product and is indicated in the price list. The price is €12.00 per pallet, excl. VAT. The price is valid until further notice. If the delivery method requires a pallet under each large bag, we charge the customer for the pallets in accordance with the currently valid pallet price list. Fescon does not accept pallets or make a refund for any.
ADDITIONAL FEE FOR COLLECTION / INCOMPLETE PALLETS	A fee of €15.00/delivery (VAT 0%) is charged for incomplete pallets and pallets that contain several products. This does not apply to product groups 7, 9–13. Only full pallets are delivered from Harjavalta and Raahe.
COMPLAINTS AND DAMAGES	<p>The buyer must inspect the goods delivered to the buyer immediately and report any faults and deficiencies without delay, and at the latest within eight (8) days of receiving them by indicating this in the waybill or using another method in writing. Errors that are noticeable only when using the product must be reported immediately before starting any casting, rendering, masonry or other use of the product. Fescon shall not be liable for any damage caused if the buyer has not made the said claims within the time limit and/or the buyer has taken the product into use contrary to the foregoing.</p> <p>The buyer must approve the tinted colour model delivered to the work site for the coloured façade products before ordering the actual product. Otherwise, Fescon will not be liable for any errors related to or resulting from the colour.</p>
INSTRUCTIONS	Before using the product, consult the product packaging and product specifications for more detailed instructions for use. Detailed product information is available at <a href="http://www.fescon.fi">www.fescon.fi</a>
LIABILITIES OF THE SUPPLIER AND BUYER	In addition to what is stated in the RYHT terms, Fescon Oy's liability for the product is limited to the information provided on the product datasheet, and matters excluded from liability comprise the structures, the events during storage and





processing, interaction with other products and any conditions with local effect. The buyer must note that the information reported on the product datasheet has been measured under standardised laboratory conditions. The selection of the product and the choices related to the use of the product shall be made project-specifically, taking into account the entire structure. If the product is to be used as part of a Fescon solution or system, the project structure must be formed in accordance with the instructions of the relevant system.

#### LIMITATION OF LIABILITY

Fescon shall not be liable for any consequential or indirect damages caused by a defect of the product or for any damages that are not foreseeable, unless Fescon has acted in a grossly negligent manner. In addition, Fescon's maximum liability to payment of compensation for any direct damages in all situations shall not exceed 500,000 euros, unless Fescon has acted in a grossly negligent manner.

#### WARRANTY PERIOD

Fescon's liability shall be limited to the errors for which the buyer has filed a complaint in writing within two years the delivery of the product. Tools have a warranty period of 12 months, but this does not extend to normal wear and tear.

#### RETURNS

We cannot accept returns.

#### CHANGES

Fescon reserves the right to changes in the price list and the terms of delivery.

#### DISPUTES

Any disputes arising out of the trade, which cannot be settled in mutual negotiations between Fescon and the buyer are to be resolved permanently by a sole-arbitrator arbitration tribunal in accordance with the arbitration rules of the Central Chamber of Commerce. The arbitration procedure is to be held in Finnish and in the jurisdiction of Helsinki. However, without prejudice to the foregoing, Fescon shall have the right to bring an action for claims before a court of general jurisdiction.

## Table of contents

1	Dry concretes and cement plasters	5
2	Fireplace mortars	12
3-4	Masonry mortars	14
5	Wall leveling compounds	25
6	Floor leveling products	30
7	Tiling plaster and waterproofing products	38
8	Plasters	46
9	Products for infrastructure construction and the repair of concrete surfaces	51
10	Mineral coatings and thin plaster	57
11	Mineral based facade paints	62
12	Liquid facade paints and coatings	63
13	Fescoterm plastering accessories	70
14	Sands	82
15	Fescotop floor hardeners	92
16	Tools	95

# 1 DRY CONCRETES AND CEMENT PLASTERS

## Thin plaster S 06

For the repair and patching of casting defects, and the repair and surface patching of concrete walls and roofs. Maximum grain size 0.6 mm. Ready-to-apply compound 13-14 l/25 kg.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841530189	Thin plaster S 06	53018	25 kg	49 sk	x	-
6416841330185	Thin plaster S 06	33018	1000 kg		-	-

x = stock product

## Cement plaster S 30

Suitable for casting thin surface flooring and corridor tiles, and the repair of casting defects and concrete structures. Maximum grain size 3 mm. Strength class C 30/37. Ready-to-apply compound 12-13 l/25 kg. Frost-resistant



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841530202	CEMENT PLASTER S 30	53020	25 kg	49 sk	x	x
6416841330208	CEMENT PLASTER S 30	33020	1000 kg		x	x

x = stock product



## Winter concrete TB S 30 ❄️

Special concrete for grouting and concrete work. Frost-resistant Largest grain size 3 mm. Strength class C 25/30. Ready-to-apply compound ca. 500 l/1000 kg. Working temperature +5°C...-15°C.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530042	WINTER CONCRETE TB S 30	53004	25 kg	49 sk	x	x
6416841330048	WINTER CONCRETE TB S 30	33004	1000 kg		x	x

x = stock product



## Winter concrete TB S 40 ❄️

Special concrete for grouting and concrete work. Frost-resistant Largest grain size 3 mm. Strength class C 30/37. Ready-to-apply compound 11-12 l/25 kg. Working temperature +5°C...-15°C.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530271	WINTER CONCRETE TB S 40	53027	25 kg	49 sk	x	-
6416841330277	WINTER CONCRETE TB S 40	33027	1000 kg		x	-

x = stock product



## Corro concrete K 30

Special concrete C 25/30 strength class casting. Frost-resistant Good wear resistance and tightness. Maximum grain size 3 mm. Ready-to-apply compound around 500 l/1000 kg. Grain size 10 mm also available to order (only in 1000 kg packages).

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330130	CORRO CONCRETE K 30	33013	1000 kg		-	-

x = stock product

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.

## Corro concrete K 45

Special concrete C 35/45 strength class casting. Frost-resistant Good wear resistance and tightness. Maximum grain size 3 mm. Ready-to-apply compound 11-12 l/25 kg. Grain size 10 mm also available to order (only in 1000 kg packages).



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530264	CORRO CONCRETE K 45	53026	25 kg	49 sk	x	-
6416841330260	CORRO CONCRETE K 45	33026	1000 kg		x	-

x = stock product

## Cement concrete S 100

Basic concrete for general casting work. Maximum grain size 10 mm. Compressive strength around 25 MPa. Ready-to-apply compound 12-13-25 l/25 kg. Frost-resistant



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530219	CEMENT CONCRETE S 100	53021	25 kg	49 sk	x	x
6416841330963	CEMENT CONCRETE S 100	33096	500 kg		x	x
6416841330215	CEMENT CONCRETE S 100	33021	1000 kg		x	x

x = stock product



## Grouting concrete JB 600/3

High-strength concrete that expands before setting, intended for grouting and supplementary casting in narrow and difficult spaces. The main applications are installation and jointing casting of pre-cast concrete elements and various anchor grouts. Maximum grain size 3 mm. Strength class C 50/60. SILKO-approved. Ready-to-apply compound 11-12-25 l/25 kg. Meets the requirements of the R4 class.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530226	GROUTING CONCRETE JB 600/3	53022	25 kg	49 sk	x	x
6416841330222	GROUTING CONCRETE JB 600/3	33022	1000 kg		x	x

x = stock product



## Grouting concrete JB 1000/3

A very high-quality concrete for demanding precision casting, such as the fastening and installation castings of machinery. Due to slight expansion that takes place before setting, the concrete fills the casting space well. Largest grain size 3 mm. Strength class C 60/75. Ready-to-apply compound 11-12 l/25 kg. SILKO-approved. Meets the requirements of the R4 class.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530233	GROUTING CONCRETE JB 1000/3	53023	25 kg	49 sk	x	-
6416841330239	GROUTING CONCRETE JB 1000/3	33023	1000 kg		x	-

x = stock product



## Grouting concrete TJB Winter ❄️

Special concrete that expands before setting for grouting and small-scale concrete work and anchor grouting. Maximum grain size 3 mm. Strength class C40/50. Ready-to-apply compound 11-12-25 l/25 kg. Working temperature +5°C...-15°C.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530141	GROUTING CONCRETE TJB WINTER	53014	25 kg	49 sk	x	x
6416841330147	GROUTING CONCRETE TJB WINTER	33014	1000 kg		x	x

x = stock product

## Vertical-joint concrete PSB K30

A non-sag, pumpable special compound for the vertical grouting of concrete elements. Largest grain size 3 mm. Ready-to-apply compound ca. 500 l/1000 kg. Strength class C 25/30.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330352	VERTICAL-JOINT CONCRETE PSB K 30	33035	1000 kg		x	x

x = stock product

## Vertical-joint concrete winter TPSB K30 ❄️

A non-sag, pumpable special compound for the vertical grouting of concrete elements in winter conditions. Frost-resistant Largest grain size 3 mm. Ready-to-apply compound ca. 500 l/1000 kg. Working temperature +5°C – -15°C. Strength class C 25/30.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330369	VERTICAL-JOINT CONCRETE WINTER TPSB K30	33036	1000 kg		x	x

x = stock product

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.



## Vertical-joint concrete PSB K40

A non-sag, pumpable special compound for the vertical grouting of concrete elements. Largest grain size 3 mm. Ready-to-apply compound ca. 500 l/1000 kg. Strength class C 30/37.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330031	VERTICAL-JOINT CONCRETE PSB K 40	33003	1000 kg		x	-

x = stock product



## Vertical-joint concrete winter TPSB K40 ❄️

A non-sag, pumpable special compound for the vertical grouting of concrete elements in winter conditions. Frost-resistant Largest grain size 3 mm. Ready-to-apply compound ca. 500 l/1000 kg. Working temperature +5°C – -15°C. Strength class C 30/37.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330949	VERTICAL-JOINT CONCRETE WINTER TPSB K40	33094	1000 kg		x	-

x = stock product



## Vertical-joint concrete PSB K50

A non-sag, pumpable special compound for the vertical grouting of concrete elements. Largest grain size 3 mm. Ready-to-apply compound ca. 500 l/1000 kg. Strength class C 40/50.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841333476	VERTICAL-JOINT CONCRETE PSB K 50	33347	1000 kg		-	-

x = stock product

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.

## Vertical-joint concrete winter TPSB K45 ❄️

A non-sag, pumpable special compound for the vertical grouting of concrete elements in winter conditions. Frost-resistant Largest grain size 3 mm. Ready-to-apply compound ca. 500 l/1000 kg. Working temperature +5°C – -15°C. Strength class C 35/45.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841333568	Vertical-joint concrete winter TPSB K45	33356	1000 kg		-	-

x = stock product

## Rapid concrete PB

A special concrete with a rapid strength gain that is suited to, for example, repairs of concrete structures, supplementary casting and floor casting. Strength class C 30/37. Largest grain size 3 mm. Ready-to-apply compound 12-13 l/25 kg. Grain size 10 mm also available to order.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841530240	RAPID CONCRETE PB	53024	25 kg	49 sk	x	x
6416841331281	RAPID CONCRETE PB	33128	1000 kg		-	-

x = stock product

## Special concrete PIKIS

Cement-based, super fast setting and hardening special concrete. Applications: Repairs of concrete surfaces, quick-casting or poles and structures as well as repairs of concrete wells. Not suitable for load-bearing structures.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841531063	Special concrete PIKIS 25 can	53106	25 kg	24 prk	-	-
6416841531070	Special concrete PIKIS 25 kg sack	53107	25 kg	49 sk	-	-

x = stock product

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.

## 2 FIREPLACE MORTARS



### Clay stove mortar SUL

For the burnt brick masonry of the frame and flues of wood-heated fireplaces indoors. Fireproof mortar must be used in fireplace masonry. Regular masonry mortar is used for the separate shell.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530653	CLAY STOVE MORTAR SUL	53065	25 kg	49 sk	x	x

x = stock product



### Fireproof masonry mortar TKM

For laying firebricks used in indoor wood-fired household fireplaces. Heat resistance over +1200 °C. A 25 kg bag yields 12-13 litres of finished mortar, which is enough for laying around 100 firebricks.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841630667	FIREPROOF MASONRY MORTAR TKM	63066	5 kg		x	x
6416841530660	FIREPROOF MASONRY MORTAR TKM	53066	25 kg	49 sk	x	x

x = stock product



### Fireproof casting concrete TKV

For the parts of ovens, fireplaces, grills and sauna stoves that need to be fireproof. Maximum operating temperature +1200°C. Minimum casting thickness 50 mm. Ready-to-apply compound 11-12 l/25 kg. Remains usable for one hour. Do not use reinforcement.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530677	FIREPROOF CASTING CONCRETE TKV	53067	25 kg	49 sk	x	x

x = stock product



## Fireproof repairing compound TTK

For patching chips, cracks and cavities in the fire boxes of household fireplaces.  
Heat resistance +1300°C.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631510	FIREPROOF REPAIRING COMPOUND TTK	63151	2 kg	60 prk	x	x
6416841531056	Fireproof repairing compound TTK	53105	25 kg	49 sk	-	-

x = stock product

## Pipe riser sealing compound HTM

Fireproof special mortar for internal sealing of pipe risers. The compound contains fireproof fibres. Does not contain flammable components.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841531087	Pipe riser sealing compound HTM	53108	25 kg	49 sk	-	-

x = stock product

## FPTL-165 Industrial mortar

Chemical-ceramic binding mortar for applications with a temperature of max. +1650°C.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841531094	FPTL-165 Industrial mortar	53109	25 kg	49 sk	-	-

x = stock product

## 3-4 MASONRY MORTARS

### Masonry mortar M100/600



Cement-based mortar for burnt and sand-lime brick masonry outdoors and indoors. For brick work jointing, jointing of natural and slate stones on vertical surfaces and for repairing existing mortar joints. For cold flue parts in chimney masonry, such as in cold attics and above the roof, as well as for the masonry of the outer brick shell of the fireplace. Maximum grain size 2.0 mm. Material usage 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT. Amount of finished mortar: 13 - 14 l / 25 kg.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530387	MASONRY MORTAR 100/600	53038	25 kg	49 sk	x	x
6416841330376	MASONRY MORTAR 100/600	33037	500 kg		x	x
6416841330383	MASONRY MORTAR 100/600	33038	1000 kg		x	x
6416841530394	MASONRY MORTAR 39 QUARTZ WHITE	53039	25 kg	49 sk	x	-
6416841330390	MASONRY MORTAR 39 QUARTZ WHITE	33039	1000 kg		-	-
6416841530592	Masonry mortar 59 Birch bark white	53059	25 kg	49 sk	x	-
6416841330598	Masonry mortar 59 Birch bark white	33059	1000 kg		-	-
6416841530400	Masonry mortar 40 Lime gray	53040	25 kg	49 sk	-	-
6416841330406	Masonry mortar 40 Lime gray	33040	1000 kg		-	-
6416841330413	Masonry mortar 41 Grain yellow	33041	1000 kg		-	-
6416841330420	Masonry mortar 42 Brick red	33042	1000 kg		-	-
6416841330451	Masonry mortar 45 Earth brown	33045	1000 kg		-	-
6416841530462	Masonry mortar 46 Peat brown	53046	25 kg	49 sk	x	-
6416841330468	Masonry mortar 46 Peat brown	33046	1000 kg		-	-
6416841530486	Masonry mortar 48 Black gray	53048	25 kg	49 sk	x	-
6416841330482	Masonry mortar 48 Black gray	33048	1000 kg		-	-
6416841530523	MASONRY MORTAR 52 LINEN LIGHT	53052	25 kg	49 sk	-	-
6416841330529	MASONRY MORTAR 52 LINEN LIGHT	33052	1000 kg		-	-
6416841330444	MASONRY MORTAR 44 SAND BROWN	33044	1000 kg		-	-
6416841339225	MASONRY MORTAR 71 SWAN	33922	1000 kg		-	-
6416841339263	Masonry mortar 72 Capercaillie	33926	1000 kg		-	-
6416841339270	MASONRY MORTAR 73 CUCKOO	33927	1000 kg		-	-
6416841339218	Masonry mortar 74 Hawk	33933	1000 kg		-	-
6416841339249	MASONRY MORTAR 75 LARK	33924	1000 kg		-	-

6416841339201	MASONRY MORTAR 77	33920	1000 kg		-	-
6416841339256	MASONRY MORTAR 79 PTARMIGAN	33925	1000 kg		-	-
6416841339287	MASONRY MORTAR 80 SIBERIAN JAY	33928	1000 kg		-	-
6416841339324	MASONRY MORTAR 81 TEAL	33932	1000 kg		-	-
6416841339218	Masonry mortar 82 Capercaillie	33921	1000 kg		-	-
6416841339362	MASONRY MORTAR 83 WILLOW GROUSE	33936	1000 kg		-	-
6416841339348	MASONRY MORTAR 85 RAVEN	33934	1000 kg		-	-
6416841339355	Masonry mortar 86 Hazel hen	33935	1000 kg		-	-

x = stock product

## Masonry mortar M100/600 Winter ❄️

Cement-based mortar for burnt and sand-lime brick facade masonry in winter conditions in the temperature range -15°C...+5°C. Suitable for brickwork repointing and for repairing mortar joints. The maximum grain size is 2.0 mm. Material usage 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330703	MASONRY MORTAR M100/600 WINTER	33070	1000 kg		x	-
6416841340009	MASONRY MORTAR 39 QUARTZ WHITE WINTER	34000	1000 kg		-	-
6416841340016	MASONRY MORTAR 59 BIRCH BARK WHITE WINTER	34001	1000 kg		-	-
6416841340023	MASONRY MORTAR 40 LIME GRAY WINTER	34002	1000 kg		-	-
6416841340030	MASONRY MORTAR 41 GRAIN YELLOW WINTER	34003	1000 kg		-	-
6416841340047	MASONRY MORTAR 42 BRICK RED WINTER	34004	1000 kg		-	-
6416841340054	MASONRY MORTAR 45 EARTH BROWN WINTER	34005	1000 kg		-	-
6416841340061	MASONRY MORTAR 46 PEAT BROWN WINTER	34006	1000 kg		-	-
6416841340078	MASONRY MORTAR 48 BLACK GRAY WINTER	34007	1000 kg		-	-
6416841340085	MASONRY MORTAR 52 LINEN LIGHT WINTER	34008	1000 kg		-	-
6416841340306	MASONRY MORTAR 44 SAND BROWN WINTER	34030	1000 kg		-	-
6416841340221	MASONRY MORTAR 71 SWAN WINTER	34022	1000 kg		-	-
6416841340252	Masonry mortar 72 Ali Winter	34025	1000 kg		-	-
6416841340276	MASONRY MORTAR 73 CUCKOO WINTER	34027	1000 kg		-	-
6416841340153	Masonry mortar 74 Hawk Winter	34015	1000 kg		-	-
6416841340269	MASONRY MORTAR 75 LARK WINTER	34026	1000 kg		-	-

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.

6416841340207	MASONRY MORTAR 77 WINTER	34020	1000 kg		-	-
6416841340245	MASONRY MORTAR 79 PTARMIGAN WINTER	34024	1000 kg		-	-
6416841340290	MASONRY MORTAR 80 SIBERIAN JAY WINTER	34029	1000 kg		-	-
6416841340115	MASONRY MORTAR 81 TEAL WINTER	34011	1000 kg		-	-
6416841340214	Masonry mortar 82 Capercaillie Winter	34021	1000 kg		-	-
6416841340320	MASONRY MORTAR 83 WILLOW GROUSE WINTER	34032	1000 kg		-	-
6416841340122	MASONRY MORTAR 85 RAVEN WINTER	34012	1000 kg		-	-
6416841340139	Masonry mortar 86 Hazel hen Winter	34013	1000 kg		-	-

x = stock product



## Compact mortar M100/600

Cement-based mortar for burnt and sand-lime brick masonry for facades exposed to harsh weather conditions. Suitable for locations subject to heavy slanted rain. Suitable for repointing brickwork and natural and slate stones on vertical surfaces, and for repairing mortar joints. Contains additives to improve density, weather resistance and workability. Maximum grain size 2.0 mm. Usage: 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331007	COMPACT MORTAR M 100/600	33100	1000 kg		x	-
6416841331335	Compact mortar 39 Quartz white	33133	1000 kg		-	-
6416841331014	Compact mortar 59 Birch bark white	33101	1000 kg		-	-
6416841331045	Compact mortar 40 Lime gray	33104	1000 kg		-	-
6416841331038	Compact mortar 41 Grain yellow	33103	1000 kg		-	-
6416841344250	Compact mortar 42 Brick red	34425	1000 kg		-	-
6416841331052	Compact mortar 45 Earth brown	33105	1000 kg		-	-
6416841331069	Compact mortar 46 Peat brown	33106	1000 kg		-	-
6416841331076	Compact mortar 48 Black gray	33107	1000 kg		-	-
6416841344274	COMPACT MORTAR 52 LINEN LIGHT	34427	1000 kg		-	-
6416841344182	COMPACT MORTAR 44 SAND BROWN	34418	1000 kg		-	-
6416841344137	COMPACT MORTAR 71 SWAN	34413	1000 kg		-	-
6416841344168	Compact mortar 72 Alli	34416	1000 kg		-	-
6416841344083	COMPACT MORTAR 73 CUCKOO	34408	1000 kg		-	-
6416841344144	Compact mortar 74 Hawk	34414	1000 kg		-	-
6416841344113	COMPACT MORTAR 75 LARK	34411	1000 kg		-	-



6416841344120	COMPACT MORTAR 77	34412	1000 kg		-	-
6416841344106	COMPACT MORTAR 79 PTARMIGAN	34410	1000 kg		-	-
6416841344243	COMPACT MORTAR 80 SIBERIAN JAY	34424	1000 kg		-	-
6416841344298	COMPACT MORTAR 81 TEAL	34429	1000 kg		-	-
6416841344151	Compact mortar 82 Capercaillie	34415	1000 kg		-	-
6416841344229	COMPACT MORTAR 83 WILLOW GROUSE	34422	1000 kg		-	-
6416841344199	COMPACT MORTAR 85 RAVEN	34419	1000 kg		-	-
6416841344236	Compact mortar 86 Hazel hen	34423	1000 kg		-	-

x = stock product

## Compact mortar M100/600 Winter ❄️

Cement-based mortar for burnt and sand-lime brick masonry for facades exposed to harsh winter weather in the temperature range -15°C...+5°C. Suitable for locations subject to heavy slanted rain. Suitable for repointing brickwork and natural and slate stones on vertical surfaces, and for repairing mortar joints. Contains additives to improve density, weather resistance and workability. Usage: 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331106	COMPACT MORTAR M 100/600 WINTER	33110	1000 kg		-	-
6416841335418	COMPACT MORTAR 39 QUARTZ WHITE WINTER	33541	1000 kg		-	-
6416841331199	COMPACT MORTAR 59 BIRCH BARK WHITE WINTER	33119	1000 kg		-	-
6416841345424	COMPACT MORTAR 40 WINTER	34542	1000 kg		-	-
6416841345417	COMPACT MORTAR 41 GRAIN YELLOW WINTER	34541	1000 kg		-	-
6416841345158	COMPACT MORTAR 42 BRICK RED WINTER	34515	1000 kg		-	-
6416841345455	COMPACT MORTAR 45 EARTH BROWN WINTER	34545	1000 kg		-	-
6416841345622	COMPACT MORTAR 46 PEAT BROWN WINTER	34562	1000 kg		-	-
6416841345479	COMPACT MORTAR 48 BLACK GRAY WINTER	34547	1000 kg		-	-
6416841345172	COMPACT MORTAR 52 LINEN LIGHT WINTER	34517	1000 kg		-	-
6416841345486	COMPACT MORTAR 44 SAND BROWN WINTER	34548	1000 kg		-	-
6416841335579	COMPACT MORTAR 71 SWAN WINTER	34557	1000 kg		-	-
6416841345615	Compact mortar 72 Alli Winter	34561	1000 kg		-	-
6416841345684	COMPACT MORTAR 73 CUCKOO WINTER	34568	1000 kg		-	-
6416841345547	Compact mortar 74 Hawk Winter	34554	1000 kg		-	-
6416841345561	COMPACT MORTAR 75 LARK WINTER	34556	1000 kg		-	-

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.

6416841345509	COMPACT MORTAR 77 WINTER	34550	1000 kg		-	-
6416841345608	COMPACT MORTAR 79 PTARMIGAN WINTER	34560	1000 kg		-	-
6416841345660	COMPACT MORTAR 80 SIBERIAN JAY WINTER	34566	1000 kg		-	-
6416841345585	COMPACT MORTAR 81 TEAL WINTER	34558	1000 kg		-	-
6416841345516	Compact mortar 82 Capercaillie Winter	34551	1000 kg		-	-
6416841345677	COMPACT MORTAR 83 WILLOW GROUSE WINTER	34567	1000 kg		-	-
6416841345639	COMPACT MORTAR 85 RAVEN WINTER	34563	1000 kg		-	-
6416841345653	Compact mortar 86 Hazel hen Winter	34565	1000 kg		-	-

x = stock product

## Compact mortar Heavy M100/600



Cement-based mortar for burnt and sand-lime brick masonry for facades exposed to extremely harsh weather. Especially suitable for coastal sites where structures will have to withstand wind and weathering. Suitable for brickwork repointing and for repairing mortar joints. Contains additives to improve density, weather resistance and workability. Maximum grain size 2.0 mm. Usage: 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841344601	COMPACT MORTAR HEAVY M100/600	34460	1000 kg		-	-
6416841345011	COMPACT MORTAR HEAVY 39 KVARTSINVALKOINEN	34501	1000 kg		-	-
6416841345028	Compact mortar Heavy 59 Birch bark white	34502	1000 kg		-	-
6416841345035	Compact mortar Heavy 40 Lime gray	34503	1000 kg		-	-
6416841345042	Compact mortar Heavy 41 Grain yellow	34504	1000 kg		-	-
6416841345059	Compact mortar Heavy 42 Brick red	34505	1000 kg		-	-
6416841345066	Compact mortar Heavy 45 Earth brown	34506	1000 kg		-	-
6416841345073	Compact mortar Heavy 46 Peat brown	34507	1000 kg		-	-
6416841345080	Compact mortar Heavy 48 Black gray	34508	1000 kg		-	-
6416841345097	COMPACT MORTAR HEAVY 52 LINEN LIGHT	34509	1000 kg		-	-
6416841345189	COMPACT MORTAR HEAVY 44 SAND BROWN	34518	1000 kg		-	-
6416841345202	COMPACT MORTAR HEAVY 71 SWAN	34520	1000 kg		-	-
6416841345165	Compact mortar Heavy 72 Alli	34516	1000 kg		-	-
6416841345141	COMPACT MORTAR HEAVY 73 CUCKOO	34514	1000 kg		-	-
6416841344649	Compact mortar Heavy 74 Hawk	34464	1000 kg		-	-
6416841345110	COMPACT MORTAR HEAVY 75 LARK	34511	1000 kg		-	-

6416841345127	COMPACT MORTAR HEAVY 77	34512	1000 kg		-	-
6416841345103	COMPACT MORTAR HEAVY 79 PTARMIGAN	34510	1000 kg		-	-
6416841345240	COMPACT MORTAR HEAVY 80 SIBERIAN JAY	34524	1000 kg		-	-
6416841345219	COMPACT MORTAR HEAVY 81 TEAL	34521	1000 kg		-	-
6416841344410	Compact mortar Heavy 82 Capercaillie	34441	1000 kg		-	-
6416841345226	COMPACT MORTAR HEAVY 83 WILLOW GROUSE	34522	1000 kg		-	-
6416841345196	COMPACT MORTAR HEAVY 85 RAVEN	34519	1000 kg		-	-
6416841345233	Compact mortar Heavy 86 Hazel hen	34523	1000 kg		-	-

x = stock product

## Compact mortar Heavy M100/600 Winter ❄️

Cement-based mortar for burnt and sand-lime brick masonry for facades exposed to extremely harsh winter weather in the temperature range -15°C...+5°C. Especially suitable for coastal sites where structures will have to withstand wind and weathering. Suitable for brickwork repointing and for repairing mortar joints. Contains additives to improve density, weather resistance and workability. Maximum grain size 2.0 mm. Usage: 1.2 kg / MRT, 1.5 kg / NKH, 1.7 kg / NRT.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841346001	COMPACT MORTAR HEAVY M100/600 WINTER	34600	1000 kg		-	-
6416841345318	COMPACT MORTAR HEAVY 39 WINTER	34531	1000 kg		-	-
6416841345325	COMPACT MORTAR HEAVY 59 BIRCH BARK WHITE WINTER	34532	1000 kg		-	-
6416841345332	COMPACT MORTAR HEAVY 40 LIME GRAY WINTER	34533	1000 kg		-	-
6416841345349	COMPACT MORTAR HEAVY 41 GRAIN YELLOW WINTER	34534	1000 kg		-	-
6416841345356	COMPACT MORTAR HEAVY 42 BRICK RED WINTER	34535	1000 kg		-	-
6416841345363	COMPACT MORTAR HEAVY 45 EARTH BROWN WINTER	34536	1000 kg		-	-
6416841345370	COMPACT MORTAR HEAVY 46 PEAT BROWN WINTER	34537	1000 kg		-	-

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.

6416841345387	COMPACT MORTAR HEAVY 48 BLACK GRAY WINTER	34538	1000 kg		-	-
6416841345295	COMPACT MORTAR HEAVY 52 LINEN LIGHT WINTER	34539	1000 kg		-	-
6416841345783	COMPACT MORTAR HEAVY 44 SAND BROWN WINTER	34578	1000 kg		-	-
6416841345905	COMPACT MORTAR HEAVY 71 SWAN WINTER	34590	1000 kg		-	-
6416841345462	Compact mortar Heavy 72 Alli Winter	34546	1000 kg		-	-
6416841345691	COMPACT MORTAR HEAVY 73 CUCKOO WINTER	34569	1000 kg		-	-
6416841345844	Compact mortar Heavy 74 Hawk Winter	34584	1000 kg		-	-
6416841345004	COMPACT MORTAR HEAVY 75 LARK WINTER	34500	1000 kg		-	-
6416841345134	COMPACT MORTAR HEAVY 77 WINTER	34513	1000 kg		-	-
6416841345806	COMPACT MORTAR HEAVY 79 PTARMIGAN WINTER	34580	1000 kg		-	-
6416841345943	COMPACT MORTAR HEAVY 80 SIBERIAN JAY WINTER	34594	1000 kg		-	-
6416841345912	COMPACT MORTAR HEAVY 81 TEAL WINTER	34591	1000 kg		-	-
6416841345714	Compact mortar Heavy 82 Capercaillie Winter	34571	1000 kg		-	-
6416841345929	COMPACT MORTAR HEAVY 83 WILLOW GROUSE WINTER	34592	1000 kg		-	-
6416841345790	COMPACT MORTAR HEAVY 85 RAVEN WINTER	34579	1000 kg		-	-
6416841345950	Compact mortar Heavy 86 Hazel hen Winter	34595	1000 kg		-	-

x = stock product



## Winter-time masonry mortar TML ❄️

For block and brick masonry in winter conditions in the temperature range +5°C – -15°C. Material usage: For bricks, the same as with masonry mortar, and for bricks, the same as with block mortar. Remains usable for around 0.5 h. Amount of finished mortar: 13-14 l/25 kg

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530509	WINTER-TIME MASORY MORTAR TML	53050	25 kg	49 sk	x	-

x = stock product

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.



## Block mortar M100/500

For lightweight aggregate block masonry. Usage: around 4 kg / H75-UH150, around 7 kg / UH200-RUH380. Remains usable for around 3 h.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530493	BLOCK MORTAR M100/500	53049	25 kg	49 sk	x	x
6416841330499	BLOCK MORTAR M100/500	33049	1000 kg		x	x

x = stock product

## Block mortar M 100/500 Winter ❄️

For lightweight aggregate block masonry in winter conditions in the temperature range +5°C – -15°C. Material usage: ca. 4 kg / H75-UH150, ca. 7 kg / UH200-RUH380.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330505	BLOCK MORTAR M100/500 WINTER	33050	1000 kg		-	-

x = stock product

## Stone adhesive KVL

For thin-jointing of sand-lime bricks and blocks. Also suitable for rough coating. Usage: 2-4 kg/m<sup>2</sup>, in rough coating 3-6 kg/m<sup>2</sup>.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530325	STONE ADHESIVE KVL 25 KG	53032	25 kg	49 sk	x	x

x = stock product

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.



## Mortar for tongue-and-groove blocks PHL

For the thin-joint masonry of lightweight aggregate blocks. Usage: around 1.5 kg/ UH 100-150, around 2.5 kg/ RUH 200-420, around 2.5 - 3.5 kg/ EH 420.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530196	MORTAR FOR TONGUE-AND-GROOVE BLOCKS PHL	53019	25 kg	49 sk	x	x
6416841330161	MORTAR FOR TONGUE-AND-GROOVE BLOCKS PHL	33016	500 kg		x	x
6416841330192	MORTAR FOR TONGUE-AND-GROOVE BLOCKS PHL	33019	1000 kg		x	x

x = stock product



## Mortar for tongue and groove blocks PHL Winter ❄️

Fescon Mortar for tongue and grove blocks Winter is a dry mortar for the winter-time thin-jointing of lightweight aggregate blocks. The maximum grain size is 1.2 mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530097	MORTAR FOR TONGUE-AND-GROOVE BLOCKS PHL WINTER	53009	25 kg	49 sk	-	-
6416841329004	MORTAR FOR TONGUE AND GROOVE BLOCKS PHL WINTER	32900	500 kg		-	-
6416841330246	MORTAR FOR TONGUE AND GROOVE BLOCKS PHL WINTER	33024	1000 kg		-	-

x = stock product

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.

## ELT Brick element grout

A coloured concrete-type grout for the grouting of industrial prefabricated brick elements. Maximum grain size 1.2 mm.

Minimum delivery 3 big bags.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841330901	ELT Brick element grout	33090	1000 kg		-	-
6416841330987	ELT Brick element grout quartz white	33098	900 kg		-	-
6416841332103	ELT Brick element grout that white	33210	900 kg		-	-
6416841332110	ELT Brick element grout lime gray	33211	900 kg		-	-
6416841332127	ELT Brick element grout grain yellow	33212	900 kg		-	-
6416841332134	ELT Brick element grout brick red	33213	900 kg		-	-
6416841332141	ELT Brick element grout earthy brown	33214	900 kg		-	-
6416841332158	ELT Brick element grout peat brown	33215	900 kg		-	-
6416841332165	ELT Brick element grout black-gray	33216	900 kg		-	-
6416841332172	ELT Brick element grout linen pale	33217	900 kg		-	-
6416841332349	ELT Brick element grout sand brown	33234	900 kg		-	-
6416841332356	ELT Brick element grout swan	33235	900 kg		-	-
6416841332318	ELT Brick element grout Alli	33231	900 kg		-	-
6416841332387	ELT Brick element grout persimmon	33238	900 kg		-	-
6416841332332	ELT Brick element grout Hawk	33233	900 kg		-	-
6416841332363	ELT Brick element grout lark	33236	900 kg		-	-
6416841332400	ELT Brick element grout jackdaw	33240	900 kg		-	-
6416841332455	ELT Brick element grout ptarmigan	33245	900 kg		-	-
6416841332462	ELT Brick element grout heard	33246	900 kg		-	-
6416841332301	ELT Brick element grout teal	33230	900 kg		-	-
6416841332394	ELT Brick element grout Capercaillie	33239	900 kg		-	-
6416841332417	ELT Brick element grout willow grouse	33241	900 kg		-	-
6416841332370	ELT Brick element grout raven	33237	900 kg		-	-
6416841332554	ELT Brick element grout Hazel hen	33255	900 kg		-	-

x = stock product



## ELK Clinker element grout

Concrete-type grout for the grouting of industrial prefabricated clinker elements.  
Maximum grain size 0.6 mm.

Minimum delivery 3 big bags.

					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841330918	ELK Clinker element grout	33091	1000 kg		-	-

x = stock product



## 5 WALL LEVELING COMPOUNDS

### Joint filler SF

A polymer-based putty and jointing product for interior walls. Suitable for block, concrete, lightweight concrete, Bedding plaster LF, brick plaster and gypsum board surfaces, and in the levelling of painted surfaces and the jointing of gypsum boards. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Whitish colour.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201003	JOINT FILLER SF	20100	20 kg	49 sk	-	-

x = stock product

### Bedding plaster LF

A polymer-based bedding plaster for wall and ceiling surfaces in dry spaces. Suitable for block, concrete, lightweight concrete, brick, brick plaster, Bedding plaster VF and Finishing plaster VHF surfaces. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Layer thickness 1 - 5 mm. Whitish colour.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201010	BEDDING PLASTER LF	20101	20 kg	49 sk	x	x

x = stock product

### Bedding plaster LF RD

A polymer-based low-dust bedding plaster for wall and ceiling surfaces in dry spaces. Suitable for block, concrete, lightweight concrete, brick, brick plaster, Bedding plaster VF and Finishing plaster VHF surfaces. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Layer thickness 1 - 5 mm. Whitish colour.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201010	BEDDING PLASTER LF	20101	20 kg	49 sk	x	x

x = stock product



Low dust.



## Finishing plaster LRF

A polymer-based finishing plaster for wall and ceiling surfaces in dry spaces. Suitable for block, concrete, lightweight concrete, Bedding plaster LF, brick plaster and gypsum board surfaces. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Layer thickness 0 - 3 mm. Whitish colour.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201027	FINISHING PLASTER LRF	20102	20 kg	49 sk	x	x

x = stock product



## Finishing plaster LRF RD

A polymer-based, low-dust finishing plaster for wall and ceiling surfaces in dry spaces. Suitable for block, concrete, lightweight concrete, Bedding plaster LF and LF RD, brick plaster and gypsum board surfaces. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Layer thickness 0 - 3 mm. Whitish colour.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202406	FINISHING PLASTER LRF RD	20240	20 kg	49 sk	-	-

x = stock product



## Brick bedding plaster TTF

A cement-based bedding plaster for wall and ceiling surfaces in dry and wet spaces. Suitable for block, brick, lightweight concrete, brick plaster and plastered surfaces. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Layer thickness 2 - 10 mm. Colour grey.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201034	BRICK BEDDING PLASTER TTF	20103	20 kg	49 sk	x	x

x = stock product



Low dust.

## Bedding plaster VF

A cement-based bedding plaster for wall and ceiling surfaces in dry and wet spaces. Suitable for block, lightweight concrete, brick and concrete surfaces. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Layer thickness 1 - 5 mm. Grey colour.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841201041	BEDDING PLASTER VF	20104	20 kg	49 sk	x	-

x = stock product

## Finishing plaster VHF

A cement-based finishing plaster for wall and ceiling surfaces in dry and wet spaces. Suitable for block, lightweight concrete and Bedding plaster VF surfaces. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Layer thickness 0 - 3 mm.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841201058	FINISHING PLASTER VHF HARMAA	20105	20 kg	49 sk	x	-

x = stock product

## Levelling compound for wet areas WTT

A cement-based wall finishing plaster for wet areas, particularly under moisture insulation. Also suitable for pump application. Usage: 1.2 kg/m<sup>2</sup>/1 mm layer. Layer thickness 2-10 mm.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841201072	LEVELLING COMPOUND FOR WET AREAS WTT 20 KG	20107	20 kg	49 sk	x	x

x = stock product





## Filling plaster TLR

A quickly hardening and drying filling plaster with a special cement binder for interior wall surfaces in dry, humid and wet areas. Recommended layer thickness: over-levelling 5-30 mm, partial levelling 5-50 mm. Usage: 1 mm layer 1.5 kg/m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201089	FILLING PLASTER TLR 20 KG	20108	20 kg	49 sk	x	-

x = stock product



## Indoor lime-cement plaster SR7

Quickly hardening and drying indoor lime-cement plaster that can be sprayed or applied manually, containing special cement binders, fibre-reinforced. Use: Straightening walls and ceilings, filling and repairs in dry, damp and wet areas.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841201102	INDOOR LIME-CEMENT PLASTER SR7	20110	20 kg	49 sk	x	-

x = stock product



## Gypsum plaster mix GL

Pumpable, lightweight, non-shrinking gypsum levelling compound, which is also suitable for shaping manually. Fescon Gypsum Plaster Mix GL is meant for straightening and levelling wall and ceiling surfaces in dry indoor spaces for layer thicknesses as large as 40 mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202383	Gypsum plaster mix GL	20238	15 kg	49 sk	x	-

x = stock product



## Wall surface strengthening membrane

Surface strengthening membrane for reinforcing the plastering of concrete block structures.

Roll size 1.0 m x 50 m.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841257116	Wall surface strengthening membrane 1M X 50 M	25711	1 roll		-	-

x = stock product

## 6 FLOOR LEVELING PRODUCTS



### Floor compound LM 6000



A cement-based, casein-free semi-dry floor compound that hardens and dries rapidly, and can be manually applied. Uses: casting, straightening, filling and grading of concrete floors. Surface levelling is recommended. Largest grain size 1.2 mm. Layer thickness 10-250 mm. Dry usage: around 1.8 kg/m<sup>2</sup>/mm. Ready-to-apply compound around 10-11 l/20 kg.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202000	Floor compound LM 6000	20200	20 kg	49 sk	x	x

x = stock product



### Underfloor heating filler LL 5500



A fibre-reinforced, casein-free floor underfloor heating filler with a special cement binder that hardens and dries rapidly, and can be manually applied. Use: underfloor heating filler for indoor concrete and primed plasterboard floors. Largest grain size 1.2 mm. Layer thickness 10-80 mm. Dry usage: around 1.8 kg/m<sup>2</sup>/mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202017	Underfloor heating filler LL 5500 20 KG	20201	20 kg	49 sk	x	x

x = stock product



### Coarse floor levelling compound LM 5000



A cement-based, casein-free floor levelling compound that hardens and dries rapidly, and can be manually applied. Uses: casting, straightening, filling and grading of concrete floors. Largest grain size 1.2 mm. Layer thickness 5-80 mm. Dry usage: around 1.8 kg/m<sup>2</sup>/mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202024	Coarse floor levelling compound LM 5000 20 KG	20202	20 kg	49 sk	x	x

x = stock product



Low dust.

## Floor levelling plaster LT 4000



A cement-based, casein-free floor levelling compound that is easily levelled, rapidly hardening and drying, and can be manually applied. Used to level the surface of concrete floors. Also suitable for graded floors. Largest grain size 0.6 mm. Layer thickness 3-30 mm. Dry usage: approx. 1.5 kg/m<sup>2</sup>/mm.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202031	Floor levelling plaster LT 4000 20 KG	20203	20 kg	49 sk	x	x

x = stock product

## Floor concrete LB 7



Special cement based, pumpable and rapidly drying floor concrete. Suitable for casting graded floors, conduit filling and applications where the structure must be taken into use rapidly, such as pipe renovations. Compressive strength around 40 MPa Fibre-reinforced. Layer thickness 30 - 150 mm. Dry usage: around 1.8 kg/m<sup>2</sup>/mm.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202154	FLOOR CONCRETE LB 7	20215	20 kg	49 sk	x	-
6416841333407	FLOOR CONCRETE LB 7	33340	1000 kg		x	-

x = stock product

## Fescorapid



A quickly hardening and drying repair plaster with a special cement binder for repairing holes in a concrete floor, correcting the floor grade, and repairing and levelling stairs. Strength approx. 30 MPa, maximum grain size 0.6 mm, and layer thickness 2-20 mm. Usage: 1.5 kg/m<sup>2</sup>/1 mm.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631015	Fescorapid 5 KG	63101	5 kg		x	x
6416841202352	Fescorapid 20 KG	20235	20 kg	49 sk	x	-

x = stock product



Low dust.



## Fescofine



Fescofine is a fast hardening and drying finishing compound with a special cement adhesive agent for concrete surfaces. Maximum grain size is 0,1 mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202390	Fescofine	20239	20 kg	49 sk	x	-

x = stock product



## FlowPlan



A cement-based, floor levelling compound that is easily levelled, rapidly hardening and drying, and has high tensile and compressive strength. Suitable for public spaces and can be pump-applied. Layer thickness 1 - 15 mm. Dry usage: around 1.6 kg / m<sup>2</sup> / mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202307	FlowPlan	20230	20 kg	49 sk	x	x
6416841338129	FlowPlan	33812	700 kg		-	-

x = stock product



## Flow H



A cement-based, casein-free floor levelling compound that is easily levelled, hardens and dries rapidly, and can be applied with a pump. Used for concrete floor levelling. Layer thickness 4-30 mm. Dry usage: around 1.7 kg/m<sup>2</sup>/mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202314	Flow H 20 KG	20231	20 kg	49 sk	-	-
6416841390738	Flow H 1000KG	39073	1000 kg		-	-
	Flow H	33122	1 kg		-	-

x = stock product



Low dust.

## Flow HS



Designed for low-strength and difficult bases, Fescon Flow HS is a fibre-reinforced, low-alkali (pH < 11), casein-free, pump-applied levelling compound with a special cement binding agent, that is easy to level and features excellent workability.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841202345	Flow HS 20 KG	20234	20 kg	49 sk	-	-
6416841331427	Flow HS 1000KG	33142	1000 kg		-	-
	Flow HS	33124	1 kg		-	-

x = stock product

## FlowBase



Fescon FlowBase is a low-alkali (pH < 11), easy-to-level, fast setting, pump-applied levelling compound with a special cement binder and with high tensile and strength properties as well as having excellent workability characteristics and strength values. Maximum grain size 0,6 mm. For layer thicknesses 2-30 mm (partial levelling max. 50 mm). Material usage: approx. 1,7 kg / m<sup>2</sup> / mm.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331489	FlowBase 1000 kg	33148	1000 kg		-	-

x = stock product



**Low dust.**





## FlowFiber

Fescon FlowFiber is a fibre-reinforced, low-alkali (Ph < 11) pump-applied levelling compound with a special cement binder, which is both self-smoothing and features excellent workability characteristics. Applications: heated floors and floating floor systems, thick layers of levelling compound and concrete bases, hollow slabs, cement-based filler surfaces, wood and gypsum based boards and insulating boards. Maximum grain size: 1,2 mm. For layer thicknesses 8-50 mm (partial levelling max. 80 mm).

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331465	FlowFiber 1000KG	33146	1000 kg		-	-

x = stock product



## Flow GS 3.0 mm Gypsum floor mass

Flow GS 3.0 mm Gypsum floor mass is a pump-applied, easily levelling floor compound with a gypsum binder and having excellent workability and spreading characteristics. Suitable for heated floor structures, in particular. Maximum grain size: 3.0 mm. Layer thickness 20-80 mm (partial levelling max. 100 mm)

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841331496	Flow GS 3.0 mm Gypsum floor mass	33149	1000 kg		-	-

x = stock product

## Flow Primer

Brush-on primer for surface pretreatment before floor levelling. Flow Primer improves the adhesion of floor levelling compounds, reduces or eliminates the formation of air bubbles, and prevents water contained in the floor levelling compound from being absorbed into the surface too quickly. Usage: Hollow-core slab surfaces: about 10 m<sup>2</sup>/l. Cast-in-place concrete surfaces: about 5 m<sup>2</sup>/l. Plaster and wood surfaces: about 7 m<sup>2</sup>/l. Mixing ratio: Concrete surfaces and surfaces with cement-based levelling: 1 part Flow Primer, 3 parts water. Surfaces that cannot withstand moisture, e.g. plaster and wood surfaces: Use undiluted. For indoor use.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841769053	Flow Primer	76905	10 l	50 prk	x	-

x = stock product

## Primer PLUS

Brush-on special primer for the pretreatment of the base on non-absorbent surfaces (ceramic, glass or steel) before levelling. Usage: around app. 150 g/ m<sup>2</sup>l. Product is ready for use and does not need to be thinned. Pallet size (5 kg) 90 cans / pallet. For indoor use.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841769060	Primer PLUS	76906	5 kg	80 prk	x	-

x = stock product



## Elevation mark

Elevation mark with adhesive tape for floor levelling compounds. Scale 10-65 mm or 10-100 mm. Sold in bags of 100.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259332	ELEVATION MARK	25933	1 pcs		x	-
6416841259363	ELEVATION MARK	25936	1 pcs		x	-

x = stock product



## Bordering strip 30x30x2000 mm

Fescon Bordering strip is a self-adhesive polyester strip for bordering floor levelling compounds. With the Bordering strip, the pumped areas can be restricted to the required size, also suitable for making door stops. Installation on a cleaned and primed base. Package size 25 pcs. / bag (50 m).

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259394	Bordering strip 30x30x2000 mm	25939	50 m		x	-

x = stock product



## Bordering strip 8x150 mm

A bordering strip for separating floating floor structures from vertical structures. The Bordering strip has a ready-fitted overlapping plastic sheet with adhesive tape, to be installed over separation fabric or insulation. The back of the Bordering strip has a fastening tape for wall mounting. Roll length 25 m. Sales lot 4 rolls/package (100 m).

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259387	Bordering strip 8x150 mm	25938	100 m		x	-

x = stock product

## Separation fabric 1.5x50 m

Breathable Separation fabric for separating floating floor structures, if the base is of weak concrete, a floor base, or insulation. Diffusion open, separation fabric, made of polypropylene, through which the water in the floor levelling compound cannot penetrate. Both long sides of the separation fabric have an overlapping tape ready-fitted, overlapping according to alignment lines.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841259370	Separation fabric 1.5x50 m	25937	75 m2		x	-

x = stock product

## 7 TILING PLASTER AND WATERPROOFING PRODUCTS



### Waterproofing compound



Roller-applied, fibre-reinforced waterproofing compound for indoor applications. Suitable for waterproofing floors and walls. Usage: around 0.7 l/m<sup>2</sup>. Certified VTT-C-870-06, ETA-approved, CE marking.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259097	Waterproofing compound 3L	25909	3 l		x	x
6416841259035	Waterproofing compound 12L	25935	12 l	52 prk	x	x

x = stock product



### Waterproofing compound WS



Fast-drying, single-component indoor waterproofing compound that can be rolled or sprayed. Suitable for the waterproofing of floors and walls. Consumption about 0.7 l/m<sup>2</sup> on walls and floors. Accessories used with Waterproofing compound WS: Fescon Primer KP, Drain flange KL-B, Waterproofing accessories (FS and VE series) and Waterproofing strip 0.15 x 25 m fibre. ETA- and M1-approved, with CE marking.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841769091	Waterproofing compound WS	76909	3 l	100 prk	x	-
6416841769121	Waterproofing compound WS	76912	15 l	24 prk	x	-

x = stock product



## Fescoseal A+B

The Fescoseal A+B two-component waterproofing compound is used in the waterproofing of floors and walls before ceramic tiles are installed. Fescoseal A+B is easy to apply, it dries rapidly, it is extremely flexible after drying, and it has excellent adhesive properties. The product is non-shrink and can withstand chlorides and frost stress. The waterproofing system has the cleanest M1 building material emission class. Certificate No. VTT-C-11838-16.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841769008	Fescoseal A	76900	10 kg	40 prk	x	-
6416841769084	Fescoseal B	76908	10 kg	40 prk	x	-

x = stock product

## Adhesion promoter

Brush-on primer for surface pretreatment before floor levelling or waterproofing. Usage: solid surfaces around 10 m<sup>2</sup> / l, porous surfaces around 6 m<sup>2</sup> / l. Mixing ratio: concrete and cement based levelling compounds: One part of primer and three parts of water, plasterboard: use undiluted. For indoor use. Pack size 5 x 3 ltr / box and 10 x 1 ltr / box.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841259110	ADHESION PROMOTER	25911	1 l		x	x
6416841259103	ADHESION PROMOTER	25910	3 l		x	x
6416841259042	ADHESION PROMOTER	25904	10 l	50 prk	x	x

x = stock product



## Fescon Primer KP

Brush-on primer for the pretreatment of the base in the Fescoseal A+B waterproofing system. Usage: solid surfaces around 10 m<sup>2</sup> / l, porous surfaces around 6 m<sup>2</sup> / l. Mixing ratio: concrete and cement based levelling compounds: One part of primer and three parts of water, plasterboard: use undiluted. For indoor use.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841769046	FESCON PRIMER KP	76904	5 l	100 prk	x	-
6416841769015	FESCON PRIMER KP	76901	10 l	40 prk	-	-

x = stock product




## Waterproofing strip

A waterproofing strip made from non-woven fabric, part of the Fescon Waterproofing System. 10 rolls/box. Not for Fescoseal waterproofing system. Also available in a waterproofing membrane of 1.0 m x 10.0 m 10 m<sup>2</sup>/roll. Not for Fescoseal waterproofing system.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259073	Waterproofing strip 0,15Mx25M	25907	1 roll		x	x
6416841259059	Waterproofing membrane 1mx10m 10m <sup>2</sup> /roll	25905	1 roll		x	x

x = stock product



## Drain flange

Ready-to-install lead-through and floor drain connector.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259141	Drain flange 300X300 mm (2pcs)	25914	2 pcs		x	x
6416841259424	Drain flange 300X300 mm (10pcs)	25942	10 pcs		x	x

x = stock product

## Drain flange KL-B

The self-adhesive butyl drain flange can be used with all Fescon waterproofing systems. The surface is reinforced with a polypropylene material. Drain flange size 37 x 37 cm. Package size: 10 pcs per box. Use: For drains that are fully covered with a butyl drain flange before the clamping ring is installed.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259530	BUTYLMANSCHETTE KL-B	25953	1 pcs		x	-

x = stock product

## Waterproofing accessories FS

Waterproofing accessories includes in all Fescon waterproofing systems. Waterproofing accessories, waterproofing strip, inner and outer corners used in waterproofing, as well as lead-through flanges.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259431	SEALING TAPE FS-N	25943	1 roll		x	-
6416841259448	OUTSIDE CORNER FS-U	25944	1 pcs		x	-
6416841259479	INSIDE CORNER FS-S	25947	1 pcs		x	-
6416841259486	WALL PACKING FS-L 10	25948	1 pcs		x	-
6416841259790	WALL PACKING FS-L 23	25979	1 pcs		x	-
6416841259493	WALL PACKING FS-L 40	25949	1 pcs		x	-
6416841259783	WALL PACKING FS-L 55	25978	1 pcs		x	-
6416841259516	WALL PACKING FS-L 70	25951	1 pcs		x	-
6416841259530	BUTYLMANSCHETTE KL-B	25953	1 pcs		x	-

x = stock product



## Waterproofing accessories VE

Waterproofing accessories, waterproofing strip, inner and outer corners used in waterproofing, as well as lead-through flanges. Used in Fescoseal and Fesccon WS waterproofing systems.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259547	SEALING TAPE VE-N	25954	1 roll		x	-
6416841259554	OUTSIDE CORNER VE-U	25955	1 pcs		x	-
6416841259561	INSIDE CORNER VE-S	25956	1 pcs		x	-
6416841259578	WALL PACKING VE-L 10	25957	1 pcs		x	-
6416841259806	WALL PACKING VE-L 23	25980	1 pcs		x	-
6416841259585	WALL PACKING VE-L 40	25958	1 pcs		x	-
6416841259813	WALL PACKING VE-L 55	25981	1 pcs		x	-
6416841259592	WALL PACKING VE-L 70	25959	1 pcs		x	-
6416841259530	BUTYLMANSCHETTE KL-B	25953	1 pcs		x	-

x = stock product



## Tile adhesive plaster VSL



A non-sag, flexible adhesive plaster for fastening ceramic and clinker tiles to concrete, tile, plastic and painted bases. For outdoor and indoor use. Usage: 2-3 kg/m<sup>2</sup>. The properties of the plaster meet the C2, S1 and T requirements.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631060	TILE ADHESIVE PLASTER VSL	63106	5 kg		x	x
6416841203021	TILE ADHESIVE PLASTER VSL	20302	20 kg	49 sk	x	x

x = stock product



Low dust.

## Tile adhesive plaster ILL

Adhesive plaster particularly designed for large floor tiles on concrete, plastic and painted bases. Enables full plaster adhesion of a large tile. Suitable for both indoor and outdoor use. Usage: 3-6 kg/m<sup>2</sup>. The properties of the plaster meet the C2 and S1 requirements.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841203014	TILE ADHESIVE PLASTER ILL	20301	20 kg	49 sk	x	x

x = stock product

## Tile adhesive plaster SS2

Fastening for flexible or otherwise moving bases, such as sheet-metal walls, and for fastening natural stones. Usage: 2-3 kg/m<sup>2</sup>. The properties of the plaster meet the C2 and S2 requirements.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841203038	TILE ADHESIVE PLASTER SS2	20303	20 kg	49 sk	-	-

x = stock product

## Tile adhesive plaster SSL Lite

Fescon Tile adhesive plaster SSL Lite is a light-coloured, non-sag, lightweight, M1-rated adhesive plaster with cement binder. Enables tiling without strips or other spacers; see research report VTT-S-05228-16. A frost-resistant adhesive plaster; see test report VTT-S-05228-16. Suitable for indoor and outdoor use.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841203052	Tile adhesive plaster SSL LITE	20305	15 kg	49 sk	x	-

x = stock product



Low dust.





## Tile seaming plaster SML



A cement-based tile grout.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841671004	Tile seaming plaster SML white 3 kg	67100	3 kg		x	-
6416841204004	Tile seaming plaster SML white 15 kg	20400	15 kg	49 sk	x	-
6416841671011	Tile seaming plaster SML marble white 3 kg	67101	3 kg		x	-
6416841204011	Tile seaming plaster SML marble white 15 kg	20401	15 kg	49 sk	x	-
6416841671028	Tile seaming plaster SML gray 3 kg	67102	3 kg		x	-
6416841204028	Tile seaming plaster SML gray 15 kg	20402	15 kg	49 sk	x	-
6416841671035	Tile seaming plaster SML light gray 3 kg	67103	3 kg		x	-
6416841204035	Tile seaming plaster SML light gray 15 kg	20403	15 kg	49 sk	x	-
6416841671042	Tile seaming plaster SML dark gray 3 kg	67104	3 kg		x	-
6416841204042	Tile seaming plaster SML dark gray 15 kg	20404	15 kg	49 sk	x	-
6416841671073	Tile seaming plaster SML light beige 3 kg	67107	3 kg		x	-
6416841204073	Tile seaming plaster SML light beige 15 kg	20407	15 kg	49 sk	x	-
6416841671127	Tile seaming plaster SML beige 3 kg	67112	3 kg		x	-
6416841204127	Tile seaming plaster SML beige 15 kg	20412	15 kg	49 sk	x	-
6416841671110	Tile seaming plaster SML black 3 kg	67111	3 kg		x	-
6416841204110	Tile seaming plaster SML black 15 kg	20411	15 kg	49 sk	x	-
6416841671134	Tile seaming plaster SML blackgray 3 kg	67113	3 kg		x	-
6416841204134	Tile seaming plaster SML blackgray 15 kg	20413	15 kg	49 sk	x	-

x = stock product

## Sanitary silicone

One-component silicone mass for expansion joints and sealing.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841259134	Sanitary silicone colorless	25913	1 pcs		x	-
6416841259165	Sanitary silicone white	25916	1 pcs		x	-
6416841260109	Sanitary silicone marble white	26010	1 pcs		x	-
6416841259202	Sanitary silicone gray	25920	1 pcs		x	-
6416841260055	Sanitary silicone light grey	26005	1 pcs		x	-
6416841259219	Sanitary silicone dark gray	25921	1 pcs		x	-
6416841260017	Sanitary silicone light beige	26001	1 pcs		x	-
6416841260123	Sanitary silicone beige	26012	1 pcs		x	-
6416841260130	Sanitary silicone black	26013	1 pcs		x	-
6416841260116	Sanitary silicone black gray	26011	1 pcs		x	-

x = stock product

## 8 PLASTERS



### Lime-cement plaster KS 10/90

Adhesive plaster. A spray-applied lime-cement plaster for adhesion plastering. Also suitable for manual application. Usage: 3-6 kg/m².

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530554	Lime-cement plaster KS 10/90 3 mm	53055	25 kg	49 sk	-	-
6416841330550	Lime-cement plaster KS 10/90 3 mm	33055	1000 kg		-	-

x = stock product



### Lime-cement plaster KS 35/65

Adhesive plaster and filling plaster. A spray-applied lime-cement plaster for adhesion plastering and filling. Also suitable for manual application. Usage: 15-30 kg/m².

Also available to order with a maximum grain size of 1.2 mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530561	Lime-cement plaster KS 35/65 3 mm	53056	25 kg	49 sk	x	-
6416841330567	Lime-cement plaster KS 35/65 3 mm	33056	1000 kg		-	-

x = stock product

## Lime-cement plaster KS 50/50



A filling plaster. A lime-cement plaster for filling and finishing. Also suitable for manual application. Usage: 15-25 kg/m<sup>2</sup>.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841560575	Lime-cement plaster KS 50/50 25KG 1,2 mm	56057	25 kg	49 sk	x	x
6416841360571	Lime-cement plaster KS 50/50 1,2 mm	36057	1000 kg		-	-
6416841530578	Lime-cement plaster KS 50/50 3 mm	53057	25 kg	49 sk	x	x
6416841330574	Lime-cement plaster ks 50/50 3 mm	33057	1000 kg		x	-

x = stock product

## Lime-cement plaster KS 65/35

Finishing plaster. A spray-applied lime-cement finishing plaster. Also suitable for manual application. Grain size 3 mm also available to order. Usage: 6-10 kg/m<sup>2</sup>.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841570611	Lime-cement plaster KS 65/35 0,6 mm	57061	25 kg	49 sk	x	-
6416841560612	Lime-cement plaster KS 65/35 1,2 mm	56061	25 kg	49 sk	x	-
6416841360618	Lime-cement plaster KS 65/35 1,2 mm	36061	1000 kg		-	-

x = stock product



## Lightweight lime-cement plaster KEV KS 35/65

Adhesive and filling plaster with lime-cement binder containing mineral lightweight filler materials. Also suitable for manual application. Usage: 1 mm layer 1.2 kg/m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841253118	Lightweight lime-cement plaster KEV KS 35/65	25311	25 kg	49 sk	x	-

x = stock product



## Lime-cement plaster HD KS 35/65 fibre

A fibre-reinforced adhesion and filling plaster with a low water absorption for 5-30 mm layer thicknesses. Also suitable for manual application. Usage 1.4 kg for a 1 mm layer. Maximum grain size 3 mm (available to order in 1.2 mm grain size).

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841571014	Lime-cement plaster KS 35/65 3 mm fibre	57101	25 kg	49 sk	-	-
6416841371010	Lime-cement plaster KS 35/65 3 mm fibre	37101	1000 kg		-	-

x = stock product



## Lime-cement plaster HD KS 20/80 fibre

A fibre-reinforced adhesion and filling plaster with a low water absorption for 5-30 mm layer thicknesses. Also suitable for manual application. Usage 1.4 kg for a 1 mm layer. Maximum grain size 3 mm (available to order in 1.2 mm grain size).

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841572011	Lime-cement plaster HD KS 20/80 3 mm fibre	57201	25 kg	49 sk	-	-
6416841372017	Lime-cement plaster KS 20/80 3 mm fibre	37201	1000 kg		-	-

x = stock product



## Base levelling plaster

Base levelling plaster suitable for base levelling in Fescoterm system applications and other thick fills of concrete surfaces. Also suitable for manual application. Maximum grain size 3 mm. Compressive strength C 25/30. Layer thickness 6-20 mm. Ready-to-apply compound 12-13 l / 25 kg. Usage 20 kg/m<sup>2</sup>/10 mm layer. Grain size 10 mm also available to order (only 1000 kg).



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530783	Base levelling plaster	53078	25 kg	49 sk	-	-
6416841331656	Base levelling plaster	33165	1000 kg		-	-

x = stock product

## Lime plaster K100/1200

Basic plaster for the on-site preparation of lime-cement plaster by adding water and cement either as volume fractions or by weighing. The finished wet plaster is suitable for use in adhesion plastering or filling according to the amount of cement. The finished lime-cement plaster is suitable for both machine and manual application. Usage in adhesion plastering 5-10 kg/m<sup>2</sup> and in filling 15-30 kg/m<sup>2</sup>.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841339010	Lime plaster K100/1200 0,6 mm	33901	800 kg		-	-
6416841339102	Lime plaster K100/1200 1,5 mm	33910	1000 kg		-	-
6416841339119	Lime plaster K100/1200 4 mm	33911	1000 kg		-	-

x = stock product



## Wet plaster

Fescon Wet plaster is a lime-based dry plaster from which ready-to-use wet plaster is prepared at a work site. With the Fescon special manufacturing method, the plaster has the good properties of traditional wet plaster. The maximum grain size is 0.6-4.0 mm. The finished wet plaster is suitable for use in adhesion plastering, filling and surface plastering according to the amount of cement. Suitable for mechanical and manual plastering.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841339010	Lime plaster K100/1200 0,6 mm	33901	800 kg		-	-
6416841339102	Lime plaster K100/1200 1,5 mm	33910	1000 kg		-	-
6416841339119	Lime plaster K100/1200 4 mm	33911	1000 kg		-	-

x = stock product

## 9 PRODUCTS FOR INFRASTRUCTURE CONSTRUCTION AND THE REPAIR OF CONCRETE SURFACES

### Bolting plaster SR

Pumpable special plaster with cement binder for bolting during quarrying. Also available in a sulphate-resistant grade. Used in tunnel excavation, and rock and infrastructure construction. CE-marked, ready-to-use dry mix that meets quality and strength requirements.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533357	BOLTING PLASTER SR	53335	25 kg	49 sk	x	-
6416841333353	BOLTING PLASTER SR	33335	800 kg		-	-

x = stock product

### Winterbolting plaster SR **NEW!**

Pumpable special plaster for reinforcement work in rock construction. The binder is made of sulphate-resistant cement. Used in tunnel excavation, and rock and infrastructure construction. CE-marked, ready-to-use dry mix that meets quality and strength requirements.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533319	Winterbolting plaster SR	53331	25 kg	49 sk	-	-

x = stock product



## SILKO Corro SKC C35/45

Special concrete for demanding casting applications with salt and frost stress. Largest grain size 10 mm. Strength class C 35/45. SILKO-approved. Minimum delivery 3 big bags.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841333049	SILKO Korro SKC C 35/45 10 mm	33304	1000 kg		-	-

x = stock product



## SILKO Rapid Corro SPC C35/45

Rapidly hardening special plaster for demanding applications. Largest grain size 3mm. Strength class C 35/45. SILKO-approved. Minimum delivery 3 big bags.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533050	SILKO Rapid corro SPC 35/45 3 mm	53305	25 kg	49 sk	-	-
6416841333056	SILKO Rapid corro SPC C 35/45 3 mm	33305	1000 kg		-	-

x = stock product

## Quick Drill 45



The Fescon Quick Drill concept is a new system for accelerating borehole concreting (grouting) in ore prospecting. The system consists of fast-setting concrete, Ciment Fondu Lafarge, and a Quick Drill additive package, by means of which the characteristics of the cement paste can be adjusted.

Prices according to separate offer.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841631800	Quick Drill 45 2,5 l	63180	2,5 l		-	-
6416841533807	Quick Drill 45 20 l	53380	20 l		-	-

x = stock product

## Adhesive plaster TL

The Fescon Adhesive Plaster is a cement-based, polymer-modified, cement-based dry mortar with additives. The maximum grain size is 0.6 mm.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841450265	Adhesive plaster TL	45026	25 kg	49 sk	x	-

x = stock product

## Non-run filling plaster VTL

A cement-based, polymer-modified fibre plaster for the repair of deep pits and corners in concrete structures. Largest grain size 1.2 mm.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841450128	Non-run filling plaster VTL 25KG	45012	25 kg	49 sk	x	-

x = stock product

## Repairing plaster KL 1.2

A cement-based, polymer-modified repairing plaster for the repair of damage, pits and casting defects in concrete structures, and the coating of walls, floors, stairs, plinths, and other such concrete surfaces. Largest grain size 1.2 mm. Estimated usage: 1 mm layer 1.8 kg/m².



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841430342	Repairing plaster KL 1.2 mm	43034	25 kg	49 sk	x	-

x = stock product





## Repairing plaster KL 40

A polymer-modified repair plaster with cement binder for grading corrections of balconies and the repairs and patching of concrete structures. Maximum grain size 1.2 mm. Compressive strength around 40 MPa. Estimated usage: 1 mm layer 1.6 kg/m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450197	Repairing plaster KL 40 1,2 mm	45019	25 kg	49 sk	-	-

x = stock product



## Overlevelling plaster YTL

A polymer-modified plaster with cement binder for the levelling and thin-layer plastering of lightweight aggregate and concrete block structures and concrete surfaces. Maximum grain size 0.6 mm. Levelling work 5-10 kg/m<sup>2</sup> (depending on how even the wall is). Thin-layer plastering 6-8 kg/m<sup>2</sup> / 2 layer applications.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450814	Overlevelling plaster YTL	45081	25 kg	49 sk	x	-

x = stock product



## Corro shotcrete RKB

Fescon Corro Shotcrete RKB is a multi-purpose, strength-rated, non-sag and fibre-reinforced special concrete. It can be used for the repair and coating of concrete structures on floors, walls and ceilings. Suitable for indoor and outdoor use. It is also suitable for use as cast concrete and sprayed concrete in applications where high strength and good weather-resistance are required. Maximum grain size 3.0 mm. Strength class C30/37. SILKO approved. Material usage approx. 2.0 kg/m<sup>2</sup>/1 mm. Good adhesive properties (adhesive class R3).

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530073	Corro shotcrete RKB	53007	25 kg	49 sk	x	-
6416841330055	Corro shotcrete RKB	33005	1000 kg		x	-

x = stock product

## Korrogard R 0.6 mm

A polymer-modified, fibre-reinforced levelling and protective plaster for concrete structures. SILKO-approved.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841533067	Korrogard R 0.6 mm	53306	25 kg	49 sk	-	-

x = stock product

## Korrogard R 1.2 mm

A polymer-modified, fibre-reinforced repair plaster for concrete structures. SILKO-approved.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841533029	Korrogard R 1.2 mm 25KG	53302	25 kg	49 sk	-	-

x = stock product

## Korrogard R 3.0 mm

A polymer-modified, fibre-reinforced repair plaster for concrete structures. SILKO-approved.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841533036	Korrogard R 3.0 mm 25KG	53303	25 kg	49 sk	-	-

x = stock product



## Korroshot D KSD 5.0 mm

A polymer-modified, fibre-reinforced special concrete for shotcreting using the dry spray method. SILKO-approved. Minimum delivery 3 big bags.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841533074	Korroshot D KSD 5 mm	53307	25 kg	49 sk	-	-
6416841333100	Korroshot D KSD 5 mm	33310	1000 kg		-	-

x = stock product

## 10 MINERAL COATINGS AND THIN PLASTER

### Facade coating JSP 0.5

A polymer-modified coating with cement binder for brick and concrete surfaces. Maximum grain size 0.5 mm or 1.5 mm. Estimated usage: 4-6 kg/m<sup>2</sup> / two applications. Smallest manufacturing batch 100 kg/tint.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450852	Facade coating JSP 0.5 mm Fescon 235	45085	25 kg	49 sk	-	-
6416841015617	Facade coating JSP 0.5 mm Fescon colors	45100	25 kg	49 sk	-	-

x = stock product

### Facade coating JSP 1.5

A polymer-modified coating with cement binder for brick and concrete surfaces. Maximum grain size 0.5 mm or 1.5 mm. Estimated usage: 4-6 kg/m<sup>2</sup> / two applications. Smallest manufacturing batch 100 kg/tint.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450869	Facade coating JSP 1.5 mm Fescon 235	45086	25 kg	49 sk	x	-
6416841016065	Facade coating JSP 1.5 mm Fescon colors	45150	25 kg	49 sk	-	-

x = stock product



## Lime-cement coating KSP

A coloured, polymer-modified lime-cement coating that can be spray-applied. Suitable for coating lime-cement plaster and brick surfaces. Largest grain size 1.5 mm. Estimated usage: 4-6 kg/m<sup>2</sup> /two applications. Smallest manufacturing batch 100 kg/tint.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841451514	Lime-cement coating KSP 1,5 mm Fescon colors	45151	25 kg	49 sk	-	-

x = stock product



## Lime-cement coating JL

A spray-applied coloured lime cement finishing plaster. Other tints offered separately. Largest grain size 1.5 mm or 3.0 mm. Usage: 4-8 kg/m<sup>2</sup>. Minimum manufacturing batch 1.5 mm 200 kg/tint and 3 mm 500 kg/tint.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450166	Lime-cement coating JL 1,5 mm 235	45016	25 kg	49 sk	-	-
6416841015075	Lime-cement coating JL 1,5 mm Fescon colors	45200	25 kg	49 sk	-	-
6416841028495	Lime-cement coating JL 3,0 mm Fescon colors	45017	25 kg	49 sk	-	-

x = stock product



## Thin-layer compo plaster KRL

Coloured lime-cement plaster for the thin-layer plastering of brick surfaces. Suitable for both spray and manual application. Other colours offered separately. Largest grain size 1.5 mm. Estimated usage: 5-8 kg/m<sup>2</sup>. Smallest manufacturing batch 500 kg/tint.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841017031	Thin-layer compo plaster KRL 1,5 mm Fescon colors	45014	25 kg	49 sk	-	-

x = stock product



## Antique plaster AL

Suitable for the coating, decorative coating and thin-layer plastering of concrete, sand-lime brick, burnt brick, lightweight aggregate block, sturdy concrete, levelling plaster, fibre plaster and cement levelling compound surfaces both indoors and outdoors. Maximum grain size 0.5 mm or 1.5 mm. Usage 3.5-5.5 kg/m<sup>2</sup>/ 2 applications. Colour white.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530318	Antique plaster AL 0,5 mm	53031	25 kg	49 sk	x	-
6416841530257	Antique plaster AL 1,5 mm	53025	25 kg	49 sk	x	-

x = stock product

## Socle and adjusting plaster SOL

For the levelling and two-layer plastering of lightweight aggregate block foundation walls and walls, and concrete surfaces. Maximum grain size 0.6 mm. Levelling work 5-10 kg/m<sup>2</sup> (depending on how even the wall is). Estimated usage: 1 mm layer 1.5 kg/m<sup>2</sup>.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841530066	Socle and adjusting plaster SOL	53006	25 kg	49 sk	x	x

x = stock product

## Fibre plaster FL

Polymer-modified plaster with cement binder and added plastic fibres. For the plastering of lightweight aggregate and concrete block surfaces, and lightweight concrete and brick surfaces. Maximum grain size 0.6 mm. Estimated usage: 1 mm layer 1.5 kg/m<sup>2</sup>.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450210	Fibre plaster FL	45021	25 kg	49 sk	x	x

x = stock product



## Levelling plaster TSL

A polymer-modified, cement-based plaster for levelling a thickly plastered precast element on the worksite. Maximum grain size 0.6 mm. Usage around 8.5 kg/m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841203106	Levelling plaster TSL	20310	25 kg	49 sk	-	-

x = stock product



## Adhesive mortar FLL

A polymer-modified plaster with cement binder. For the fastening of Fescoterm thin-layer plastering insulation. Maximum grain size 0.6 mm. Usage 4.5 kg/m<sup>2</sup>. Also available in winter grade.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450234	Adhesive mortar FLL	45023	25 kg	49 sk	x	-

x = stock product



## Adhesive mortar FLL Winter ❄️

A polymer-modified plaster with cement binder for the fastening of Fescoterm thin-layer plastering insulation in the temperature range +5 – -10°C. Maximum grain size 0.6 mm. Usage 4-5 kg/m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841640116	Adhesive mortar FLL Winter	64011	25 kg	49 sk	-	-

x = stock product

❄️ Winter products available on 15.9.-1.3., Otherwise Delivery item.

## Reinforcing mortar FVL

A cement-based, polymer-modified, fibre-reinforced plaster. The mesh plaster for Fescoterm thin-layer plastering. Largest grain size 0.6 mm. Material usage: EPS 6-9 kg/m<sup>2</sup>, wool 8-12 kg/m<sup>2</sup>



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841450241	Reinforcing mortar FVL 25KG	45024	25 kg	49 sk	x	-

x = stock product

# 11 MINERAL BASED FACADE PAINTS



## Stone colour KS



Facade paint with lime cement binder for brick and rendered surfaces. Maximum grain size 0.1 mm. Usage 0.3-0.8 kg/m<sup>2</sup>/ 2 applications. Smallest manufacturing batch 100 kg/tint.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450500	Stone colour KS 235	45050	15 kg	49 sk	-	-
6416841001344	Stone colour KS Fescon colors	45055	15 kg	49 sk	-	-

x = stock product



## Stone colour S



Facade paint with cement binder for concrete surfaces. Maximum grain size 0.1 mm. Usage 0.3-0.8 kg/m<sup>2</sup>/ 2 applications. Smallest manufacturing batch 100 kg/tint.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841450401	Stone colour S 235	45040	20 kg	49 sk	-	-
6416841016577	Stone colour S Fescon colors	45045	20 kg	49 sk	-	-

x = stock product



## Lime paint KM

The lime paint is produced in a traditional manner from hand-picked, charcoal-burnt limestone, as well as lime stored for more than a year and wet-quenched with clean water.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841762689	Lime paint KM	76268	10 l	44 prk	-	-
6416841762696	Lime paint KM	76269	10 l	44 prk	-	-

x = stock product

## 12 LIQUID FACADE PAINTS AND COATINGS

### Protective paint

Liquid, water-soluble, alkali-resistant acrylate paint for protecting concrete surfaces against moisture and carbonisation. Usage 0.2-0.5 l/m<sup>2</sup>/application.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841761002	Protective paint	76100	18 l	22 prk	x	-
	Protective paint HR 1	50300	18 l		-	-
	Protective paint HR 2	50301	18 l		-	-
	Protective paint HR 3	50302	18 l		-	-

x = stock product

### Silicone-resin primer MC

Solvent-free primer guaranteeing adhesion and even absorption for concrete, board and plaster surfaces, and paint surfaces in good condition. Primer for application before the Silicone resin coating and Fescosan coating. Usage 0.2 kg/m<sup>2</sup> (when thinned by 50%). Can be tinted.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841760500	Silicone-resin primer MC	86050	15 kg	40 prk	x	-
	Silicone-resin primer MC	50305	15 kg		-	-
		50306	15 kg		-	-

x = stock product



## Silicone resin coating MC



A liquid, water-soluble silicone resin coating that is extremely breathable and water-resistant. This durable coating is suitable for new and previously coated stone surfaces on façades. It is also a coating product in the Fescoterm thin-layer plastering system. Usage: 2.2-4.2 kg/m<sup>2</sup> (depending on grain size). Grain sizes 1.5 and 3.0 mm also available to order. The silicone resin primer MC is used as the primer.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760685	Silicone resin coating MC 2 mm	86068	25 kg	24 prk	x	-
	Silicone resin coating MC HR1 Fescon colors	50310	25 kg		-	-
	Silicone resin coating MC HR 2 Fescon colors	50311	25 kg		-	-

x = stock product



## Piirto silicone resin coating

A liquid, water-soluble silicone resin coating that is extremely breathable and water-resistant. This durable coating is suitable for new and previously coated stone surfaces on façades. It is also a coating product in the Fescoterm thin-layer plastering system. Usage: 3.5 kg/m<sup>2</sup> (depending on grain size). The silicone resin primer MC is used as the primer.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760678	Piirto silicone resin coating 2 mm	86067	25 kg	24 prk	-	-
	Piirto silicone resin coating HR1	50312	25 kg		-	-
	Piirto silicone resin coating HR 2	50313	25 kg		-	-

x = stock product

## Fescosan-Coating

The silicone resin based Fescosan coating minimises dirt accumulation on the façade. Its homogeneous composition, optimal open time and good workability help achieve an extremely good result. The product is very water-resistant and weather-resistant and permeates water vapour. Fescosan offers good protection against algae and mould. Can be applied by rubbing and spraying. It is also a coating product in the Fescoterm thin-layer plastering system. Usage 2.2-4.2 kg/m<sup>2</sup> (depending on grain size). Also available in 1.5 and 3.0 mm grain sizes to order. The silicone resin primer MC is used as a primer.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760814	Fescosan-Coating 2 mm	86081	25 kg	24 prk	-	-
	Fescosan-Coating HR 1 Fescon colors	50314	25 kg		-	-
	Fescosan-Coating HR 2 other colors	50315	25 kg		-	-

x = stock product

## Deeply penetrating primer

Colourless primer for sand-releasing and weak bases. Usage around 0.2 l/m<sup>2</sup>/application.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760661	Deeply penetrating primer	76066	10 l	60 prk	x	-

x = stock product



## Silicone resin paint

A high-quality, matte finish silicone resin paint for façades that is highly permeable to water vapour. Suitable bases include mineral plaster surfaces, durable façade surfaces, and textured plaster surfaces. Usage: 0.2 l/m<sup>2</sup>/application.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760562	Silicone resin paint WHITE 235 12,5L	76056	12,5 l	32 prk	x	-
	Silicone resin paint HR 1 Fescon colors	50318	12,5 l		-	-
	Silicone resin paint HR 2 other colors	50319	12,5 l		-	-

x = stock product

## Fescosan-Facade paint **NEW!**



A highly water-repellent, extremely high-quality façade paint with excellent opacity. Dries quickly into a rainproof coating even in adverse weather conditions, good colour fastness. Microporous and CO<sub>2</sub> permeable, weather and alkali resistant. Dirt-repellent and self-cleaning like bionic mechanisms (repels liquid, beading effect). The protection provided by the Fescosan-Facade paint prevents the growth of algae and fungi on the treated surface. Usage: 0.2 l/m<sup>2</sup>/application. Tinting net prices.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760708	Fescosan-Facade paint	76070	12,5 l	32 prk	x	-
	Fescosan-Facade paint HR 1 Fescon colors	50320	12,5 l		-	-
	Fescosan-Facade paint HR 2 other colors	50321	12,5 l		-	-

x = stock product

## Silicate Primer

Colourless primer for the Silicate facade paint. Suitable for strengthening mineral bases. For evening the absorption of highly absorptive and sand-releasing surfaces. Does not contain solvents. Usage around 0.2-0.4 l/m<sup>2</sup> (thinned 2:1 with water)



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760616	Silicate Primer	76061	10 l	60 prk	-	-

x = stock product

## Silicate facade paint

A high-quality potassium silicate based façade paint. Effective coverage. A silicate façade paint forms an extremely weather-resistant façade coating with good water vapour permeability. Suitable bases are masonry walls, previously plastered surfaces, and durable, previously silicate-coated surfaces. Usage: around 0.18-0.25 l/m<sup>2</sup>/application.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760623	Silicate facade paint 12,5L	76062	12,5 l	32 prk	-	-
	Silicate façade paint HR 1	50322	12,5 l		-	-
	Silicate façade paint HR2	50323	12,5 l		-	-

x = stock product

## 2-K Primer

The 2-K Primer is an epoxy-based, two-component, solvent-free primer for concrete surfaces. Used for priming new and old concrete balconies. UV-protected. Usage: 0.2-0.4 kg/m<sup>2</sup>.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841762603	2-K Primer	76260	10 kg	32 prk	-	-

x = stock product



## 1-K Elastic

The Fescon 1-K Elastic is a matte, one-component durable polyurethane coating for indoor and outdoor use. UV-protected. Used for coating of new and old concrete balconies. Colour RAL 7038, light grey. Usage: approx. 1.6 kg/1 mm layer.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841762658	1-K Elastic 12,5 KG	76265	12,5 kg	44 prk	-	-

x = stock product

## Protective lacquer

The Fescon Protective Lacquer is a clear, matte polyurethane lacquer for protecting the 1-K balcony coatings in outdoor areas. Usage 150 - 250 g/m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841762757	Protective lacquer 5KG	76275	5 kg		-	-

x = stock product



## Decorative flakes

PVA flakes are used with epoxy and polyurethane-based balcony coatings. Black-and-white in colour. Other tints available to order. Usage: around. 50 g/m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841760227	Decorative flakes 1KG	76280	1 kg		-	-

x = stock product



## Thinner

A solvent-based thinner for washing tools and thinning the 1-K coatings and the 2-K Primer.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841760197	Thinner 5L	76019	5 l		-	-

x = stock product

## 13 FESCOTERM PLASTERING ACCESSORIES



### Perma-base plastering board

Used in Fescopanel board plastering as a baseboard for plastering. For outdoor and indoor use. Also available as a flexible version (for curved surfaces). Grey colour.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock

x = stock product



### Side moulding for board plastering with mesh

Used in Fescopanel board plastering at the bottom and side edges of the board. Length 2500 mm. 25 pcs./box. Colour white.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501394	Side moulding for board plastering with mesh	50139	1 pcs		x	-

x = stock product



### Side moulding for board plastering without mesh


Length 2500 mm. 10 pcs./box

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501431	Side moulding for board plastering without mesh	50143	1 pcs		x	-

x = stock product

## Bottom moulding for board plastering with mesh

Length 2500 mm. 20 pcs./box



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501554	Bottom moulding for board plastering with mesh	50155	1 pcs		x	-

x = stock product

## Top moulding for board plastering

Used in Fescopanel board plastering at the top edge of the board. Length 2500 mm. 20 pcs/bundle. Colour white.




EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501288	Top moulding for board plastering 2,5 M	50128	1 pcs		x	-

x = stock product

## Expansion joint with fibreglass mesh

The moulding is used as an expansion joint profile in plastering. Profile depth 6 mm. Length 2500 mm. A package contains 10 pcs.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501547	Expansion joint with mesh 2,5M	50154	1 pcs		x	-

x = stock product



## Expansion joint with fibreglass mesh

The moulding is used as an expansion joint profile in plastering for 5-25 mm wide movement joints. Length 2500 mm. A package contains 25 pcs.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501943	Expansion joint with mesh 2,5M	50194	1 pcs		x	-
6416841501974	Expansion joint angle	50197	1 pcs		x	-

x = stock product




## Ventilation profile for board plastering

Used in Fescopanel board plastering as a ventilation profile at the bottom of the wall.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501752	Ventilation profile for board plastering 25MM	50175	1 pcs		x	-

x = stock product



## Angle guide profile 5 mm


Used for reinforcing outer corners in thin-layer plastering. Length 2500 mm 15 pcs./box.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501837	Angle guide profile 5 mm	50183	1 pcs		x	-

x = stock product

## Socle moulding with mesh 5 mm

The PVC socle moulding with mesh is used as the starting strip in thin-layer plastering. Layer thickness 5 mm Length 2500 mm. A package contains 10 pcs. Smallest delivery batch one package.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841040718	Socle moulding with mesh 5 mm	50177	1 pcs		x	-

x = stock product

## Socle moulding 10 mm for thin-layer plastering

A PVC starting and edge strip, length 2.5 m.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501530	Socle moulding 10 mm	50153	1 pcs		x	x

x = stock product

## Water bar for thin plaster applications **NEW!**


Used as a water bar on the upper parts of thin plaster walls and under the water dampers of windows. Length 2500 mm. 10 pcs. / box.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501981	Water bar for thin plaster applications 2,5 m	50198	1 pcs		x	-

x = stock product






## Bordering moulding with mesh 6 mm

Length 2500 mm. 50 pcs./box

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501639	Bordering moulding with mesh 6 mm	50163	1 pcs		-	-

x = stock product




## Fibreglass mesh

7 mm x 7 mm, width 1000 mm. The fibreglass mesh is used in board and thin-layer plastering on wall surfaces to strengthen the plastering surface. Can also be used with floor levelling compounds. Alkali-protected. One roll contains 50 m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841500380	Fibreglass mesh 1000 mm 50 m <sup>2</sup> /rll	50038	1 roll	24 rll	x	x

x = stock product



## Corner bead 100 x 150 mm


Used for corner reinforcement in thin-layer plastering. Length 2500 mm. 50 pcs/bundle. Smallest delivery batch one bundle.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841500502	Corner bead 100 x 150 mm	50050	1 pcs		x	x

x = stock product

## Corner bead roll 100 x 150 mm

Used for corner reinforcement in thin-layer plastering. Angle can be freely adjusted between 0 and 180 degrees. Length 50 lineal metres. Smallest delivery batch one box.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501561	Corner bead roll 100 x 150 mm	50156	1 roll		x	-

x = stock product

## Stick-on corner moulding 6 mm

Length 2600 mm 30 pcs./box



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501844	Stick-on corner moulding 6 mm	50184	1 pcs		-	-

x = stock product


## Stick-on corner moulding 10 mm

Used for finishing window frames in thin-layer plastering. The moulding is fastened to the window or door frame using the included adhesive tape. A protective plastic sheet can be easily fastened to the frame moulding with adhesive tape. Length 2600 mm. A package contains 60 pcs.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841500601	Stick-on corner moulding 10 mm white	50060	1 pcs		x	x

x = stock product



## Stick-on corner moulding with mesh

Used for finishing window frames in thin-layer plastering. The moulding is fastened to the window or door frame using the included adhesive tape. A protective plastic sheet can be easily fastened to the frame moulding with adhesive tape. Length 2600 mm. A package contains 50 pcs.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501509	Stick-on corner moulding with mesh	50150	1 pcs		x	-

x = stock product



## Stick-on corner moulding 9 mm grey

Length 2600 mm. 60 pcs./box

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501578	Stick-on corner moulding 9 mm grey	50157	1 pcs		-	-

x = stock product



## Stick-on corner moulding with mesh 9 mm grey

Length 2600 mm. 50 pcs./box

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501615	Stick-on corner moulding with mesh 9 mm grey	50161	1 pcs		-	-

x = stock product

## Fescoterm aluminium profile

Aluminium profile for protecting the bottom edge of the insulation in the Fescoterm thin-layer plastering system. Package size 10 pcs/bundle. Smallest delivery batch one bundle. Length 2.5 m.




EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841500519	Fescoterm aluminium profile 50 mm 2,5 m	50051	1 pcs		-	-
6416841500526	Fescoterm aluminium profile 70 mm 2,5 m	50052	1 pcs		-	-
6416841500533	Fescoterm aluminium profile 100 mm 2,5 m	50053	1 pcs		-	-
6416841500540	Fescoterm aluminium profile 140 mm 2,5 m	50054	1 pcs		-	-
6416841500557	Fescoterm aluminium profile 160 mm 2,5 m	50055	1 pcs		-	-
6416841500571	Fescoterm aluminium profile 80 mm 2,5 m	50057	1 pcs		-	-
6416841501356	Fescoterm aluminium profile 180 mm 2,5 m	50135	1 pcs		-	-
6416841501363	Fescoterm aluminium profile 200 mm 2,5 m	50136	1 pcs		-	-
6416841501370	Fescoterm aluminium profile 200-300 mm	50137	1 pcs		-	-

x = stock product

## Drip moulding with mesh

A mesh reinforcement attached to the front edge of the aluminium profile. Drip moulding. Application thickness 10 mm. Length 2.5 m, 15 pcs/package.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501523	Drip moulding with mesh 2,5M	50152	1 pcs		-	-

x = stock product



## Connector

Used to connect Fescoterm aluminium profiles to each other. Reduces the risk of cracking in insulation plastering. A bag contains 100 pcs. Supplied in batches of one bag.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501585	Connector 100 PCS	50158	100 pcs		-	-

x = stock product



## Fescoterm plug fastener

The nylon fastener is used to fasten the Fescoterm thin-layer plastering system insulation. Package size 100 pcs/box.


EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Fescoterm plug fastener 115 mm 100 pcs	50420	100 pcs		-	-
	Fescoterm plug fastener 135 mm 100 pcs	50421	100 pcs		-	-
	Fescoterm plug fastener 155 mm 100 pcs	50422	100 pcs		-	-
	Fescoterm plug fastener 175 mm 100 pcs	50423	100 pcs		-	-
	Fescoterm plug fastener 195 mm 100 pcs	50424	100 pcs		-	-
	Fescoterm plug fastener 215 mm 100 pcs	50425	100 pcs		-	-
	Fescoterm plug fastener 235 mm 100 pcs	50426	100 pcs		-	-
	Fescoterm plug fastener 275 mm 100 pcs	50427	100 pcs		-	-

x = stock product



## Covering flange mineral wool

Used as a covering flange for the Fescoterm thin-layer plastering system's inset fasteners. Diameter 65 mm, thickness 15 mm. 100 pcs/box.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501714	Covering flange mineral wool 100PCS	50171	100 pcs		-	-

x = stock product

## Covering flange EPS

Used as a covering flange for the inset fasteners of the Fescoterm thin-layer plastering system. Diameter 65 mm, thickness 15 mm. 100 pcs/box.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501721	Covering flange EPS 100PCS	50172	100 pcs		-	-

x = stock product

## Installation piece

For straightening the socle profile and adjusting its distance from the mounting surface on uneven surfaces. 100 pcs/box.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501738	Installation piece 100PCS	50173	100 pcs		-	-

x = stock product



## Fastener for the Fescoterm thick-layer plastering system

A fastener for fastening the insulation and mesh to the bedding in the Fescoterm thick-layer plastering insulation system. Usage: 4-10 pcs/m<sup>2</sup>. 100 pcs/box.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Fastener for the Fescoterm thick-layer plastering system	50097	100 pcs		-	-
	MERK mounting hook 50 mm 100 pcs 50 mm 100 pcs	50400	100 pcs		-	-
	MERK mounting hook 70 mm 100 pcs	50401	100 pcs		-	-
	MERK mounting hook 100 mm 100 pcs	50402	100 pcs		-	-
	MERK mounting hook 150 mm 100 pcs	50403	100 pcs		-	-
	MERK mounting hook 160 mm 100 pcs	50404	100 pcs		-	-
	MERK mounting hook 170 mm 100 pcs	50405	100 pcs		-	-
	MERK mounting hook 180 mm 100 pcs	50406	100 pcs		-	-
	MERK mounting hook 200 mm 100 pcs	50407	100 pcs		-	-

x = stock product



## Plaster mesh fastener RVK

Used in thick-layer plastering to fasten the mesh to the base so that it stays clear of the base. Material RST A2. 500 pcs/package.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841501783	Plaster mesh fastener RVK 5/6	50178	500 pcs		-	-
6416841501790	Plaster mesh fastener RVK 10/6	50179	500 pcs		x	-

x = stock product

## Plaster mesh Tammet

Hot-dip galvanised plaster mesh for thick-layer plastering. Opening size 19 x 19 mm/1.0 mm.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841501486	Plaster mesh Tammet 250 mm	50148	1 roll	48 rll	-	-
6416841500120	Plaster mesh Tammet 1000 mm	50012	1 roll	12 rll	x	-
6416841500243	Plaster mesh Tammet 1500 mm	50024	1 roll	12 rll	x	-

x = stock product

## 14 SANDS



### Seaming and blasting sand SPH

Seaming sand for the seaming of yard stones and slabs and sand blasting. Grain size 0.1-0.6 mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610041	Seaming and blasting sand SPH 0,1-0,6 mm	61004	25 kg	49 sk	x	x
6416841620019	Seaming and blasting sand SPH 0,1-0,6 mm	62001	1000 kg		-	x
	Seaming and blasting sand SPH		1 kg		-	-

x = stock product



### Seaming sand, black SHM

Hard, impermeable and almost dust-free black seaming sand for the seaming of yard stones and slabs. Grain size 0.1–0.6 mm. Also suitable for sandblasting.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610133	Seaming sand, black SHM	61013	25 kg	49 sk	-	-
	Seaming sand, black SHM		1 kg		-	-

x = stock product

## Blasting sand PH

Screened, clean natural sand for sand blasting. Grain size 0.5-1.6 mm.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841610058	Blasting sand PH 0,5-1,6 mm	61005	25 kg	49 sk	x	x
6416841620026	Blasting sand PH 0,5-1,6 mm	62002	1000 kg		-	x
	Blasting sand PH		1 kg		-	-

x = stock product

## FescoStone Seaming sand **NEW!**

FescoStone is jointing sand for paving. FescoStone is made of natural sand and binders. FescoStone prevents weeds from growing, does not wash away with rain, and reduces the needs for maintaining the gaps between paving stones. Once the product has hardened, it still allows water to permeate through it, and it is suitable for seams of less than 5 mm. Recommended for grey concrete stones. Material usage: stone 60x140x280 mm, app. 3-4 kg/m<sup>2</sup>/2 mm seam width.



					HAUSJÄRVI	HAUKIPUDAS
EAN code	Product name	Product number	Package size	Platform size	In Stock	In Stock
6416841610195	FescoStone Seaming sand	61019	25 kg	49 sk	x	-

x = stock product





## Sanding aggregate HSS

Dried gritting crushed stone macadam for gritting passages in yards and for preventing slipperiness. Grain size 3-6 mm. Pack size 20 kg plastic sack and a 1000 kg large sack.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610096	Sanding aggregate HSS 3-6 mm	61009	20 kg	49 sk	x	x
6416841610355	Sanding aggregate HSS 3-6 mm	61035	1000 kg		-	-

x = stock product



## Playground sand LH

Screened, clean natural sand for yard construction, e.g. for sandboxes or installation use. Grain size 0-2 mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610072	Playground sand LH 0-2 mm	61007	25 kg	49 sk	x	-
6416841610119	Playground sand LH 0-2 mm	61011	1000 kg		-	-

x = stock product



## Playground sand TRH

Playground sand is sieved, round, non-compacting, pure natural sand under playground equipment to minimise impact when tripping or falling. Playground sand grain size is 1-8 mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841620163	Playground sand TRH 1-8 mm	62016	1000 kg		-	-

x = stock product

## Levelling sand TH

Screened, clean natural sand for the installation of yard stones and slabs, and the levelling of the base. Grain size 0-8 mm.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610065	Levelling sand TH 0-8 mm	61006	25 kg	49 sk	x	-
6416841610102	Levelling sand TH 0-8 mm	61010	1000 kg		-	-

x = stock product

## Stone dust KVT

Crushed stone for driveways and garden paths and as foundation for levelling the ground for garden tiles. Grain size 0-6 mm, mixed colour.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610126	Stone dust KVT 0-6 mm	61012	25 kg	49 sk	-	-
6416841610300	Stone dust KVT 0-6 mm	61030	1000 kg		-	-

x = stock product

## Aggregate 8 - 16 mm

Crushed stone for foundations and filling the sides of walls.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610409	Aggregate 8 - 16 mm	61040	1000 kg		-	-

x = stock product



## Black blasting abrasive PRM OKTO

Blasting abrasive is made of crushed, hard rock material. It is a coarse media suitable for sandblasting for both professional and home use. Hard abrasive is also suitable for seaming yard stones. Deep-cutting blasting abrasive is almost dust-free, making it an excellent media for sandblasting.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841610164	Black blasting abrasive PRM OKTO	61016	25 kg	49 sk	-	-
6416841620156	Black blasting abrasive PRM OKTO	62015	1000 kg		-	-
	Black blasting abrasive PRM OKTO		1 kg		-	-

x = stock product

## Filter sand



Filter sand produced by Fescon is widely used in a number of different water filtering processes. Our products are based on carefully selected raw materials and industrial sand processing methods. We provide precision sieved sand fractions for water filtering for all our customers' needs.

GRAIN SIZE

Standard sizes: 0.8–1.2 mm and 1.2–2.0 mm.

Other fractions available where required.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841615831	Filter sand SUH 0,8-1,2 mm	61583	25 kg	49 sk	-	-
	Filter sand 0,8-1,2 mm		1000 kg		-	-
	Filter sand 0,8-1,2 mm		1 kg		-	-
	Filter sand 1,2-2,0 mm		25 kg		-	-
	Filter sand 1,2-2,0 mm		1000 kg		-	-
	Filter sand 1,2-2,0 mm		1 kg		-	-
	Filter sand		1 kg		-	-

x = stock product

## Top-dressing sand for golf courses

Top-dressing sand is manufactured from natural sand. The sand is precision sieved to the desired fractions. The dust removal system at our plant considerably reduces the amount of fine particles in the sand, resulting in significantly less dust at the application stage compared to regular sand. The removal of excess dust also improves conditions at the putting green.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Top-dressing sand for golf courses		1 kg		-	-

x = stock product

## Fairway sand for golf courses

Fairway sand is manufactured from natural sand. It can be made in two different ways, wet-sieved or precision-sieved. The benefit of precision-sieved product is its more precise fraction distribution.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Fairway sand for golf courses		1 kg		-	-

x = stock product

## Bunker sand for golf courses

Bunker sand is manufactured from natural sand according to customer needs. Available in wet-sieved and precision-sieved varieties. Precision-sieved bunker sand may also be manufactured according to USGA standards.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Bunker sand for golf courses		1 kg		-	-

x = stock product

## Substrate for natural grass

The substrate is manufactured from precision-sieved sand and sieved peat. Sand and peat are mixed to the desired ratio. The correct distribution of different fractions and the decomposition stage of peat have a major impact on the functioning of the substrate. Characteristics such as water permeability and moisture retention are important in the manufacturing of substrates.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Substrate for natural grass		1 kg		-	-

x = stock product

## Top-dressing sand for natural grass



Top-dressing sand is manufactured from natural sand. The sand is precision sieved to the desired fractions. The dust removal system at our plant considerably reduces the amount of fine particles in the sand, resulting in significantly less dust at the application stage compared to regular sand. The removal of excess dust also improves conditions at the putting green.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Top-dressing sand for natural grass		1 kg		-	-

x = stock product

## Top-dressing sand for artificial turf



Top-dressing sand is manufactured from natural sand. The sand is precision sieved to the desired fractions. The dust removal system at our plant considerably reduces the amount of fine particles in the sand, resulting in significantly less dust at the application stage compared to regular sand. The removal of excess dust also improves conditions at the putting green.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Top-dressing sand for artificial turf		1 kg		-	-

x = stock product



## Long jump sand

Long jump sand is manufactured from natural sand, dried and precision sieved. During the manufacturing process, dust is removed from sand with a dust removal system; thanks to this procedure, the sand is almost dust-free.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Long jump sand		1 kg		-	-

x = stock product

## Manège sand

Manège sand is manufactured from natural sand according to customer needs.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Manège sand		1 kg		-	-

x = stock product

## Substrate for lawn

The substrate is manufactured from precision-sieved sand and sieved peat. Sand and peat are mixed to the desired ratio. The correct distribution of different fractions and the decomposition stage of peat have a major impact on the functioning of the substrate. Characteristics such as water permeability and moisture retention are important in the manufacturing of substrates.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Substrate for lawn		1 kg		-	-

x = stock product

## Top-dressing sand for baseball fields (artificial turf)



Top-dressing sand is manufactured from natural sand. The sand is precision sieved to the desired fractions. The dust removal system at our plant considerably reduces the amount of fine particles in the sand, resulting in significantly less dust at the application stage compared to regular sand. The removal of excess dust also improves conditions at the putting green.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Top-dressing sand for baseball fields (artificial turf)		1 kg		-	-

x = stock product



## Beach Volley sand

The sand is manufactured from natural sand, dried and precision sieved to the desired fractions.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Beach Volley sand		1 kg		-	-

x = stock product

## Playground sand for playgrounds



Playground sand is sieved, round, non-compacting, pure natural sand under playground equipment to minimise impact when tripping or falling. Playground sand grain size is 1-8 mm. Product tested and approved according to the SFS-EN 1177:2008 method.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Playground sand TRH		1 kg		-	-

x = stock product

## Alkali-resistant bed material GR-GRANULI™

Thanks to its composition and high melting point, alkali-resistant GR-Granuli is suitable for power plants where difficult materials, such as glues, are incinerated, or where a very high bed temperature is required. The melting point of GR-Granuli is over 1400°C.

### GRAIN SIZE

Standard grain size 0.5–1.5 mm.

Other fractions available where required.

### PACKAGES

1 ton big bag

In bulk



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Alkali-resistant bed material GR-GRANULI™		1 kg		-	-

x = stock product

## Bed sand HP1000™ for standard boiler conditions

Bed sand manufactured from natural sand for standard boiler conditions.

### GRAIN SIZE

Available in several different fractions.

### PACKAGES

1 ton big bag

In bulk



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
	Bed sand HP1000™ for standard boiler conditions		1 kg		-	-

x = stock product

## 15 FESCOTOP FLOOR HARDENERS



### Fescotop F10

A quartz-based dry-shake hardener for hardening concrete surfaces. Grain size 3.0 mm. Available in 12 standard colours. Coloured dry-shake hardeners are offered separately. Minimum manufacturing batch of coloured dry-shake hardeners is 3 tonnes. Usage: 5-10 kg/m<sup>2</sup>.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770035	Fescotop F10 3 mm natural/betharm	77003	25 kg	49 sk	x	x
6416841771209	Fescotop F10 3 mm bright gray	77120	25 kg	49 sk	-	-
6416841770608	Fescotop F10 3 mm black	77060	25 kg	49 sk	-	-
6416841770615	Fescotop F10 3 mm bone white	77061	25 kg	49 sk	-	-
6416841770622	Fescotop F10 3 mm dark brown	77062	25 kg	49 sk	-	-
6416841770639	Fescotop F10 3 mm brown-gray	77063	25 kg	49 sk	-	-
6416841770646	Fescotop F10 3 mm terracotta	77064	25 kg	49 sk	-	-
6416841770653	Fescotop F10 3 mm green	77065	25 kg	49 sk	-	-
6416841770660	Fescotop F10 3 mm light blue	77066	25 kg	49 sk	-	-

x = stock product

## Fescotop F45K

A corundum-based dry-shake hardener for hardening concrete surfaces. Grain size 3 mm. Available in nine standard colours. Coloured dry-shake hardeners are offered separately. Minimum manufacturing batch of coloured dry-shake hardeners is 3 tonnes. Usage: 5-10 kg/m<sup>2</sup>.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770042	Fescotop F45K 3 mm natural/betharm	77004	25 kg	49 sk	x	x
6416841770011	Fescotop F45K 3 mm bright gray	77001	25 kg	49 sk	-	-
6416841770677	Fescotop F45K 3 mm black	77067	25 kg	49 sk	-	-
6416841770684	Fescotop F45K 3 mm bone white	77068	25 kg	49 sk	-	-
6416841770691	Fescotop F45K 3 mm dark brown	77069	25 kg	49 sk	-	-
6416841770707	Fescotop F45K 3 mm brown-gray	77070	25 kg	49 sk	-	-
6416841770714	Fescotop F45K 3 mm terracotta	77071	25 kg	49 sk	-	-
6416841770721	Fescotop F45K 3 mm green	77072	25 kg	49 sk	-	-
6416841770738	Fescotop F45K 3 mm light blue	77073	25 kg	49 sk	-	-

x = stock product

## Fescotop F300

A corundum-based dry-shake hardener for hardening concrete surfaces. Grain size 3 mm. The minimum production batch is 3000 kg. Usage: 5-10 kg/m<sup>2</sup>.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770806	Fescotop F300 natural/betharm	77080	25 kg	49 sk	-	-

x = stock product





## Fescotop F90K high-performance concrete

Fescotop F90K is a cement-based, fibre-reinforced high-performance concrete for sites requiring impermeable concrete surfaces resistant to wear and corrosive substances. The maximum grain size is 3.0 mm. Contains corundum.

Minimum delivery batch is 3000 kg.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770264	Fescotop F90K high-performance concrete	77026	25 kg	49 sk	-	-

x = stock product

## Bedding mortar 2-K for high-performance concrete

Fescon Bedding mortar 2-K for high-performance concrete is a 2-component, cement-based, dispersion-modified product, applied as the bedding mortar for Fescotop F90K High-performance concrete. The maximum grain size is 1.2 mm.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770271	Bedding mortar 2-K for high-performance concrete, powder	77027	25 kg	49 sk	-	-
6416841769107	Bedding mortar 2-K for high-performance concrete, liquid dispersion	76910	10 l		-	-

x = stock product



## Curing compound

One-component water-soluble polymer dispersion. Applied on fresh concrete to prevent the concrete from drying too rapidly. A clear liquid after drying. Coverage around 10 m<sup>2</sup> / l.

EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841770226	Curing compound 5 L	77022	5 l	90 prk	-	-
6416841770219	Curing compound 20L	77021	20 l	32 prk	x	x

x = stock product

## 16 TOOLS

### FescoBlaster FBL mortar pump

Hand-held mortar pump for applying plaster and concrete to seams and for fixing holes in concrete and stone structures, for example. A very high-quality, professionally designed mortar pump that allows you to easily apply different pastes into difficult places. Easy and simple to use: Pull the trigger to fill the pump's container, and then fill the hole by pushing the paste out of the pump.



EAN code	Product name	Product number	Package size	Platform size	HAUSJÄRVI	HAUKIPUDAS
					In Stock	In Stock
6416841100009	FescoBlaster FBL 1 Mortar pump, nozzle 18 mm rectangle	10000	1 pcs		-	-
6416841100016	FescoBlaster FBL 2 Mortar pump, nozzle 24 mm round, bent	10001	1 pcs		-	-
6416841100023	FescoBlaster FBL 3 Mortar pump, nozzle 18 mm rectangle, bent	10002	1 pcs		-	-
6416841100030	FescoBlaster FBL 4 Mortar pump, nozzle 10 mm rectangle	10003	1 pcs		-	-
6416841100054	FescoBlaster FBL 6 Mortar pumps, tubing 13 mm	10005	1 pcs		-	-
6416841100061	FescoBlaster FBL 7 Mortar pumps, tubing 25 mm	10006	1 pcs		-	-
6416841100108	FescoBlaster FBL piston, spare part	10010	1 pcs		x	-
6416841100115	FescoBlaster FBL pump cover, spare part	10011	1 pcs		x	-

x = stock product

# Index

1-K Elastic	68	ELK Clinker element grout	24
2-K Primer	67	ELT Brick element grout	23
Adhesion promoter	39	Expansion joint with fibreglass mesh	71
Adhesive mortar FLL	60	Expansion joint with fibreglass mesh	72
Adhesive mortar FLL Winter	60	Facade coating JSP 0.5	57
Adhesive plaster TL	53	Facade coating JSP 1.5	57
Aggregate 8 - 16 mm	85	Fairway sand for golf courses	87
Alkali-resistant bed material GR-GRANULI™	91	Fastener for the Fescoterm thick-layer plastering system	80
Angle guide profile 5 mm	72	FescoBlaster FBL mortar pump	95
Antique plaster AL	59	Fescofine	32
Base levelling plaster	49	Fescoson Primer KP	40
Beach Volley sand	90	Fescorapid	31
Bed sand HP1000™ for standard boiler conditions	91	Fescosan-Coating	65
Bedding mortar 2-K for high-performance concrete	94	Fescosan-Facade paint	66
Bedding plaster LF	25	Fescoseal A+B	39
Bedding plaster LF RD	25	FescoStone Seaming sand	83
Bedding plaster VF	27	Fescoterm aluminium profile	77
Black blasting abrasive PRM OKTO	86	Fescoterm plug fastener	78
Blasting sand PH	83	Fescotop F10	92
Block mortar M 100/500 Winter	21	Fescotop F300	93
Block mortar M100/500	21	Fescotop F45K	93
Bolting plaster SR	51	Fescotop F90K high-performance concrete	94
Bordering moulding with mesh 6 mm	74	Fibre plaster FL	59
Bordering strip 30x30x2000 mm	36	Fibreglass mesh	74
Bordering strip 8x150 mm	36	Filling plaster TLR	28
Bottom moulding for board plastering with mesh	71	Filter sand	86
Brick bedding plaster TTF	26	Finishing plaster LRF	26
Bunker sand for golf courses	87	Finishing plaster LRF RD	26
Cement concrete S 100	7	Finishing plaster VHF	27
Cement plaster S 30	5	Fireproof casting concrete TKV	12
Clay stove mortar SUL	12	Fireproof masonry mortar TKM	12
Coarse floor levelling compound LM 5000	30	Fireproof repairing compound TTK	13
Compact mortar Heavy M100/600 Winter	19	Floor compound LM 6000	30
Compact mortar Heavy M100/600	18	Floor concrete LB 7	31
Compact mortar M100/600	16	Floor levelling plaster LT 4000	31
Compact mortar M100/600 Winter	17	Flow GS 3.0 mm Gypsum floor mass	34
Connector	78	Flow H	32
Corner bead 100 x 150 mm	74	Flow HS	33
Corner bead roll 100 x 150 mm	75	Flow Primer	35
Corro concrete K 30	6	FlowBase	33
Corro concrete K 45	7	FlowFiber	34
Corro shotcrete RKB	54	FlowPlan	32
Covering flange EPS	79	FPTL-165 Industrial mortar	13
Covering flange mineral wool	79	Grouting concrete JB 1000/3	8
Curing compound	94	Grouting concrete JB 600/3	8
Decorative flakes	68	Grouting concrete TJB Winter	9
Deeply penetrating primer	65	Gypsum plaster mix GL	28
Drain flange	40	Indoor lime-cement plaster SR7	28
Drain flange KL-B	41	Installation piece	79
Drip moulding with mesh	77	Joint filler SF	25
Elevation mark	36	Korroguard R 0.6 mm	55

Korrogard R 1.2 mm	55	Silicone resin paint	66
Korrogard R 3.0 mm	55	Silicone-resin primer MC	63
Korroshot D KSD 5.0 mm	56	SILKO Corro SKC C35/45	52
Levelling compound for wet areas WTT	27	SILKO Rapid Corro SPC C35/45	52
Levelling plaster TSL	60	Socle and adjusting plaster SOL	59
Levelling sand TH	85	Socle moulding 10 mm for thin-layer plastering	73
Lightweight lime-cement plaster KEV KS 35/65	48	Socle moulding with mesh 5 mm	73
Lime paint KM	62	Special concrete PIKIS	11
Lime plaster K100/1200	49	Stick-on corner moulding 10 mm	75
Lime-cement coating JL	58	Stick-on corner moulding 6 mm	75
Lime-cement coating KSP	58	Stick-on corner moulding 9 mm grey	76
Lime-cement plaster HD KS 20/80 fibre	48	Stick-on corner moulding with mesh	76
Lime-cement plaster HD KS 35/65 fibre	48	Stick-on corner moulding with mesh 9 mm grey	76
Lime-cement plaster KS 10/90	46	Stone adhesive KVL	21
Lime-cement plaster KS 35/65	46	Stone colour KS	62
Lime-cement plaster KS 50/50	47	Stone colour S	62
Lime-cement plaster KS 65/35	47	Stone dust KVT	85
Long jump sand	89	Substrate for lawn	89
Manège sand	89	Substrate for natural grass	88
Masonry mortar M100/600	14	Thin plaster S 06	5
Masonry mortar M100/600 Winter	15	Thin-layer compo plaster KRL	58
Mortar for tongue and groove blocks PHL Winter	22	Thinner	69
Mortar for tongue-and-groove blocks PHL	22	Tile adhesive plaster ILL	43
Non-run filling plaster VTL	53	Tile adhesive plaster SS2	43
Overlevelling plaster YTL	54	Tile adhesive plaster SSL Lite	43
Permabase plastering board	70	Tile adhesive plaster VSL	42
Piirto silicone resin coating	64	Tile seaming plaster SML	44
Pipe riser sealing compound HTM	13	Top moulding for board plastering	71
Plaster mesh fastener RVK	80	Top-dressing sand for artificial turf	88
Plaster mesh Tammet	81	Top-dressing sand for baseball fields (artificial turf)	90
Playground sand for playgrounds	90	Top-dressing sand for golf courses	87
Playground sand LH	84	Top-dressing sand for natural grass	88
Playground sand TRH	84	Underfloor heating filler LL 5500	30
Primer PLUS	35	Wall surface strengthening membrane	29
Protective lacquer	68	Water bar for thin plaster applications	73
Protective paint	63	Waterproofing accessories FS	41
Quick Drill 45	52	Waterproofing accessories VE	42
Rapid concrete PB	11	Waterproofing compound	38
Reinforcing mortar FVL	61	Waterproofing compound WS	38
Repairing plaster KL 1.2	53	Waterproofing strip	40
Repairing plaster KL 40	54	Ventilation profile for board plastering	72
Sanding aggregate HSS	84	Vertical-joint concrete PSB K30	9
Sanitary silicone	45	Vertical-joint concrete PSB K40	10
Seaming and blasting sand SPH	82	Vertical-joint concrete PSB K50	10
Seaming sand, black SHM	82	Vertical-joint concrete winter TPSB K30	9
Separation fabric 1.5x50 m	37	Vertical-joint concrete winter TPSB K40	10
Side moulding for board plastering with mesh	70	Vertical-joint concrete winter TPSB K45	11
Side moulding for board plastering without mesh	70	Wet plaster	50
Silicate facade paint	67	Winter concrete TB S 30	6
Silicate Primer	67	Winter concrete TB S 40	6
Silicone resin coating MC	64	Winterbolting plaster SR	51

Winter-time masonry mortar TML

20



**Product advice**

+358 20 789 5901

# FESCON

## **A Finnish developer and manufacturer**

Founded in 1984, Fescon Oy is the largest Finnish developer and manufacturer of mortar, sand and flooring products, and solutions for the construction industry.

## **High-quality mortar and sand products for construction**

Fescon's main products are dry mortars and concretes, plaster and repair mortars, facade coatings and paints, wall and floor plasters, Nanten concrete floor coatings, insulation plastering systems, and tiling and water-proofing products. We also rent silo and mixing equipment for masonry and plastering sites. In addition, our sand business unit offers a variety of sand and mineral products. Our sand products business unit also offers various sands that are suitable for golf and sports courts, court-yards, power plants, or sandblasting, for example. We also offer technology services for industrial applications.

## **Reliable and efficient logistics, and professional customer service**

Fescon's strengths are quality products, reliable and fast deliveries, customer service, a fast colour card service and longterm product development in cooperation with customers.



www.fescon.com

### **Fescon Oy**

Hämeenkatu 9, FI-05800 Hyvinkää, Finland

tel. +358 20 789 5900 | fescon@fescon.fi

www.fescon.fi

### **Factories in Finland:**

Hausjärvi | Haukipudas | Raahe | Harjavalta

### **Nanten Oy**

Teollisuustie 6, FI-04300 Tuusula, Finland

tel. +358 9 274 7970 | nanten@nanten.com

www.nanten.fi