

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## FIREPROOF REPAIRING COMPOUND TTK



### Product description

Fescon Fireproof Repairing Compound is a compound with a cement binder, designed for the repairs of cracks and cavities in the fireboxes of household fireplaces.

- Easy to use
- Heat resistance +1300°C
- Layer thickness 5 - 20 mm
- Good workability characteristics

### Applications

- Fireplaces, ovens, grills, ground ovens, and their fireboxes and roofs
- Can be used for patching cracks in the shell and jointing fireplaces and sauna stoves

**The product is listed in the portal for building products that can be used in Nordic Swan Ecolabelled buildings.**

### Instructions

### Work instructions

Mix around 5 dl of clean, room-temperature water into 2 kg of plaster powder. You can use a straight-tipped trowel, jointing iron or a rubber glove to spread the plaster. In order to ensure adhesion, brush the patched location clean with a steel brush and remove any dust with a damp rag. Use a screwdriver to enlarge the cracks before patching. The durability of the patches is improved, if they are allowed to bind for a couple of days before heating. Be careful not to heat the oven too much the first time.

### Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>



Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

Updated 20.12.2024 Printed 2.7.2025

## Technical information

<b>Water requirement</b>	2.5 dl/kg
<b>Type</b>	Powder
<b>Colour</b>	Grey
<b>Maximum grain size</b>	2.0 mm
<b>Package size</b>	2 kg plastic container
<b>Storage</b>	18 months in the original package in a dry location
<b>Layer thickness</b>	5 - 20 mm
<b>Workability time</b>	1 h

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.