

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Updated 31.8.2023 Printed 25.4.2024

CURING COMPOUND

Product description

The Fescon Curing Compound is a one-component, water-soluble polymer dispersion designed for fresh concrete to prevent it from drying too rapidly. The product doesn't contain paraffin.

Applications

The product can be applied to fresh concrete on both horizontal and vertical surfaces on all concrete surfaces. Due to it being odourless and drying rapidly, the product is suitable for use in almost all applications. The product does not affect the adhesion of any future coatings.

Instructions

Work instructions

The product is a ready-to-use solution we do not recommend thinning. Mix the product carefully before use. We recommend applying the product evenly with a gardening spray or an industrial spray.

Other considerations

Wash tools with water.

Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>



Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Technical information

| | |
|---------------------------------|--|
| Material usage | approx. 10 m / l |
| Type | liquid |
| Colour | white, bright after drying |
| Package size | 5 l and 20 l |
| Storage | 12 – 15 months in dry conditions at a temperature of +5°C...+30°C in tightly sealed containers |
| Sufficiency | 0.1 µm |
| Lowest usage temperature | +5°C |
| Drying time | 1-4 hours depending on air humidity and temperature |
| pH | 7 - 9 |
| Solids content | 8- 10% |
| Viscosity | 10 – 200 mPa.s |
| Weight | nominal weight 1.02 kg/l |