

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
[www.fescon.fi](http://www.fescon.fi)

Updated 16.2.2023 Printed 28.3.2024

## WATERPROOFING STRIP

### Product description

Fibre-based waterproofing strip for use in the Fescon WS and waterproofing systems. The waterproofing strip can be used for through-holes with a maximum diameter of 75 mm.

- The strip dimensions are 0.15 x 25 m, 10 rolls per box
- Also available as waterproofing membrane 1.0 x 10 m. Not suitable for the Fescoseal A+B waterproofing system



### Applications

- Strengthening waterproofing strip used in the Fescon WS and waterproofing systems
- Suitable for making through-hole pieces up to 75 mm in diameter

**The product is listed in the portal for building products that can be used in Nordic Swan Ecolabelled buildings.**

### Instructions

#### Installation

- Spread the waterproofing compound into the corners, where two elements meet, and into through-holes. The waterproofing accessories are attached to the wet waterproofing compound. Spread the waterproofing compound thoroughly over the strengthening strips using a brush or roller. Make sure that the strips are fully attached to the waterproofing compound below, with no exposed parts. The strengthening strips must be between two waterproofing compound layers.

#### Other points to note

- Through-holes can also be made using waterproofing strip 0.15 x 25 m or waterproofing membrane. A waterproofing strip can be used for through-holes with a maximum diameter of 75 mm. Any larger through-holes are made using waterproofing membrane or a drain flange 300 x 300 fibre product. A ready-made drain flange must be used for drains.
- Waterproofing is carried out in accordance with RT cards and RIL guidelines.

#### Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

Updated 16.2.2023 Printed 28.3.2024

## Technical information

<b>Colour</b>	blue
<b>Package size</b>	box of 10 rolls
<b>Storage</b>	store in a warm place, must not freeze
<b>Usage temperature</b>	+10°C...+25°C (base and indoor temperature)
<b>Size</b>	waterproofing strip 0.15 x 25 mwaterproofing membrane 1.0 x 10 mthickness approx. 0.5 mm