Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

NANTEN PU TIX



Product description

Liquid hardening/thickening agent (Component C) for use in solvent-free Nanten polyurethane coatings, designed to reduce sagging on inclined surfaces.

Applications

- Strongly sloped surfaces (≥1:100)
- Skirtings
- Drainage areas

Instructions

Mixing

The A-component of Nanten PU Flex Bio coating must first be mixed to a uniform consistency. A small portion of Part A is set aside – refer to the Mixing Ratio section for guidance. Nanten PU Tix is then added to Part A and mixed thoroughly for one minute. After that, Part B is added and mixed for two minutes, avoiding air entrapment in the mixture. Finally, the mixture is poured into a clean container and mixed for an additional one minute, again avoiding air entrapment.

Mixing ratio

The additive accelerates the curing reaction. We recommend preparing no more than 2–4 litres of coating mixture at a time.
For painting skirtings, Nanten PU Tix should be used at 1% by weight of the total coating mixture.
Example: 0.75 litres of Nanten PU Flex Bio Part A + 1% (= 12.6 g = 12.1 ml) Nanten PU Tix + 0.25 litres of Nanten PU Flex Bio Part B.

Waste handling

Storage and handling of waste
See the separate storage and disposal instructions https://www.fescon.fi/en/material-bank

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Technical information

Package size	1 l
Storage	+5°C to +25°C, protected from light, maximum storage time 12 months
Density	1.02 kg/l

Remember to consult the Maintenance Instructions for Coated Floors and the product Safety Data Sheet on our website at www.fescon.fi, or request a copy by calling +358 9 274 7970. Although the technical details provided in this product description are based on our best knowledge and experience, the information above should always be regarded as indicative. The user is responsible for verifying the suitability of the product for the intended application. If the instructions are not followed, the user assumes full responsibility for any resulting damage or consequences. Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.