

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## NANTEN ANTI-SLIP

### Product description

Polyethylene beads for mixing into varnishes, paints, or coatings.  
Available in three different grain sizes: 0.100 mm, 0.250 mm and 0.500 mm.

### Applications

- Used as an anti-slip agent in wet areas and on inclined surfaces, such as spas, swimming pools, shower rooms, changing rooms, and ramps

### Instructions

### Instructions for use

Mix into varnish, paint, or coating. For example, use at 1.5–15% by weight. The ready-to-use mixture is applied by roller onto the finished coating/paint film.

1 dl 100 = 96 g

1 dl 250 / 500 = 128 g

### Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>



Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## Technical information

<b>Type</b>	Coarse powder
<b>Colour</b>	White
<b>Package size</b>	0.5 kg metal can
<b>Storage</b>	Storage in a dry place, at room temperature
<b>Density</b>	100, 0.96 g/cm <sup>3</sup> 250 1.28 g/cm <sup>3</sup> 500 1.28 g/cm <sup>3</sup>

Remember to consult the Maintenance Instructions for Coated Floors and the product Safety Data Sheet on our website at [www.fescon.fi](http://www.fescon.fi), or request a copy by calling +358 9 274 7970. Although the technical details provided in this product description are based on our best knowledge and experience, the information above should always be regarded as indicative. The user is responsible for verifying the suitability of the product for the intended application. If the instructions are not followed, the user assumes full responsibility for any resulting damage or consequences. Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.