

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## **SYLOTHIX 51**

### **Product description**

Fine polyethylene fibre for thixotropic thickening of coatings. Normally added 1–3 wt-% into component A of the coating and mixed thoroughly for 5–10 minutes before adding the hardener.

### **Applications**

- Used for stiffening epoxy and acrylic coatings, e.g. in upturns

### **Instructions**

### **Application instructions**

- Normally added 1–3 wt-% into component A of the coating and mixed thoroughly for 5–10 minutes before adding the hardener.

### **Waste handling**

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## Technical information

<b>Type</b>	Powder, fibrous
<b>Colour</b>	White
<b>Package size</b>	3 l (0.3 kg) tin can, 10 kg paper sack
<b>Storage</b>	Store in a dry place

Remember to consult the Maintenance Instructions for Coated Floors and the product Safety Data Sheet on our website at [www.fescon.fi](http://www.fescon.fi), or request a copy by calling +358 9 274 7970. Although the technical details provided in this product description are based on our best knowledge and experience, the information above should always be regarded as indicative. The user is responsible for verifying the suitability of the product for the intended application. If the instructions are not followed, the user assumes full responsibility for any resulting damage or consequences. Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.