

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Updated 19.8.2025 Printed 17.5.2026

PRIMER PLUS



Product description

Fescon Primer PLUS is a water-soluble, synthetic rubber latex with additives improving adhesion. The product is designed for the priming of non-absorbent surfaces before levelling. Not suitable for use together with solvent-based adhesives. For indoor use.

- Ready for use
- For the priming of non-absorbent surfaces
- Drying time about 1 h

Applications

- Natural stones
- Film faced plywood
- Ceramic and glass surfaces
- Steel surfaces
- Quartz vinyl tiles and other such hard floor materials
- For priming Gypsum plaster mix GL on hard and non-absorbent precast concrete surfaces

The product is listed in the portal for building products that can be used in Nordic Swan Ecolabelled buildings.

Instructions

Base

- The substrate must be clean, solid, and dust-free, and vacuumed.
- All dirt, oil, grease, and loose material must be removed. If necessary, the substrate should be roughened.
- The substrate must be sufficiently strong, dimensionally stable, and load-bearing.
- The temperature of the base floor structure must be $> +10^{\circ}\text{C}$.
- Corrosion-sensitive metal surfaces must be protected before priming.

Mixture

- The product is ready-to-use

Applying the primer

- The well-mixed primer is applied as a thin, even layer by brushing (avoid puddles).
- The primer must have dried before further work; its drying time around 1 hour ($+15^{\circ}\text{C}$ / 50% RH).
- Wash tools and equipment with water immediately.

Other considerations

- Not suitable for use together with solvent-based adhesives

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Technical information

Material usage	Approx. 150 g/m ² (approx. 33 m ² /5 kg)
Colour	Blue
Package size	5 kg
Storage	In a closed container, stored in a cool place (not below +6°C), shelf life 12 months. Must not freeze.
Density	1 l = 1.5 kg
Usage temperature	+10°C...+25°C (base floor structure and room temperature)
Drying time	Approx. 1 h (+15°C, RH 50 %)
Thinner	Ready to use
Method of application	Brushing
Transport	Warm transport

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.