

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

Updated 19.8.2025 Printed 6.6.2026

## PRIMER PLUS



### Product description

Fescon Primer PLUS is a water-soluble, synthetic rubber latex with additives improving adhesion. The product is designed for the priming of non-absorbent surfaces before levelling. Not suitable for use together with solvent-based adhesives. For indoor use.

- Ready for use
- For the priming of non-absorbent surfaces
- Drying time about 1 h

### Applications

- Natural stones
- Film faced plywood
- Ceramic and glass surfaces
- Steel surfaces
- Quartz vinyl tiles and other such hard floor materials
- For priming Gypsum plaster mix GL on hard and non-absorbent precast concrete surfaces

**The product is listed in the portal for building products that can be used in Nordic Swan Ecolabelled buildings.**

### Instructions

#### Base

- The substrate must be clean, solid, and dust-free, and vacuumed.
- All dirt, oil, grease, and loose material must be removed. If necessary, the substrate should be roughened.
- The substrate must be sufficiently strong, dimensionally stable, and load-bearing.
- The temperature of the base floor structure must be  $> +10^{\circ}\text{C}$ .
- Corrosion-sensitive metal surfaces must be protected before priming.

#### Mixture

- The product is ready-to-use

#### Applying the primer

- The well-mixed primer is applied as a thin, even layer by brushing (avoid puddles).
- The primer must have dried before further work; its drying time around 1 hour ( $+15^{\circ}\text{C}$  / 50% RH).
- Wash tools and equipment with water immediately.

#### Other considerations

- Not suitable for use together with solvent-based adhesives

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
[www.fescon.fi](http://www.fescon.fi)

### **Waste handling**

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## Technical information

<b>Material usage</b>	Approx. 150 g/m <sup>2</sup> (approx. 33 m <sup>2</sup> /5 kg)
<b>Colour</b>	Blue
<b>Package size</b>	5 kg
<b>Storage</b>	In a closed container, stored in a cool place (not below +6°C), shelf life 12 months. Must not freeze.
<b>Density</b>	1 l = 1.5 kg
<b>Usage temperature</b>	+10°C...+25°C (base floor structure and room temperature)
<b>Drying time</b>	Approx. 1 h ( +15°C, RH 50 % )
<b>Thinner</b>	Ready to use
<b>Method of application</b>	Brushing
<b>Transport</b>	Warm transport

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.