

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

FIREPROOF REPAIRING COMPOUND TTK



Product description

Fescon Fireproof Repairing Compound is a compound with a cement binder, designed for the repairs of cracks and cavities in the fireboxes of household fireplaces.

- Easy to use
- Heat resistance +1300°C
- Layer thickness 5 - 20 mm
- Good workability characteristics

Applications

- Fireplaces, ovens, grills, ground ovens, and their fireboxes and roofs
- Can be used for patching cracks in the shell and jointing fireplaces and sauna stoves

The product is listed in the portal for building products that can be used in Nordic Swan Ecolabelled buildings.

Instructions

Work instructions

Mix around 5 dl of clean, room-temperature water into 2 kg of plaster powder. You can use a straight-tipped trowel, jointing iron or a rubber glove to spread the plaster. In order to ensure adhesion, brush the patched location clean with a steel brush and remove any dust with a damp rag. Use a screwdriver to enlarge the cracks before patching. The durability of the patches is improved, if they are allowed to bind for a couple of days before heating. Be careful not to heat the oven too much the first time.

Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>



Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Updated 20.12.2024 Printed 24.5.2026

Technical information

Water requirement	2.5 dl/kg
Type	Powder
Colour	Grey
Maximum grain size	2.0 mm
Package size	2 kg plastic container
Storage	18 months in the original package in a dry location
Layer thickness	5 - 20 mm
Workability time	1 h

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.