

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## SANDING AGGREGATE HSS



### Product description

Sanding aggregate HSS is a screened and dried product made from crushed aggregate, with a grain size optimized for effective slip prevention. The 3–6 mm grain size ensures excellent traction on pedestrian and vehicle routes. The sanding gravel is low in dust, and its durable grains allow efficient use even in demanding winter conditions. The gravel is dried before being bagged in a plastic sack, ensuring easy handling and usability in freezing weather. The product does not form frozen lumps that would hinder spreading.

- Crushed aggregate, grain size 3–6 mm
- Dried, non-freezing
- Plastic sack protects the product from weather exposure
- Reusable

### Applications

- Sanding and slip prevention
- Surface material for walkways
- Decorative or other garden use

### Instructions

#### Instructions for use

Sanding gravel is used for slip prevention during winter on walkways, yards, driveways, and parking areas. Apply approximately 150 grams per square meter. The product can be spread manually or with a mechanical spreader.

Tip: If the sanding gravel has been stored in a warm place before spreading, it often adheres better to the surface, improving traction.

#### Additional information

The product can be reused after cleaning.

#### Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>



Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
[www.fescon.fi](http://www.fescon.fi)

## Technical information

**Maximum grain size**

3 - 6 mm

**Package size**

20 kg and 1000 kg

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.