Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

WATERPROOFING STRIP



Product description

Fiber-reinforced waterproofing strip used in Fescon WS- and Waterproofing systems for reinforcing corners, edges, and joints. The 0.1 x 25 m waterproofing strip can be used for penetrations with a diameter of 10–40 mm. The 0.2 x 25 m waterproofing tape is suitable for penetrations with a diameter of 55–110 mm. The 1.0 x 10 m Waterproofing fabric can also be used for making penetrations and reinforcement pieces. When the waterproofing fabric is used as a drain collar, it is only compatible with the Fescon Waterproofing system

- The strip dimensions are 0.1 x 25 m or 0.2 x 25 m, 10 rolls per box
- Also available as waterproofing membrane 1.0 x 10 m. Not suitable for the Fescoseal A+B waterproofing system

Applications

- Strengthening waterproofing strip used in the Fescon WS and Waterproofing systems
- Suitable for making through-hole pieces up to 110 mm in diameter

The product is listed in the portal for building products that can be used in Nordic Swan Ecolabelled buildings.

Instructions

Installation

- Spread the waterproofing compound into the corners, where two elements meet, and into through-holes. The waterproofing accessories are attached to the wet waterproofing compound. Spread the waterproofing compound thoroughly over the strengthening strips using a brush or roller. Make sure that the strips are fully attached to the waterproofing compound below, with no exposed parts. The strengthening strips must be between two waterproofing compound layers.

Other points to note

- Through-holes can also be made using waterproofing strip 0.1 x 25 m or 0.2 x 25 m or Waterproofing membrane. A waterproofing strip can be used for through-holes with a maximum diameter of 110 mm. Any larger through-holes are made using waterproofing membrane or a drain flange 300 x 300 fibre product. A ready-made drain flange must be used for drains.
- Waterproofing is carried out in accordance with RT cards and RIL guidelines.

Waste handling

Storage and handling of waste
See the separate storage and disposal instructions https://www.fescon.fi/en/material-bank

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Technical information

Colour	White
Package size	Box of 10 rolls
Storage	Store in a warm place, must not freeze
Usage temperature	+10°C...+25°C (base and indoor temperature)
Weight	Waterproofing strip 0.25 kg Waterproofing membrane 0.673 kg
Size	Waterproofing strip 0.1 x 25 m Waterproofing strip 0.2 x 25 m Waterproofing membrane 1.0 x 10 m Thickness approx. 0.5 mm

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.