

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## WATERPROOFING STRIP

### Product description

Fiber-reinforced waterproofing strip used in Fescon WS- and Waterproofing systems for reinforcing corners, edges, and joints. The 0.1 x 25 m waterproofing strip can be used for penetrations with a diameter of 10–40 mm. The 0.2 x 25 m waterproofing tape is suitable for penetrations with a diameter of 55–110 mm. The 1.0 x 10 m Waterproofing fabric can also be used for making penetrations and reinforcement pieces. When the waterproofing fabric is used as a drain collar, it is only compatible with the Fescon Waterproofing system

- The strip dimensions are 0.1 x 25 m or 0.2 x 25 m, 10 rolls per box
- Also available as waterproofing membrane 1.0 x 10 m. Not suitable for the Fescoseal A+B waterproofing system



### Applications

- Strengthening waterproofing strip used in the Fescon WS and Waterproofing systems
- Suitable for making through-hole pieces up to 110 mm in diameter

The product is listed in the portal for building products that can be used in Nordic Swan Ecolabelled buildings.

### Instructions

### Installation

- Spread the waterproofing compound into the corners, where two elements meet, and into through-holes. The waterproofing accessories are attached to the wet waterproofing compound. Spread the waterproofing compound thoroughly over the strengthening strips using a brush or roller. Make sure that the strips are fully attached to the waterproofing compound below, with no exposed parts. The strengthening strips must be between two waterproofing compound layers.

### Other points to note

- Through-holes can also be made using waterproofing strip 0.1 x 25 m or 0.2 x 25 m or Waterproofing membrane. A waterproofing strip can be used for through-holes with a maximum diameter of 110 mm. Any larger through-holes are made using waterproofing membrane or a drain flange 300 x 300 fibre product. A ready-made drain flange must be used for drains.
- Waterproofing is carried out in accordance with RT cards and RIL guidelines.

### Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## Technical information

<b>Colour</b>	White
<b>Package size</b>	Box of 10 rolls
<b>Storage</b>	Store in a warm place, must not freeze
<b>Usage temperature</b>	+10°C...+25°C (base and indoor temperature)
<b>Weight</b>	Waterproofing strip 0.25 kg Waterproofing membrane 0.673 kg
<b>Size</b>	Waterproofing strip 0.1 x 25 m Waterproofing strip 0.2 x 25 m Waterproofing membrane 1.0 x 10 m Thickness approx. 0.5 mm

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.