

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

Updated 19.8.2025 Printed 4.6.2026

## PRIMER KP



### Product description

Water-soluble Fescon Primer KP is used in the Fescon WS and Fescoseal A+B waterproofing systems. For indoor use.

- Pretreatment of substrate before waterproofing
- Improves adhesion
- Brushable



### Applications

- Fescon WS and Fescoseal A+B waterproofing systems
- Concrete and cement-based filler substrates
- Building boards suitable for wet spaces

**The product is listed in the portal for building products that can be used in Nordic Swan Ecolabelled buildings.**

### Instructions

#### Base

- The substrate must be clean, dust-free, solid and immobile
- Loose layers, cement paste, and any other impurities must have been removed mechanically to ensure adhesion.
- The subfloor structure must be more than +10°C.
- When using Fescon WS waterproofing compound, the substrate's relative humidity must be < 90%, with Fescoseal A+B waterproofing compound < 95%

#### Mixing

- Concrete and cement-based levelling compounds: 1 part of primer and 3 parts of water
- Substrates that do not tolerate moisture, such as gypsum boards on floors and wood substrates: Not to be thinned.
- Mix the product before use by turning the package avoid shaking.

#### Application

- The primer is spread thinly using a brush. Fescon primer must not be applied so much that it creates puddles.
- The primer must be dry before the waterproofing compound or leveling compound is spread (1–4 hours, depending on the conditions).
- Highly absorbent substrates (such as in-situ cast concrete floors or renovated floors) are primed twice. The first layer with a ratio of 1:5 (1 part primer, 5 parts water), and the second layer with a ratio of 1:3.
- Wash tools and equipment with water immediately.

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
[www.fescon.fi](http://www.fescon.fi)

## Other points to note

- When using building boards in wet spaces, check the priming instructions from the manufacturer.

## Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

## Technical information

### Material usage

Cement-based leveling compound substrates:  
ready mixture (ratio 1:3) approx. 10<sup>2</sup>/l  
Concrete substrates cast in situ: ready mixture (ratio 1:3)  
approx. 6 m<sup>2</sup>/l  
Gypsum board and wood substrates (undiluted): approx. 7m<sup>2</sup>/l

<b>Type</b>	Liquid
<b>Package size</b>	5 l and 10 l
<b>Storage</b>	In a cool place, not below +6°C, in a tightly closed original container for up to 1 years
<b>Density</b>	1 l = 1 kg
<b>Usage temperature</b>	+10°C...+25°C (base and indoor temperature)
<b>Drying time</b>	1-4 h depending on the conditions
<b>Thinner</b>	Water
<b>Method of application</b>	Brushing
<b>Transport</b>	Warm transport

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.