Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

DEEPLY PENETRATING PRIMER



Product description

Fescon Deeply Penetrating Primer is a water-soluble, solvent-free, almost odourless, colourless primer with acrylic polymer resin binder for indoor and outdoor use. Used as a primer for Silicone resin paint and Fescosan-Facade paint on highly absorbent and/or weak mineral substrates.

- Milky, colourless after drying
- Good penetration depth
- Reinforces the base
- Solvent-free
- Alkali-resistant
- Permeates water vapour
- High diffusion

Applications

- Masonry structures
- Lime-cement and cement mortar renders
- Concrete surfaces

Instructions

Base

- The substrate must be intact and dry.
- Remove dirt, dust, cement paste and all loose material from the base.

Work instructions

- Spread the well-mixed primer into a thin, even layer do not thin by more than 30%.
- Work with a brush or a sprayer (nozzle 0.18-0.28 mm). The best result can be achieved by spreading the product with a brush.
- Can be overpainted after 4-5 hours, depending on the conditions.
- Wash tools and equipment with water immediately after use.

Waste handling

Storage and handling of waste
See the separate storage and disposal instructions https://www.fescon.fi/en/material-bank

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Technical information

Material usage	Smooth, normally absorbent plastering around 170 ml/m^2
Type	Liquid
Package size	10 l
Storage	Must be protected from frost. Do not store at a temperature of over +25°C
Density	1.01 g/cm^3
Lowest usage temperature	+5°C
Drying time	4-5 h depending on the conditions
Thinner	Water
Method of application	Brush, roller, spray
Transport	Warm transport
VOC content	Max. 30 g/l EU limit value for the product A/h 30 g/l (2010)

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.