

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

Updated 24.9.2025 Printed 22.5.2026

## DEEPLY PENETRATING PRIMER

### Product description

Fescon Deeply Penetrating Primer is a water-soluble, solvent-free, almost odourless, colourless primer with acrylic polymer resin binder for indoor and outdoor use. Used as a primer for Silicone resin paint and Fescosan-Facade paint on highly absorbent and/or weak mineral substrates.

- Milky, colourless after drying
- Good penetration depth
- Reinforces the base
- Solvent-free
- Alkali-resistant
- Permeates water vapour
- High diffusion

### Applications

- Masonry structures
- Lime-cement and cement mortar renders
- Concrete surfaces

### Instructions

#### Base

- The substrate must be intact and dry.
- Remove dirt, dust, cement paste and all loose material from the base.

#### Work instructions

- Spread the well-mixed primer into a thin, even layer do not thin by more than 30%.
- Work with a brush or a sprayer (nozzle 0.18-0.28 mm). The best result can be achieved by spreading the product with a brush.
- Can be overpainted after 4-5 hours, depending on the conditions.
- Wash tools and equipment with water immediately after use.

#### Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>



Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

Updated 24.9.2025 Printed 22.5.2026

## Technical information

<b>Material usage</b>	Smooth, normally absorbent plastering around 170 ml/m <sup>2</sup>
<b>Type</b>	Liquid
<b>Package size</b>	10 l
<b>Storage</b>	Must be protected from frost. Do not store at a temperature of over +25°C
<b>Density</b>	1.01 g/cm <sup>3</sup>
<b>Lowest usage temperature</b>	+5°C
<b>Drying time</b>	4-5 h depending on the conditions
<b>Thinner</b>	Water
<b>Method of application</b>	Brush, roller, spray
<b>Transport</b>	Warm transport
<b>VOC content</b>	Max. 30 g/l EU limit value for the product A/h 30 g/l (2010)

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.