

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

Updated 17.2.2025 Printed 20.6.2026

## WATERPROOFING ACCESSORIES FS

### Product description

Waterproofing accessories FS can be used in all Fescon waterproofing systems. The product family includes: waterproofing strip, inner and outer corners, and through-hole flanges. The waterproofing compounds are made of butyl, with a surface made of polypropylene fabric for extra strength.



- The through-hole flange must be one size smaller than the hole to be waterproofed. FS-L 70 is suited for a 110 mm sewer pipe, FS-L 55 for 75 mm pipes, FS-L 40 for tap angle boxes and 50 mm pipes, FS-L 23 for 32 mm pipes, and FS-L 10 for smaller through-holes.
- Waterproofing strip FS-N is 120 mm wide. The length of inner and outer corners is 135 mm in both directions; the total width of the floor and wall is 120 mm.
- Waterproofing strip FS-N is suitable for airtightness repairs together with Fescoseal A+B.

### Applications

- For all Fescon waterproofing systems
- Through-holes
- Where the wall and floor meet
- Strengthening of inner and outer corners

### Instructions

### Installation

- Spread the waterproofing compound into the corners, where two elements meet, and into through-holes. FS waterproofing accessories compatible with the system are attached to the wet waterproofing compound. Spread the waterproofing compound thoroughly over the strengthening strips using a brush or roller. Make sure that the strips are fully attached to the waterproofing compound below, with no exposed parts. The strengthening strips must be between two waterproofing compound layers.

### Other points to note

- Waterproofing is carried out in accordance with RT cards and RIL guidelines.

### Waste handling

Storage and handling of waste

See the separate storage and disposal instructions <https://www.fescon.fi/en/material-bank>

Hämeenkatu 9  
05800 HYVINKÄÄ  
Tel. 020 789 5900  
www.fescon.fi

Updated 17.2.2025 Printed 20.6.2026

## Technical information

<b>Package size</b>	10 rolls/box
<b>Storage</b>	Store in a warm place. The product must not freeze.
<b>Usage temperature</b>	+10°C...+25°C (base and indoor temperature)
<b>Size</b>	FS-N tape 120 mm x 25 m Outer and inner corner 135 x 135 x 120 mm Thickness approx. 0.6- 1.0 mm depending on the product

Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.