Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

NANTEN ANTI-SLIP



Product description

Polyethylene beads for mixing into varnishes, paints, or coatings. Available in three different grain sizes: 0.100 mm, 0.250 mm and 0.500 mm.

Applications

- Used as an anti-slip agent in wet areas and on inclined surfaces, such as spas, swimming pools, shower rooms, changing rooms, and ramps

Instructions

Instructions for use

Mix into varnish, paint, or coating. For example, use at 1.5–15% by weight. The ready-to-use mixture is applied by roller onto the finished coating/paint film.
1 dl 100 = 96 g
1 dl 250 / 500 = 128 g

Waste handling

Storage and handling of waste
See the separate storage and disposal instructions https://www.fescon.fi/en/material-bank

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Technical information

Type	Coarse powder
Colour	White
Package size	0.5 kg metal can
Storage	Storage in a dry place, at room temperature
Density	100, 0.96 g/cm^3 250 1.28 g/cm^3 500 1.28 g/cm^3

Remember to consult the Maintenance Instructions for Coated Floors and the product Safety Data Sheet on our website at www.fescon.fi, or request a copy by calling +358 9 274 7970. Although the technical details provided in this product description are based on our best knowledge and experience, the information above should always be regarded as indicative. The user is responsible for verifying the suitability of the product for the intended application. If the instructions are not followed, the user assumes full responsibility for any resulting damage or consequences. Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.