Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

COLOURED SAND

Product description

Coloured, coated quartz sand. Available in single colours and ready-made colour mixes. See the colour samples in the Nanten colour chart for trowelable coatings. Grain size 0.6–1.2 mm (white and grey also 0.3–0.8 mm as well as mix 180, 380 and 480).

Applications

- Used as fill sand in trowelable acrylic and epoxy coatings

Waste handling

Storage and handling of waste
See the separate storage and disposal instructions https://www.fescon.fi/en/material-bank

Hämeenkatu 9
05800 HYVINKÄÄ
Tel. 020 789 5900
www.fescon.fi

Technical information

Maximum grain size	Grain size 0.6–1.2 mm (white and grey also 0.3–0.8 mm as well as mix 180, 380 and 480)
Package size	25 kg

Remember to consult the Maintenance Instructions for Coated Floors and the product Safety Data Sheet on our website at www.fescon.fi, or request a copy by calling +358 9 274 7970. Although the technical details provided in this product description are based on our best knowledge and experience, the information above should always be regarded as indicative. The user is responsible for verifying the suitability of the product for the intended application. If the instructions are not followed, the user assumes full responsibility for any resulting damage or consequences. Limitation of liability, product use notes and restrictions: Please familiarize yourself with Fescon Oy's general terms of delivery and the design and work instructions related to the product.